ACCESSORIES AND PARTS
240.630.00.1

CHICAGO FAUCETS

a Geberit company

Product Type

Transformer Plug-in - Single-use

Features & Specifications

• Class 2A Transformer
• Standard 2 Prong 115V Outlet
• Input Voltage 120VAC 60Hz
• Output Voltage 12VAC
• Output Current 50mA
• Short Circuit (Thermal Cutout) Protection
• CFNow! Item Ships in 5 Days

Warranty

• 1-Year Manufacturing Material Defects Warranty

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

[ ] Submitted as Shown   [ ] Submitted with Variations

Date _____

Architect/Engineer Specification

Chicago Faucets No. 240.630.00.1, Transformer Plug-in - Single-use.Class 2A Transformer. Standard 2 Prong 115V Outlet. Input Voltage 120VAC 60Hz. Output Voltage 12VAC. Output Current 50mA. Short Circuit (Thermal Cutout) Protection. .

Operation and Maintenance

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning the product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at www.chicagofaucets.com.

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.

Last Revision: 06/06/2012 • Date Printed: 04/11/2013 • Product specifications subject to change without notice