

**Grundfos EF25 Effluent Pumps**



**Applications:**

- Gray Water Pumping
- Septic Tank Effluent
- STEP Systems
- Water Transfer
- Dewatering
- Basement Sumps

**Features & Benefits:**

- Lightweight
- Corrosion resistant
- Continuous duty when fully submerged
- Discharge size 1-1/4" FNPT and 3/4" adjustable hose fitting (included)

Grundfos EF25 Dewatering Utility Pump								
Head (ft)	2'	4'	6'	8'	10'	12'	14'	16'
Flow (GPM)	26	23.5	20.5	17.5	14	10.5	6.5	2.5

Grundfos KP/AP Sump Pumps							
Product Number	Grundfos Number	Max. Solids (in)	HP	Voltage	Cord Length (ft)	Control	Approx. Wt. (lbs)
EF25	96001478	1/4	1/4	115	8	Manual	7

**Grundfos KP & AP Sump Pumps**



KP Series

**Applications:**

- Basement Sumps
- Dewatering
- Water Transfer

**Features:**

- Lightweight
- Corrosion Resistant  
Stainless Steel
- Continuous Duty
- Minimum pumping Level:  
KP: 1/2"  
AP: 1-3/8"



AP Series

Grundfos KP/AP Sump Pumps						
MODEL	GPM @ Total Head					
	5'	10'	15'	20'	25'	30'
KP150	35	25	12	23	7	-
KP250	50	42.5	33.5	24	7.5	-
AP12	71	64	55	44	31	15

Grundfos KP/AP Sump Pumps								
Product Number	Grundfos Number	Discharge Size (FNPT)	Max. Solids (in)	HP	Control	Voltage	Cord Length (ft)	Approx. Wt. (lbs)
KP150	011DC001	1-1/4	3/8	1/4	Manual	115	10	14
KP250	012DC001	1-1/4	3/8	1/3	Manual	115	10	18
AP12	96023926	1-1/2	7/16	1/2	Manual	115	10	20