

JARD Pressure Switches

MARS SERIES **339**



Fixed Setting Pressure Controls High Pressure Cut-Outs

JARD offers the most complete line of high pressure cut-outs available.

Features:

- Tamper proof construction
- Direct mounting on tubing

Specifications:

- Contacts rated at 6 amps, 24-240 volts
- 1/4" female flare S.A.E. mounting
- 18" leads
- UL & CSA recognized

High Pressure Cut-Outs, Open on Pressure Rise, Automatic Reset, Normally Closed

FORMER MARS2 NO.	JARD NO.	DESCRIPTION	OPENING PRESSURE	RESET PRESSURE	MOUNTING
33954	43922	200/150 HP Open on rise	250	150	1/4" Female Flare Fitting S.A.E. Mounting
33910	43924	275/195 HP Open on rise	275	195	1/4" Female Flare Fitting S.A.E. Mounting
33955	43925	300/200 HP Open on rise	300	200	1/4" Female Flare Fitting S.A.E. Mounting
33913	43926	325/225 HP Open on rise	325	225	1/4" Female Flare Fitting S.A.E. Mounting
33916	43920	350/245 HP Open on rise	350	245	1/4" Female Flare Fitting S.A.E. Mounting
33956	43927	350/250 HP Open on rise	350	250	1/4" Female Flare Fitting S.A.E. Mounting
33919	43928	375/275 HP Open on rise	375	275	1/4" Female Flare Fitting S.A.E. Mounting
33957	43929	400/200 HP Open on rise	400	200	1/4" Female Flare Fitting S.A.E. Mounting
33922	43930	400/280 HP Open on rise	400	280	1/4" Female Flare Fitting S.A.E. Mounting
33958	43931	400/300 HP Open on rise	400	300	1/4" Female Flare Fitting S.A.E. Mounting
33925	43932	425/300 HP Open on rise	425	300	1/4" Female Flare Fitting S.A.E. Mounting
	43933	425/325 HP Open on rise	425	325	1/4" Female Flare Fitting S.A.E. Mounting
33959	43934	450/250 HP Open on rise	450	250	1/4" Female Flare Fitting S.A.E. Mounting
	43965	590/418 HP Open on rise	590	418	1/4" Female Flare Fitting S.A.E. Mounting
	43935	600/475 HP Open on rise	600	475	1/4" Female Flare Fitting S.A.E. Mounting

JARD