Plumbing & Piping Products

MARS SERIES 954

Silver Brazing Flux Paste

- · Powerful cleaning action reduces waste of expensive silver solders
- Packed in break-resistant plastic jars
- Use with torch, furnace, resistance or induction heating
- Meets Mil. Spec. MIL-F-4883
- Certified by NSF to meet ANSI/NSF Std. 61 for use on potable water
- Temperature range: 1000° F to 1700° F (538° C to 927° C)

MARS	DESCRIPTION	MARS	CASE
NO.		PACK	QTY.
95448	2 oz.	48	48
95449	6 oz. w/brushcap	24	24

Regular Soldering Flux Liquid

- · Contains no zinc chloride or other heavy metal chloride
- · Non-acid, non-toxic, lead free
- Use with new lead-free, tin/silver, plus 40/60, 50/50, 60/40 and 95/5 solders
- · For high speed production and mechanized soldering equipment
- For use on copper, galvanized iron, sheet lead, zinc, nickel, tin, silver, mild steel, terne plate, malleable iron
 Packed in break resistant plastic bottles

MARS NO.	DESCRIPTION	MARS PACK	CASE QTY.
95445	1 qt.	12	12

Aluminum Flux Paste & Solder Kit

- · Complete repair kit for tradesmen and repairmen
- Solders aluminum easily
- For repairing aluminum evaporators and tubing, ducts, and gutters

•	AISO SOIDE	ers aluminum to copper • Blister carded for imp	uise sales		
	MARS NO.	DESCRIPTION	MARS PACK	CASE QTY.	
	95454	1 oz. of alum. flux and 1/2 oz. of #60 solder	12	12	

Flux-Rite 90[®] Flux

- Meets ASTM B-813 · Completely water soluble for faster flushing from pipe lines
- Super detergent action cleans as it solders Non-acid, non-toxic, lead-free
- Contains no zinc chloride Use with all common soft solders including: tin-silver,96/4, 94/6, 95/5, 50/50, 40/60 and 60/40
- For use on copper, brass, galvanized iron, lead, zinc, tin, silver, nickel, mild steel, terne plate, and malleable iron

MARS	DESCRIPTION	MARS	CASE
NO.		PACK	QTY.
95456	4 oz.	24	24

Visu-Glow[®] Leak Detector

- · High visibility, fluorescent color shows brightly, even in dimly lit places
- · High viscosity, stays on vertical surfaces · Makes it easy to find leaks
- Temperature range: 15° F to 200° F (-9° C to 93° C) Safe for oxygen
- Non-corrosive, non-toxic

MARS	DESCRIPTION	MARS	CASE
NO.		PACK	QTY.
95462	8 oz.	24	24

Sure-Check[®] All Temperature Leak Detector

- All temperature formula: -55° F to 200° F (-48° C to 93° C)
- Ultra-sensitive, long-lasting bubbles · Available in handy spray bottle
- Fluorescent for improved visibility · Safe for oxygen
- Non-corrosive, non-toxic Green liquid

	en e en inquita		
MARS	DESCRIPTION	MARS	CASE
NO.		PACK	QTY.
95466	1 pint	24	24
95468	1 quart	12	12



SI-84

The largest selection of motors, components and accessories for the HVAC/R Industry

