

Drwa. 1

●42-42-0420

SWITCH BUTTON KIT CONTAINS:

42-42-0430	Push Button - GREEN
42-42-0435	Push Button - YELLOW
42-42-0440	Push Button - WHITE (CLEAR)
42-42-0445	Push Button - AMBER
42-42-0450	Push Button - Push Button Blank

DRILL RECEPTACLE

SPEED DIAL

PANEL OPERATIONAL CHECK LIST

1. SET SPEED DIAL TO THE FULL-ON POSITION
(ROTATE CLOCKWISE UNTIL DIAL KNOB STOPS)
2. SET UP
A) PLUG A DRILL INTO THE DRILL RECEPTACLE
B) APPLY 120 VAC
3. PRESS THE "FWD" BUTTON AND THEN PRESS THE "REV" BUTTON
RESPONSE - DRILL DOES NOT ROTATE
4. PRESS THE "OFF-RESET" BUTTON AND THEN THE "MAGNET-ON" BUTTON
RESPONSE - "MAGNET-ON" BUTTON WILL LIGHT, DRILL DOES NOT ROTATE
5. PRESS THE "FWD" BUTTON AGAIN
RESPONSE - DRILL ROTATES IN FORWARD DIRECTION
6. PRESS THE "OFF-RESET" BUTTON
RESPONSE - DRILL ROTATION STOPS
7. PRESS THE "REV" BUTTON
RESPONSE - DRILL ROTATES IN THE REVERSE DIRECTION
8. PRESS THE "OFF-RESET" BUTTON
RESPONSE - DRILL ROTATION STOPS
9. PRESS THE "FWD" BUTTON AND THEN THE "MAGNET-OFF" BUTTON
RESPONSE - DRILL ROTATES IN FORWARD DIRECTION AND "MAGNET-ON" BUTTON AND "FWD" BUTTON ARE LIT
10. PRESS THE "REV" AND THEN THE "MAGNET-OFF" BUTTON
RESPONSE - DRILL ROTATES IN REVERSE DIRECTION AND REVERSES WITHOUT "PLUGGING" THE MOTOR. "MAGNET-ON" AND "REV" BUTTONS ARE LIT
11. PRESS THE "OFF-RESET" BUTTON
RESPONSE - DRILL ROTATION STOPS AND "MAGNET-ON" BUTTON STAYS LIT
12. PRESS THE "MAGNETIC-OFF" BUTTON
RESPONSE - "MAGNET-ON" BUTTON LAMP EXTINGUISHES
13. PRESS THE "MAGNET-OFF" BUTTON AND HOLD FOR APPROXIMATELY TWO SECONDS
RESPONSE - "MAGNET-OFF" BUTTON GLOWS RED

