




Specifications: Serenity & Stretch Models

Dimensions	Serenity: 33.5"W x 29.5"H x 36.5"L Stretch: 33.5"W x 29.5"H x 40.5"L
Door Swing	Right or Left Hand
Tub construction	Marine grade gel coat fiberglass with fire retardant properties
Tub surface	"Kohler" white - CSA approved bath gel coat supported with fire retardant fiberglass
Warranty	*5 year warranty on bathtub, door handle, and latching mechanism- 1 year parts and labor, remaining 4 years parts only. *One year warranty on hydrotherapy components, hand-held shower, drains and booster seat *Lifetime warranty on door seal
Approvals	CSA  UL/ANSI
Door clearance required	30.0" - 28.0" with door jambs removed
Length	Serenity: will replace a 5 ft. bathtub Door closed: 36.5" With drip tray: 40.5" Door open: 59.5" Stretch: Door closed: 40.5" With drip tray: 44.5 " Door open: 63.5"
Width	Serenity & Stretch 33.5"
Height	Serenity & Stretch 29.5"
Seat height	Serenity 10.5" with 4" removable booster seat Stretch 14.5" – no booster seat provided
Door opening width	16.5"
Step in height	4.25"
Booster Seat	Serenity model only – 3" and 4" height
Optional Faucet panel	Pre-plumbed Moen Posi-Temp TL 183 faucet, includes tub spout with diverter and pop up drain & hand-held shower

Weight	200lbs Shipping weight 285 lbs
Capacity	Serenity: 300 lbs or up to 6 ft tall Stretch: over 300 lbs and/or over 6 ft. tall
Water Capacity	Serenity: 20 – 25 gallons Stretch: 25- 30 gallons
Door seal	Extruded silicone rubber gasket
Door lock	Stainless steel cantilever mechanism
Hinges	Stainless steel
Access Panels	Measures: 8" X 8" Located on 3 sides of the shroud Access is also possible from below the bathtub
Trim Boards	Laminated press board with water proof coating
Drain Size & Location	1.5", ABS connection When viewed from outside the tub, drain is always on the right hand side, regardless of door swing
Drain System	Cable driven
Drain size (drip-tray)	1.25"
Jets	Options: *Soaker Tub with no jets *12 Warm Air Jets
Water Pump/Air Blower	CSA, UL approved Model V – Water massage ¾ HP, 120 V, 60 HZ Model A - Air massage 9.5 A 120 V, 60 HZ
Power Input	110/120 V – 15A GFI outlet required for jetted tubs
Piping	PVC flex
Optional Corner Skirt & Trim Boards	3 corner finishing skirt (slip-resistant surface) with trim boards will finish off the area where a standard bathtub was removed
Optional Platform	Acrylic reinforced with fiberglass Allows for shallow drain application 2 pieces totaling 60"L x 34" W x 5"H Slip-resistant surface