



Single Threshold Shower Floors

Veritek® SHOWER FLOORS

With Fit-Flo Drain

Manufactured from Veritek®
(see page 2 for detailed information)

WARRANTY
Limited Lifetime – Residential
Limited 5-year – Commercial

FEATURES

- Will not mold or mildew, no grout to clean
- Coordinates with Swanstone shower and bath walls, vanity tops and wainscoting
- Pebbled, slip-resistant surface
- Made of Veritek with no surface coating to chip or crack

Model	Nominal Size	Rough-In Dimensions			
		A	B	C	D
R-3232	32" x 32"	32-3/8"	32-3/16"	16-3/16"	16-3/16"
R-3248	32" x 48"	48-3/8"	32-3/16"	24-3/16"	16-3/16"
R-3260	32" x 60"	60-3/8"	32-3/16"	30-3/16"	16-3/16"
R-3442	34" x 42"	42-3/8"	34-3/16"	21-3/16"	17-3/16"
R-3448	34" x 48"	48-3/8"	34-3/16"	24-3/16"	17-3/16"
R-3454	34" x 54"	54-3/8"	34-3/16"	27-3/16"	17-3/16"
R-3460	34" x 60"	60-3/8"	34-3/16"	30-3/16"	17-3/16"
R-3636	36" x 36"	36-3/8"	36-3/16"	18-3/16"	18-3/16"
R-4236	42" x 36"	36-3/8"	42-3/16"	18-3/16"	20-3/16"
R-4242	42" x 42"	42-3/8"	42-3/16"	21-3/16"	21-3/16"

Model	A	B	C	D
R-3232	32"	32"	16"	16"
R-3248	48"	32"	24"	16"
R-3260	60"	32"	30"	16"
R-3442	42"	34"	21"	17"
R-3448	48"	34"	24"	17"
R-3454	54"	34"	27"	17"
R-3460	60"	34"	30"	17"
R-3636	36"	36"	18"	18"
R-4236	36"	42"	18"	20"
R-4242	42"	42"	21"	21"

IMPORTANT: Rough-in dimensions are provided for reference only. You must measure the actual shower floor and check local building code requirements before construction of the stud wall.

SPECIFICATIONS

Single Threshold Shower Floors With Fit-Flo Drain

Model	Part	Nominal Size Dimensions	COLORS			
			Ship Wt. Lb.	Ship UPS	Carton Dims. In.	Cu. Ft.
R-3232	FF03232MD	32" D x 32" W (813 mm x 813 mm)	32	–	38 x 37 x 10	9
R-3248	FF03248MD	32" D x 48" W (813 mm x 1219 mm)	49	–	54 x 38 x 10	12
R-3260	FF03260MD	32" D x 60" W (813 mm x 1524 mm) - Center drain	56	–	66 x 37 x 10	15
R-3442	FF03442MD	34" D x 42" W (864 mm x 1067 mm)	46	–	48 x 40 x 10	12
R-3448	FF03448MD	34" D x 48" W (864 mm x 1219 mm)	47	–	54 x 39 x 10	13
R-3454	FF03454MD	34" D x 54" W (864 mm x 1372 mm)	55	–	60 x 40 x 10	14
R-3460	FF03460MD	34" D x 60" W (864 mm x 1524 mm)	63	–	66 x 40 x 10	16
R-3636	FF03636MD	36" D x 36" W (914 mm x 914 mm)	40	–	42 x 41 x 10	10
R-4236	FF04236MD	42" D x 36" W (1067 mm x 914 mm)	44	–	47 x 42 x 10	12
R-4242	FF04242MD	42" D x 42" W (1067 mm x 1067 mm)	53	–	48 x 48 x 10	14

Kit Includes: One code approved compression molded Veritek® shower floor with molded-in Fit-Flo drain and complete installation instructions.

Packaging: Each floor packed in a rectangular carton.

STANDARDS AND RATINGS

Class B fire rating

American National Standard Institute—ANSI Z124.1.2–2005

International Association of Plumbing and Mechanical Officials (IAPMO)—listed

cUPC listed—Certified to CSA Standard B45 by IAPMO

American Society for Testing and Materials

National Electrical Manufacturers Association

SUPPORT DOCUMENTS

Installation instructions available on line at www.swanstone.com

MADE IN USA.

MAINTENANCE AND CLEANING INFORMATION

Everyday cleaning with liquid cleaners such as **Dow** or **Lysol** foaming bubbles, **Top Job**, **Mr. Clean** or similar type products with a sponge or **Mr. Clean Magic Eraser**. To remove hard water stains or mineral build-up, scale removers such as **Lime Away**, **Rust-out** or **Whink** are recommended. Abrasive cleaners are not recommended on shower bases because they are designed with high sheen areas to help prevent soap scum build up. Prolonged scrubbing will dull the surface over time and promote build-up and soap scum. **Do not** use "leave on" cleaning products such as the Automatic Shower Cleaner. Prolonged contact with harsh chemicals could have an adverse reactive over time and discolor your surfaces. **Do not** use cleaning agents that caution use on acrylic, polyester or plastics.

TUB & SHOWER