
4-150

Senior institutional shower head with semi-adjustable spray. Spray face is non-clogging and non-removable. Anchor plate mounting bracket, all mounting fasteners are vandal resistant recessed hex socket type.

Suffix A: Anchor plate to simplify mounting on ceramic tile

Suffix B: Back plate and thru bolts for extra thick wall


Standard Installation Head pushes onto mounting bracket and is secured with a single heavy duty Mounting bracket sweats Back view of socket head screw to copper tubing mounting bracket (for maximum vanshowing screw dal proofing fill finish hole locations socket head with wall solder or putty). 7/8" 5/8" 22mm 16mm 5/8" 16mm 1/2" copper supply must protrude 7/8"-22mm from finish wall Wood screws and anchors (supplied) secure mounting bracket to wall The back section of head contains an o-ring that seals on machined diameter of mounting bracketclean and grease mating part




Installation with Anchor Plate — Suffix "A"

before head installation onto mounting bracket.

Installation with Back Plate — Suffix "B"





Anchor plate used for ceramic tile application—plate screws to wall and tile is applied up to sides of plate. Mounting bracket is mounted on finished wall with machine screws into anchor plate

Symmons Industries, Inc. • 31 Brooks Drive • Braintree, MA 02184 (800) 796-6667, (781) 848-2250 • Fax (800) 961-9621, (781) 843-3849 Website: www.symmons.com • Email: customerservice@symmons.com

