



SYMMONS[®] Temptrol[®] II BP Series
the smart choice[™]

Every Symmons Temptrol[®] II tub and shower system features the legendary Symmons Temptrol[®] pressure-balancing mixing valve. Constructed of solid brass, bronze and stainless steel, and featuring a piston that adjusts automatically to instantly and continually equalize or “balance” the hot and cold water pressure as demands are made elsewhere in the plumbing system. Symmons Temptrol[®] puts an end to “Shower Shock” and provides a safe, comfortable shower every time.



Symmons Temptrol[®] II
BP series is available
in this finish:



Polished
Chrome

Tub and Shower Systems

SYMMONS® Temptrol® II BP Series
the smart choice™



BP-56-1

Temptrol II BP Series Pressure-Balancing mixing valve with adjustable stop screw to limit handle turn. Clear-Flo showerhead with arm and flange.

BP-46-2 Valve only



BP-56-2

Temptrol II BP Series Pressure-Balancing mixing valve with adjustable stop screw to limit handle turn. Diverter tub spout, Clear-Flo showerhead, arm and flange.

BP-46-2 Valve only



BP-56-300-B30-V

Temptrol II BP Series Pressure-Balancing mixing valve with lever handle and adjustable stop screw to limit handle turn. Wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, 30" slide bar for hand shower mounting.



BP-56-400-B30-V

Temptrol II BP Series Pressure-Balancing mixing valve with lever handle and adjustable stop screw to limit handle turn. Diverter tub spout, wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, 30" slide bar for hand shower mounting.



BP-56-500-B30-V

Temptrol II BP Series Pressure-Balancing mixing valve with adjustable stop screw to limit handle turn. Lever diverter with integral volume control. Clear-Flo showerhead with arm and flange. Wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, 30" slide bar for hand shower mounting.



BP-56-600-B30-V

Temptrol II BP Series Pressure-Balancing mixing valve with adjustable stop screw to limit handle turn. Lever diverter with integral volume control. Tub spout. Clear-Flo showerhead with arm and flange. Wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, 30" slide bar for hand shower mounting.

Modifications: Suffix X: Integral service stops - allows water shutoff at valve for service • Suffix IPS: 1/2" female IPS connections • Suffix REV: Reverse coring, hot on right, cold on left, for back to back installations • Delete Suffix B30: 2 wall hooks in place of 30" bar • Suffix LR: Lever handle • Suffix LP: Loop handle