



SYMMONS[®] Temptrol[®]
the smart choice[™]

Every Symmons Temptrol[®] tub and shower system features the legendary Symmons Temptrol[®] pressure-balancing mixing valve. Constructed of solid brass, bronze and stainless steel, and featuring a piston that adjusts automatically to instantly and continually equalize or “balance” the hot and cold water pressure as demands are made elsewhere in the plumbing system. Symmons Temptrol[®] puts an end to “Shower Shock” and provides a safe, comfortable shower every time.



Symmons Temptrol[®]
is available in
this finish:



Polished
Chrome

Tub and Shower Systems



S-96-1

Temptrol pressure-balancing mixing valve with **integral volume control** and adjustable stop screw to limit handle turn. Clear-Flo showerhead with arm and flange.

S-86-1 Valve only



96-1

Temptrol pressure-balancing mixing valve with adjustable stop screw to limit handle turn. Clear-Flo showerhead with arm and flange.

86-2 Valve only



S-96-2

Temptrol pressure-balancing mixing valve with combination **integral diverter and volume control** and adjustable stop screw to limit handle turn. Clear-Flo showerhead with arm and flange.

S-86-2 Valve only



96-2

Temptrol pressure-balancing mixing valve with adjustable stop screw to limit handle turn. Clear-Flo showerhead with arm and flange. **Diverter tub spout.**

86-2 Valve only



96-300-B30-L-V

Temptrol pressure-balancing mixing valve with lever handle and adjustable stop screw to limit handle turn. Wall/hand spray, in-line vacuum breaker, flexible metal hose, wall connection and flange. 30" slide bar for hand spray mounting.



S-96-400-B30-L-V

Temptrol Pressure-Balancing mixing valve with lever handle, combination **integral diverter and volume control** and adjustable stop screw to limit handle turn. Tub spout. Wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, 30" slide bar for hand shower mounting.



96-500-B30-L-V

Temptrol pressure-balancing mixing valve with lever handle and adjustable stop screw to limit handle turn. Lever diverter with volume control. Clear-Flo showerhead with arm and flange. Wall/hand spray, in-line vacuum breaker, flexible metal hose, wall connection and flange. 30" slide bar for handspray mounting.



96-600-B30-L-V

Temptrol pressure-balancing mixing valve with lever handle, combination **integral diverter and volume control** and adjustable stop screw to limit handle turn. Lever diverter with volume control. Clear-Flo showerhead with arm and flange. Wall/hand spray, in-line vacuum breaker, flexible metal hose, wall connection and flange. 30" slide bar for hand spray mounting.

Modifications: Suffix X: Integral service stops - allows water shutoff at valve for service • Suffix IPS: 1/2" female IPS connections • Suffix REV: Reverse coring, hot on right, cold on left, for back to back installations • Suffix 231: Super showerhead in place of Clear-Flo head • Suffix SS: Slip spout on any tub and shower unit • Suffix L: Single blade lever handle • Delete Suffix B30: 2 wall hooks in place of 30" bar