

Tub & Hand Shower System S-5304 **Specification Submittal**

Feature Highlights

- Symmons Tub & Hand Shower System with lever handle
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Secondary integral volume control handle
- Wall/hand shower with 5 foot flexible metal hose, in-line vacuum breaker, wall connection and cradle for hand shower mounting
- Standard flow rate is 2.5 gpm (9.5 L/min) *Optional lower flow rate restrictor available*



- Tub spout, brass #T-671
- Polished chrome finish (standard)

Model Numbers

- □ S-5304 Tub & Hand Shower System with Symmons Temptrol® mixing valve p/n S-4002-BODY
- ☐ S-5304-TRM Trim only, mixing valve ordered separately
- ☐ S-4002-BODY Symmons Temptrol® mixing valve without trim
- ☐ S-4002-X-BODY Symmons Temptrol[®] mixing valve without trim. Valve includes integral service stops to allow water shut-off for service

Finish Options / Modifications

Append appropriate -suffix to model number

- -STN Satin nickel
- -BLK Polished graphite
 - Polished chrome (standard finish)

Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05





Options / Modifications

Append appropriate -suffix to model number

- П -IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve
- -X Symmons Temptrol® mixing valve includes П integral service stops to allow water shut-off for service, p/n S-4002-X-BODY. (Option only applies when ordering model S-5304)
- Reverse coring in valve for back to back installations; hot on right, cold on left, (available with -X integral stops only)
- -2.0 2.0 (7.6 L/min) flow rate restrictor
- -1.5 1.5 (5.7 L/min) flow rate restrictor
- L/HS Hand Shower wand not included П (includes hose, in-line vacuum breaker, wall connections and flange only)
- -R Vinyl hose in place of flexible metal hose
 - -6 6 foot hose in place of standard 5 foot hose
 - -QD Quick-disconnect at hand shower wall connection

Warranty

П

П

- Limited Lifetime to the original end purchaser in consumer installations
- 5 years for commercial installations





