THERMAL DYNAMICS. CutSkill.

Plasma Power without the Price

CutSkill® **C-20C Air Plasma Cutting System**

• Fast, Easy Cuts on Most Metals
A favorite for HVAC installations, sheet
metal fabrication, metal art, and home projects,

this machine delivers clean cuts on most metals including stainless steel, aluminum, mild steel copper or brass, with minimum heat input & distortion of metal. It also cuts through rusted, painted or coated surfaces without prior surface preparation.



This inverter based power supply automatically links the unit to primary voltage from 115 to 230 Volts, single phase, 50 or 60 Hz, typically found in most homes and maintenance shops. Weighing just 57 lbs. (26 kg) including the built-in compressor, the C-20C is easy to move from location to location.



Maximum Arc Visibility for Excellent Operator Control

The SureLok® PCH-42ER Torch provides excellent cut performance and cut quality, particularly on sheet metal. These are just some of the important torch features:

- Precision-engineered consumable parts are easy to change and require no tools.
- Ergonomic torch handle is comfortable to hold, especially during extended cutting sessions.
- Robust, flexible, heat resistant Leads
- MaximumLife® parts for better operating costs.

- SureLok electrode eliminates tip wobble found in some torch designs, resulting in a cleaner cut and longer parts life.
- Protective interlock circuitry disables the power supply if torch consumable parts are incorrectly assembled.
- Two modes of operation available standoff cutting or drag cutting.
- Latch feature allows the cutting arc to remain active without constantly depressing the torch switch.
- Full 1-year warranty on repair parts and labor.

System Specifications

C-20C Air Plasma Cutting System

Cut Capacity	Input	Output	Duty Cycle	Panel Indicators	Dimensions	Weight
1/4" (6mm) 115V 3/8" (10mm) 230V	115V +/-10%, 1 ph, 50/60 Hz, 20A 230V +/-10%, 1 ph, 50/60 Hz, 14A	20A @ 115VAC 25A @ 230VAC		AC, Over Temp, Air, Latch	H: 11.0" (279mm) W:10.5" (267mm) L: 15.5" (394mm)	Net Wt. 56.6 lbs. (25.7 kg) Ship Wt. 61.1 lbs. (27.7 kg)



Ordering Information

C-20C Air Plasma Cutting System

Product Description	Catalog No.	
C-20C Plasma System (115V/230V) Includes Power Supply, PCH-42 Torch with 20 ft. (6.1m) Leads, 10 ft. (3m) Input Power Cable & Plug (5-20P), 20 ft. (6.1m) Work Cable & Clamp, 3 Extra Tips and 2 Extra Electrodes, and Operating Manual.	1-1626	
TORCH		
PCH-42ER, 70 deg., 20 ft. (6.1m) Leads	7-4220	
Shield Cup	9-6003	
Tip - 20A	9-6504	
SureLok® Electrode - 40A	9-6542	
Gas Distributor	9-6507	
Torch Head	9-8442	
ACCESSORIES		
Cutting Guide Kit	7-8910	
Single Stage Air Filter	7-7507	
20 ft. (6.1m) Leather Leads Cover	9-1260	



CutSkill® C-20C Air Plasma Cutting System with Built-in Air Compressor



Cutting Guide Kit Cat. No. 7-7501



Single Stage Air Filter Cat. No. 7-7507




Leather Leads Cover Cat. No. 9-1260

Torch Specifications

SureLok PCH-42ER

Torch Head	70 deg.		
Gas Type	Built-in Air Compressor		
Gas Flow	2.3 scfm (61 lpm)		
Pilot Method	CD Start		
Lead Length	20 ft. (6.1m)		





Gas Distributor

Tip



Shield Cup



WORLD HEADQUARTERS: Suite 300, 16052 Swingley Ridge Road • St. Louis, MO 63017 • 636-728-3000



Thermadyne Canada Oakville, Ontario Canada Ph: (1) 905-827-4515

Thermadyne Chile Santiago, Chile Ph: (56) 2-557-2465 Fax: (56) 2-557-5349 Thermadyne Victor Brasil Rio de Janeiro, Brazil Ph: (55) 21-2-485-8990 Fax: (55) 21-2-485-8735

INTERNATIONAL CUSTOMER CARE:

U.S. AUTOMATION CUSTOMER CARE:

CUSTOMER CARE:

Thermadyne Europe Chorley, EnglandPh: (44) 1257-261755
Fax: (44) 1257-224800

90 F1I. (44) 1257-221793 35 Fax: (44) 1257-224800 P.T. Thermadyne Utama Indonesia Cikarann, Indonesia Thermadyne China Shanghai, China Ph: (86) 21-6280-1271 (or 1273) Fax: (86) 21-3226-0955

HERMADYNE_®

Cigweld Australia Melbourne, Australia Ph: (61) 3-9474-7400 Fax: (61) 3-9474-7510

800-752-7621 • FAX 800-221-4401

905-827-9777 • FAX 905-827-9797

866-279-2628 • FAX 316-941-4491

Thermadyne Japan Osaka, JapanPh: (81) 6-4809-8411
Fax: (81) 6-4809-8412

Thermadyne Asia Sdn. Bhd. Kuala Lumpur, Malaysia Ph: (603) 6092-2988 Fax: (603) 6092-1085

Fax: (1) 905-827-3648

Thermadyne Asia/Pacific Pte. Ltd. Singapore Ph: (65) 6832-8066 Fax: (65) 6763-5812

Cikarang, Indonesia Ph: (62) 21-8983-0011 (or 0012) Fax: (62) 21-893-6067

International Customer Care

Oakville, Ontario, Canada

Ph: (1) 905-827-9777 Fax: (1) 905-827-9797