


### Hampton Locking MEDICINE CABINET




#### FEATURES/TYPICAL SPECIFICATIONS

- Recess Mount Installation
  - Wall Opening/Rough-in Dimensions: 14" x 24" x 3"
- One piece drawn steel housing (HY/ST)
  - 26 gauge steel with white, heat cured, acrylic paint finish
- Framed mirror door
  - Extruded polystyrene frame with laminate, decorative foil in oil rubbed bronze finish
  - 3MM float glass mirror door front with clean cut edges
  - 26 gauge steel door back with white, heat cured, acrylic paint finish
- Round magnet with soft plastic white cover located in the door aligns to the cabinet body flange (1 typical)
- 16" piano hinge with 90° stop welded to the door and mechanically fastened to the cabinet body (HG01) (1 typical)
- Non-key retaining cylinder lock, includes 2 brass keys that are unique and numbered
- Reversible for left-hand or right-hand door swing
- 5/32" thick float glass shelves, adjustable (ADJ) (3 typical)
- Mounting hardware included
- Standard Pallet Quantity of 26 units

#### Finishes:

Housing: PT01 — Basic White  
 Mirror: Flat Mirror  
 Frame: ORB—Oil Rubbed Bronze



		Dimensions In Inches									
Model #	Description	A	B	C	D	E	F	G	H	J	K
625N244BZCL	MEDCAB 1DR 15X25 ORB HY/ST	15-13/16	25½	2	5	13½	1	15½	23½	1	0

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by
			Date

\* All models and material specifications are subject to change or withdrawal without notice.