

Mini-Tanks for Point-of-Use or Booster Applications



SHC Series

MINI-TANK
ELECTRIC WATER HEATERS












- > Plugs into standard 120 V outlet
- > 6-Year warranty on tank
- T & P valve included
- > Glass-lined tank
- > Fast recovery
- Lowest stand-by losses in the industry

SHC Mini-Tank Electric Water Heaters

Highly efficient point-of-use mini-tanks from the world leader in hot water technology.





SHC saves space

An SHC mini-tank frees up precious space while providing plenty of hot water for hand washing or kitchen applications. Why store 30 or more gallons of hot water when 6, 4, or even 2.5 gallons are sufficient?

SHC saves water and electricity

Plumbed with cold water and used as a stand-alone supply of hot water, or plumbed with hot water from a remote tank to minimize delays, an SHC always delivers hot water when needed. By putting hot water right where it is used, pipe runs are minimized and water and energy use reduced. The smaller tank coupled with superb insulation reduces stand-by losses especially when compared with larger tank-type water heaters.

Quality product

Stiebel Eltron is known for high quality products, and the SHC is no exception with a six-year warranty on the tank, and a twoyear warranty on all other components.

Commercial | Industrial | Institutional

- Office Buildings
- > Restaurants
- > Stores
- > Gas Stations
- > Malls
- > Schools
- Warehouses
- > Hotels/Motels
- > Food Trucks

Residential

- > Bathroom Sinks > RVs
- > Kitchen Sinks
- > Cabins/Cottages
- > Laundry Areas
- Low Flow Showers

Distributed by:

Installation is quick

With its flat back and included bracket an SHC easily mounts right under or near the sink. Once filled with water it simply plugs into a 120 V outlet. With only an 11 amp current draw, no special wiring is reguired. Lightweight and compact, the SHC saves space, quickly provides hot water right where it is needed.





Save water, space, electricity & money.

Technical Data



<u>ISO 9</u>001



Tested and certified by WOA against NSF/ANSI 372 for lead free compliance

Model	SHC 2.5	SHC 4	SHC 6
Item number	233219	234046	235089
Phase - 60/50 Hz	single	single	single
Voltage	120 v	120 v	120 v
Wattage	1300 w	1300 w	1300 w
Amperage	11.3 A	11.3 A	11.3 A
Nominal water volume	2.65 gal / 10 l	4.0 gal / 15 l	6.0 gal / 22.7 l
Weight empty	15.9 lb / 7.2 kg	19.8 lb / 9.0 kg	26.5 lb / 12.0 kg
Height (includes P&T valve)	18 ¹¹ / ₁₆ " / 475 mm	19³/₄″ / 501 mm	20 ¹ / ₂ " / 520 mm
Width	11" / 280 mm	125/8" / 320 mm	151/8" / 385 mm
Depth	105/8" / 270 mm	12 ¹ /2" / 318 mm	15" / 380 mm
Maximum operating pressure	150 psi / 10 bar	150 psi / 10 bar	150 psi / 10 bar
Maximum adjustable temperature	140°F / 60°C	140°F / 60°C	140°F / 60°C
Recovery time	18 minutes	27 minutes	45 minutes
Standby energy loss @ 131°F / 55°C	0.37 kWh / day	0.39 kWh / day	0.43 kWh / day
Water connections	black steel ½" NPT	black steel ½" NPT	black steel ½ NPT

EBEL ELTRON

17 West Street West Hatfield, MA 01088

TOLL FREE 800.582.8423 PHONE **413.247.3380** FAX 413.247.3369 info@stiebel-eltron-usa.com www.stiebel-eltron-usa.com