

***This unit offers anti-siphon protection and pressure relief valves.***

The freezeless Model 22 hot and cold faucet is designed and intended for year-round hot and cold irrigation and cleaning purposes regardless of outside temperature. Separate hot and cold inlet tubes allow for manually operated temperature control with cross contamination protection. This faucet contains patented pressure relief valves that prevents the faucet from bursting in freezing weather should a hose be accidentally left on. The Model 22 contains an integral backflow protection device and does not require and add-on vacuum breaker.

**Available in two models:**

- Model 22 *Horizontal Mount* - Rough Brass
- Model V22 *Vertical Mount* - Rough Brass for end wall installation


**SPECIFICATIONS:**

- Manufactured under one or more of the following patents: 3,208,715; 3,278,201; 5,590,679; 5,632,303; 6,142,172; 6,532,986 and patents pending
- ASSE 1019 Listed
- CSA, UPC, cUPC Approved
- Not intended for continuous use



**FEATURES:**

- *Patented resetting pressure relief valve prevents the faucet tube from bursting in freezing conditions even if a hose is unintentionally left on.*



- *Built-In Vent Float style Vacuum Breaker*
- *Faucet drains automatically when hose is removed*
- EPDM packing to prevent leaking
- Oval, powder-coated, die cast aluminum handle
- Stainless steel seat - eliminates wire draw
- Standard "O" size seat washer
- Tee Key configuration - (extra charge)
- No-lead solder
- 3/4" male hose thread

**MAX PRESSURE** - 125 p.s.i.

**MAX TEMPERATURE** - 120° F

**INSTALLATION REQUIREMENTS:**

- The faucet length used is to be comparable to what would be used with standard freezeless faucets.
- The inlet connection must be located in a heated area.
- The gap between the house and faucet must be sealed to prevent air leaks.
- The faucet must be installed with a slight downward pitch toward the nozzle.
- Adequate insulation is required around the faucet, wall board and sill plate.

***For Installation / Troubleshooting Instructions go to  
www.woodfordmfg.com or call 1-800-621-6032***

# Freezeless Hot & Cold Wall Faucet Model 22 & V22




Model 22




Model V22


**INLET OPTIONS**




**C INLET  
COMBINATION**  
Copper Sweat Fitting  
1/2" K, L or M Inside  
3/4" M Only Outside




**CP INLET  
COMBINATION**  
1/2" Male Pipe Thread  
1/2" Female Sweat



**CP3 INLET  
COMBINATION**  
3/4" Male Pipe Thread  
3/4" Female Sweat



**P INLET  
COMBINATION**  
1/2" Female Pipe Thread  
3/4" Male Pipe Thread



**PX INLET**  
1/2" PEX Tube Fitting  
**PX3 INLET**  
3/4" PEX Tube Fitting  
**W INLET**  
1/2" Wirsbo PEX Tube Fitting  
**W3 INLET**  
3/4" Wirsbo PEX Tube Fitting


***When ordering, specify model, inlet and wall thickness***



#### RK-PRV-\*

Wall Thickness	Overall Length Dim "A"
RK-PRV-4	5 7/8"
RK-PRV-6	7 7/8"
RK-PRV-8	9 7/8"
RK-PRV-10	11 7/8"
RK-PRV-12	13 7/8"
RK-PRV-14	15 7/8"
RK-PRV-16	17 7/8"
RK-PRV-18	19 7/8"
RK-PRV-20	21 7/8"
RK-PRV-22	23 7/8"
RK-PRV-24	25 7/8"

\*Insert wall thickness  
Example for 10" wall thickness:  
RK-PRV-10



#### MODEL 22 & V22 PARTS LIST


ITEM	PART#	DESCRIPTION
1	30566	Plug Button-H-Red
1a	30565	Plug Button-C-Blue
2	30002	Handle Screw (2)
3	30559	Oval, Die Cast Alum. Handle (2)
4	30059	Packing Nut (2)
5	30560	EPDM Packing (2)
6	30421	Packing Support Washer (2)
7	RK-PRV	Valve Stem Assembly (See chart above)
<i>Note: Valve stems are interchangeable with Model 22 and V22 Head assemblies.</i>		
8	30459	Check Valve (2)
9	30008	Valve Seat Rubber (2)
10	30804	Retainer Screw (2)
11	RK-22VB	Vacuum Breaker Float Kit (Model 22)
12	50012	Tee Key
13	30512	Deep Packing Nut
	RK-22PRV	Repair Kit (metal handles) Includes 1 ea: Items 1, 1a, 11 2 ea: Items 2 - 6, 8 - 10

#### Model 22 & V22 Shipping Weight


Wall Thickness (inches)

4	6	8	10	12	14	16	18	20	22	24
2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4	4.6	4.8

Shipping Wt. Ea. (lbs)



**Model 22**  
**Rough-In Dimensions**



**Model V22**  
**Rough-In Dimensions**

\*Overall Length Dimension: Add wall thickness and inlet option length shown in chart on reverse side.

For more information contact...

## WOODFORD MANUFACTURING COMPANY

2121 Waynoka Road, Colorado Springs, Colorado 80915 • Phone: (800) 621-6032 • Fax: (800) 765-4115

To view our complete product line visit: [www.woodfordmfg.com](http://www.woodfordmfg.com) or email: [sales@woodfordmfg.com](mailto:sales@woodfordmfg.com)

A Division Of WCM Industries, Inc.