

For Commercial Applications

Job Name _____ Item Designation _____
 Job Location _____ Contractor _____
 Engineer _____ Representative _____
 Inlet: P-1/2__ P-3/4 __ CP __ C __ Finish: CH __ BR __ PC__

For Non Freezing Areas

Woodford Model 26 Backflow Protected Wall Faucet

The Model 26 is a backflow protected wall faucet designed for use in mild climate areas. The Model 26 is intended for irrigation purposes and is designed to blend in with modern architecture for installation on homes, service stations, churches, motels, drive-in restaurants, etc.

Features:

- EPDM Packing
- Adjustable brass packing nut
- Standard "O" size valve seat washer
- Polycarbonate wheel handle and loose tee key
 Optional: Metal wheel handle
- 4 inlet options

Specifications:

PATENTED HIGH FLOW DOUBLE CHECK BACKFLOW PREVENTER

- NIDEL® Model 50HF with 3/4 inch male hose thread
- ASSE Standard 1052 approved
- Field Testable
- Two Independent Check Valves
- Drains automatically when hose is removed
- No spray back
- **Maximum Working Pressure:** 125 p.s.i.
- **Maximum Temperature:** 120° F

Specify as follows:

Wall faucet shall be a Woodford Model 26 for non-freezing areas with ASSE 1052 approved NIDEL® Model 50HF high flow double check backflow preventer. 3/4" hose connection (specify type of inlet). Exterior finish to be Chrome Plated (options: Rough Brass or Polished Chrome). Loose tee key to be furnished with each faucet. Intended for irrigation purposes. Inlet Type _____

Model & Inlet



26P-1/2
1/2" FPT

26P-3/4
3/4" FPT



26CP
Combination
1/2" Copper Tube
1/2" MPT



26C
Combination
1/2" Copper Tube
1/2" MPT




Optional Tee Key
Included

Exterior Finish:

Standard - Chrome (CH)
 Optional - Rough Brass (BR) or Polished Chrome (PC)

Rough-In Dimensions - Typical



WOODFORD MANUFACTURING COMPANY

2121 WAYNOKA ROAD
 COLORADO SPRINGS, CO 80915
 Phone (800) 621-6032 Fax (800) 765-4115
 Website: www.woodfordmfg.com
 Email: sales@woodfordmfg.com