
s Ρ Ν S Н Ε С F С Α Т 0 Ε I I Ĩ Ε









Two Handle Bar Faucet

DESCRIPTION

- $\cdot\,$ Metal construction with chrome plated finish
- · 1/2" IPS connections
- · Six (6) individual boxes per master carton
- \cdot Handles withstand aggressive scrubbing cleaners

OPERATION

- · Lever-style handles
- Hot side: Turn counterclockwise to open (clockwise to close)
- Cold side: Turn clockwise to open (counterclockwise to close)
- · Will operate with less than 5 lbs. of torque
- No grasping motion required to operate the faucet handles

FLOW

Aerator limited to 2.2 gpm (8.3 L/min)

CARTRIDGE

- · Ceramic disc technology
- $\cdot\,$ Non-metallic, non-ferrous, and brass material
- · Single body construction for easy replacement

STANDARDS

- Third party certified to CSA B125, ASME A112.18.1, ANSI A117.1, ANSI/NSF 61/9, IAPMO, and all applicable requirements referenced therein, the Federal Safe Drinking Water Act, California Proposition 65, Illinois, Massachusetts, and Texas
- All CFG products are compliant to all plumbing codes that require 3rd party certification to the applicable plumbing/fitting standards
- Features red/blue hot/cold temperature indicators

WARRANTY - RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects
 in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information