

Viega Product Catalog
May 2014

The
global
leader

The global leader
in plumbing, heating
and pipe joining systems

viega



Viega ... One source, multiple solutions

Designed for peace of mind

Viega manufactures and distributes complete system solutions engineered to integrate. Whether you are installing a potable water line in a restaurant or specifying a natural gas line for a hospital, Viega offers a solution that reduces overall project cost and provides guaranteed peace of mind. With a wide range of adapters for each material, all Viega press fitting solutions can work together.

Join different piping materials with the same trusted technology

Viega offers the same proven press technology in copper, stainless, carbon steel and even high-performance polymer. Viega ProPress for copper and stainless and Viega MegaPress for black iron help reduce installation time up to 60% and are approved for use in the largest range of applications in the industry. Viega PEX Press systems are available in sizes up to 2" with the first press fitting for PEX tubing. Viega ProPress, Viega MegaPress and Viega PEX Press polymer fittings all help installers finish a job with confidence, using the patented Viega Smart Connect feature which allows easy identification of unpressed fittings.

Heat and cool with energy-efficient radiant systems

Viega ProRadiant heating and cooling systems are highly engineered to be user friendly. From start to finish, Viega offers the highest-quality, most complete systems in the industry with PEX tubing, manifolds, controls and innovative mat systems. Whether the project is installing radiant heating or cooling in a warehouse or radiant snow melting in a parking lot, Viega provides everything you need.

The term Viega does not apply to a specific company within the company as a whole. The term Viega can refer to either the Viega Group of Companies or to the Viega brand itself. The Viega Group of Companies includes Viega GmbH & Co. KG and all of its direct and indirect subsidiaries, each of which is separate and distinct.

Registered Trademark:



Superior performance with Viega system solutions

Viega introduced press technology to North America in 1999 with Viega ProPress. Now, almost 15 years later, Viega press technology has made consistent, secure connections possible on copper, stainless, black iron and PEX. No other manufacturer can offer the same press technology across multiple pipe joining materials. Viega press systems also offer guaranteed security through innovations like the patented Viega Smart Connect feature, which is only available on genuine Viega press fittings. Installers can trust a Viega connection and finish a job without worrying because the Viega Smart Connect feature helps ensure that they identify unpressed connections during pressure testing.

Company Information:

Viega LLC
North American Headquarters
301 N. Main, 9th Floor
Wichita, KS 67202

Phone:

800-976-9819

Other Locations:

Viega Manufacturing and
Distribution Center – McPherson, KS
Northeast Distribution Center – Harrisburg, PA
Southeast Distribution Center – Atlanta, GA
West Distribution Center – Reno, NV
Viega Educational Facility – Nashua, NH

Websites:

www.viega.us
www.viega.mx
www.viega.ca

Standard terms and conditions in this catalog are those in effect on the date of publication of the catalog. Complete installation information and technical specifications are available on www.viega.us. Viega reserves the right to adjust prices, change its product offering and change standard Terms and Conditions. To obtain current information, go to www.viega.us.

Legend

Abbreviation	Definition
BA	Hydronic Mixing Equipment Outlet Connection
BP	Bolt Pattern
BSP	British Standard Pipe
BW (IPS)	Butt Weld (Iron Pipe Size)
C	Female Copper Tube Size
Closet	Closet Connection
Comp	Compression
Crimp	PEX Crimp Connection
CTS	Copper Tube Size
D	Depth
d	Diameter
d1	Diameter 1
d2	Diameter 2
d3	Diameter 3
DG	Discount Group
FNT	Female Nominal Thread
FPT	Female Pipe Thread
FTG	Street
G (IPS)	Groove (Iron Pipe Size)
gpm	Gallons Per Minute
H	Height
Hose	Hose Connection
IPS	Iron Pipe Size
L	Length
Lav	Lav Connection
Lbs	Pounds
MNT	Male Nominal Thread
MPT	Male Pipe Thread
NPT	National Pipe Thread
OC	On Center
OD	Outside Diameter
P	Press Connection

Abbreviation	Definition
P1	Press Connection 1
P2	Press Connection 2
P3	Press Connection 3
Part No	Part Number
PB	Polybutylene Connection
pc	Piece
PE	Polyethylene Connection
PFC	ProGeo Female Connection
PLS	Polysulfone
PP	ProPress
SMA	Stainless Manifold Connection
Stub	Connection end that is the same size as pipe OD, similar to a street fitting
SVC	Standard Viega Connection
SWIVEL	Fitting connection that attaches with a nut that has an integral flat gasket to make a seal
V	Volt
W	Width
Wt	Weight
XL	Extra Large

How to Read Dimensions of a Fitting or a Product



Viega ProPress tee
Smart Connect feature, Zero Lead
 - Copper
 - Press connection
Components
 - EPDM sealing elements
Model 2918

P1	P2	P3	Wt [lb]	Quantity	Part No	DG
1/2	1/2	1/2	0.204	10	77377	8
1/2	1/2	3/4	0.287	10	77382	8
1/2	1/2	1	0.320	5	15493	8
3/4	1/2	1/2	0.274	10	77392	8
3/4	1/2	3/4	0.319	5	77397	8
3/4	3/4	1/2	0.292	10	77402	8



Viega ProPress tee Vent
Smart Connect feature, Zero Lead
 - Bronze
 - Press connection, female pipe thread

P1	P2	FPT	Wt [lb]	Quantity	Part No	DG
1/2	1/2	1/8	0.154	2	79635	8
3/4	3/4	1/8	0.234	2	79640	8



Viega PEX Press tee
Zero Lead
 - For fire sprinkler systems
 - Bronze
 - Press connection, female pipe thread
 - Mounts to vertical surfaces
Note
 For use with black ViegaPEX Ultra only.

P1	P2	FPT	Wt [lb]	Quantity	Part No	DG
3/4	3/4	1/2	0.454	1	94736	6
1	3/4	1/2	0.505	1	94738	6
1	1	1/2	0.551	1	94739	6




Viega PEX Press manifold
Smart Connect feature, Zero Lead
 - Only use with lock clip Part No 58075
 - Polymer
 - Press connection

Outlet(s)	P1	P2	P3	Wt [lb]	Quantity	Part No	DG
2	3/4	3/4	1/2	0.202	10	49152	6
3	3/4	3/4	1/2	0.255	10	49153	6
4	3/4	3/4	1/2	0.318	10	49054	6
4	1	3/4	1/2	0.330	10	49254	6



Viega PEX Press tub elbow 90°
Zero Lead
 - Brazed copper
 - Press connection, street
Model 2820.0ZL

P	FTG	L1 [in]	L2 [in]	Wt [lb]	Quantity	Part No	DG
1/2	1/2	3	6	0.261	25	92221	6



Viega ManaBloc distribution manifold
Smart Connect feature, Zero Lead
 - Press connection
 - Color coded ports for hot and cold water
Components
 - 1/4 turn valves, T-handle valve key
Note
 Does not include supply connections
Model V5630

d=Diameter of tubing

Adapter	Port(s)	d	hot	cold	Wt [lb]	Quantity	Part No	DG
polymer	14	3/8	6	8	5.543	1	49142	2



Manifold cabinet
 - Galvanized steel, epoxy powder-coated finish
Model 2879.6US

W [in]	H [in]	D [in]	Wt [lb]	Quantity	Part No	DG
21	30	4 1/2	28.975	1	15800	4
27	30	4 1/2	33.990	1	15801	4
45	30	4 1/2	49.986	1	15802	4

PEX Press



3.1



PEX Press

For both residential and commercial applications, Viega PEX Press is the trusted way to join PEX tubing. As the world leader in press technology, Viega was the first to offer a press system to the PEX market. Combined with our revolutionary Viega ManaBloc water distribution system and the highest rated PEX tubing in the industry, Viega is a complete, premium plumbing solution.

FEATURES AND BENEFITS

- The original press fitting for PEX tubing
- Factory-assembled press fittings reduce installation errors on the job
- Available in sizes from 3/8" to 2"
- The only PEX fittings with the Viega Smart Connect feature
- Available in two materials, proprietary Zero Lead bronze and high-performance polymer
- Comprehensive 10-year transferable warranty

CODES AND STANDARDS

- ASTM E84: Specification for Surface Burning Characteristic
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for PEX Insert Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- AWWA C904: Cross-linked Polyethylene (PEX) Pressure Pipe for water service
- CAN/ULC S101: Standard Method of Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Method of Test for Surface Burning Characteristics
- CSA International: Canadian Standard Association
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- IAPMO: Uniform Plumbing Code
- ICC: International Plumbing Code
- NSF/ANSI 61: Drinking Water System Components – Health Effects
- NSF/ANSI 61G: Lead Content Evaluation Procedure to meet < 0.25% average lead content
- NSF/ANSI 14: Plastics Piping System Components and Related Materials
- NSPC: National Standard Plumbing Code
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service

ZERO LEAD

References to Zero Lead throughout this publication means product meeting the requirements of NSF 61-G through testing under NSF/ANSI Standard 372 (0.25% or less percent maximum weighted average lead content).

NOTE

A Green Dot on a Viega PEX Press fitting indicates the Smart Connect feature.

Index

Tubing	82
Elbows	86
Tees	88
Adapters	90
Couplings	91
Valves	92
Viega ManaBlocs	93
Manifolds	96
Stub-Outs	96
Lav adapters	97
Closet adapters	97
Outlet boxes	97
Tools	98
Accessories	100

Tubing



ViegaPEX tubing

Zero Lead

- PEX

- Coil

Technical Data

PEX designation code 5006
Chlorine resistance rating CL5
UV resistance 60 days

ASTM F876, ASTM F877

Model V5001

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	red	5.000	1	32101 ¹	1
3/8	500	red	21.000	1	32105 ¹	1
3/8	1000	red	42.000	1	32100	1
1/2	100	red	5.800	1	32121 ¹	1
1/2	300	red	17.100	1	32123 ¹	1
1/2	500	red	28.000	1	32125 ¹	1
1/2	1000	red	58.000	1	32120	1
3/4	100	red	11.000	1	32141 ¹	1
3/4	300	red	32.100	1	32143 ¹	1
3/4	500	red	53.000	1	32145 ¹	1
3/4	1000	red	106.000	1	32140 ²	1
1	100	red	16.900	1	33323 ¹	1
1	300	red	50.700	1	32163	1
1	500	red	88.000	1	32165	1

¹) center pull coil
²) Available while supplies last



ViegaPEX tubing

Zero Lead

- PEX

- Straight length

Technical Data

PEX designation code 5006
Chlorine resistance rating CL5
UV resistance 60 days

ASTM F876, ASTM F877

Model V5001.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	red	0.540	5	33272	1
1/2	20	red	1.060	5	33120	1
3/4	10	red	1.020	5	33275	1
3/4	20	red	2.040	5	33145	1
1	20	red	3.420	5	33270	1



ViegaPEX tubing

Zero Lead

- PEX

- Coil

Technical Data

PEX designation code 5006
Chlorine resistance rating CL5
UV resistance 60 days

ASTM F876, ASTM F877

Model V5002

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	blue	5.000	1	32201 ¹	1
3/8	500	blue	21.000	1	32205 ¹	1
3/8	1000	blue	42.000	1	32200	1
1/2	100	blue	5.300	1	32221 ¹	1
1/2	300	blue	17.100	1	32223 ¹	1
1/2	500	blue	26.500	1	32225 ¹	1
1/2	1000	blue	55.000	1	32220	1
3/4	100	blue	11.000	1	32241 ¹	1
3/4	300	blue	32.100	1	32243 ¹	1
3/4	500	blue	53.000	1	32245 ¹	1
3/4	1000	blue	106.000	1	32240 ²	1
1	300	blue	50.700	1	32263	1
1	500	blue	88.000	1	32265	1

¹) center pull coil
²) Available while supplies last



ViegaPEX tubing

Zero Lead

- PEX

- Straight length

Technical Data

PEX designation code 5006
Chlorine resistance rating CL5
UV resistance 60 days

ASTM F876, ASTM F877

Model V5002.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	blue	0.540	5	33274	1
1/2	20	blue	1.060	5	33240	1
3/4	10	blue	1.020	5	33277	1
3/4	20	blue	2.040	5	33265	1
1	20	blue	3.420	5	33271	1



ViegaPEX tubing
Zero Lead
 - For installation between studs
 - PEX
 - ManaPac
Components
 Recycled plastic reels
Technical Data
 PEX designation code 5006
 Chlorine resistance rating CL5
 UV resistance 60 days
ASTM F876, ASTM F877
Model V5004

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	2	red/blue	58.000	1	32300	1
3/8	500	1	blue	28.000	1	32905	1
3/8	500	1	red	28.000	1	32805	1
1/2	300	2	red/blue	48.000	1	32326	1
1/2	300	1	blue	23.100	1	32923	1
1/2	300	1	red	23.100	1	32823	1



ViegaPEX tubing
Zero Lead
 - PEX
 - Coil
Technical Data
 PEX designation code 5006
 Chlorine resistance rating CL5
 UV resistance 60 days
ASTM F876, ASTM F877
Model V5003

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/4	100	white	3.200	1	32011	1
1/4	500	white	14.000	1	32015	1
3/8	100	white	5.000	1	32001¹	1
3/8	500	white	21.000	1	32005¹	1
3/8	1000	white	42.000	1	32000	1
1/2	100	white	6.000	1	32021¹	1
1/2	300	white	17.100	1	32023¹	1
1/2	500	white	28.000	1	32025¹	1
1/2	1000	white	55.000	1	32020	1
3/4	100	white	11.000	1	32041¹	1
3/4	300	white	32.100	1	32043¹	1
3/4	500	white	53.000	1	32045¹	1
3/4	1000	white	106.000	1	32040²	1
1	100	white	17.000	1	32061¹	1
1	300	white	51.900	1	32063	1
1	500	white	88.000	1	32065	1

¹) center pull coil
²) Available while supplies last



ViegaPEX tubing
Zero Lead
 - PEX
 - Straight length
Technical Data
 PEX designation code 5006
 Chlorine resistance rating CL5
 UV resistance 60 days
ASTM F876, ASTM F877
Model V5003.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	white	0.540	5	33273	1
1/2	20	white	1.080	5	33020	1
3/4	10	white	1.020	5	33276	1
3/4	20	white	2.060	5	33045	1
1	20	white	3.420	5	33061	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5005

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	red	21.000	1	32505	1
1/2	100	red	6.000	1	32521	1
1/2	300	red	17.100	1	32523	1
1/2	500	red	28.000	1	32525	1
1/2	1000	red	55.000	1	32520	1
3/4	100	red	11.000	1	32541	1
3/4	300	red	32.100	1	32543	1
3/4	500	red	53.000	1	32545	1
1	100	red	17.000	1	32551	1
1	300	red	51.900	1	32553	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5005.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	red	0.550	50	33529	1
1/2	20	red	1.180	50	33520	1
3/4	10	red	0.550	25	33549	1
3/4	20	red	2.020	25	33540	1
1	20	red	3.480	5	33551	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Coil

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5006

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	blue	21.000	1	32605	1
1/2	100	blue	6.000	1	32621	1
1/2	300	blue	15.900	1	32623	1
1/2	500	blue	28.000	1	32625	1
1/2	1000	blue	55.000	1	32620	1
3/4	100	blue	11.000	1	32641	1
3/4	300	blue	30.900	1	32643	1
3/4	500	blue	53.000	1	32645	1
1	100	blue	17.000	1	32651	1
1	300	blue	51.900	1	32653	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Straight length

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5006.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	blue	0.550	50	33629	1
1/2	20	blue	1.180	50	33620	1
3/4	10	blue	0.550	25	33649	1
3/4	20	blue	2.020	25	33645	1
1	20	blue	3.480	5	33651	1



ViegaPEX Ultra tubing

Zero Lead

- For installation between studs
- PEX
- ManaPac

Components

Recycled plastic reels

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5008

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	2	red/blue	116.000	1	33300	1
3/8	500	1	blue	28.000	1	33905	1
3/8	500	1	red	28.000	1	33805	1
1/2	300	2	red/blue	48.000	1	33326	1
1/2	300	1	blue	23.100	1	33923	1
1/2	300	1	red	23.100	1	33823	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Coil

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5007

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	white	21.000	1	32405	1
1/2	100	white	6.000	1	32421	1
1/2	300	white	17.100	1	32423	1
1/2	500	white	28.000	1	32425	1
3/4	100	white	11.000	1	32441	1
3/4	300	white	32.100	1	32443	1
3/4	500	white	53.000	1	32445	1
1	100	white	17.000	1	32461	1
1	300	white	51.900	1	33362	1
1	500	white	88.000	1	32465	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Straight length

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5007.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	white	0.550	50	33429	1
1/2	20	white	1.100	50	33420	1
3/4	10	white	0.550	25	33459	1
3/4	20	white	2.100	25	33405	1
1	20	white	3.480	5	33461	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5009

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	black	21.000	1	32705 ¹⁾	1
1/2	100	black	5.500	1	32721	1
1/2	300	black	16.500	1	32723	1
1/2	500	black	29.000	1	32725	1

¹⁾ Available while supplies last



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
UL listed for NFPA 13D systems, ASTM F876,
ASTM F877
Model V5009.1

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/4	100	black	10.500	1	34741	1
3/4	300	black	31.500	1	34743	1
3/4	500	black	52.500	1	34745	1
1	100	black	17.400	1	34761	1
1	500	black	87.000	1	34765	1
1 1/4	100	black	25.500	1	34771	1
1 1/4	300	black	76.500	1	34773	1
1 1/2	100	black	35.400	1	34781	1
2	100	black	63.000	1	32791	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5009.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	20	black	1.100	50	33720	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
UL listed for NFPA 13D systems, ASTM F876,
ASTM F877
Model V5009.51

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/4	20	black	2.100	25	35745	1
1	20	black	3.480	5	35761	1
1 1/4	20	black	5.100	5	35771	1
1 1/2	20	black	7.060	5	35781	1
2	20	black	12.280	5	33791	1



Viega FostaPEX tubing
Zero Lead
 - Only for Viega PEX Press fittings
 - PEX/AL/PE
 - Coil
 - Form stable
Technical Data
 PEX designation code 5006
 Chlorine resistance rating CL5
 UV resistance extended
ASTM F876, ASTM F877
Model 2805US

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	150	silver	15.000	1	35020 ¹⁾	6
1/2	300	silver	30.000	1	35019 ¹⁾	6
1/2	400	silver	38.000	1	35021 ¹⁾	6
3/4	150	silver	24.000	1	35040 ¹⁾	6
1	150	silver	39.000	1	35060 ¹⁾	6

¹⁾ center pull coil



Viega FostaPEX tubing

Zero Lead

- Only for Viega PEX Press fittings
- PEX/AL/PE
- Straight length
- Form stable

Technical Data

PEX designation code 5006
Chlorine resistance rating CL5
UV resistance extended

ASTM F876, ASTM F877

Model 2806US

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	20	silver	2.000	25	35520	6
3/4	20	silver	3.200	25	35540	6
1	20	silver	5.200	10	35560	6



Viega FostaPEX tubing

Zero Lead

- Only for Viega PEX Press fittings
- PEX/AL/PE
- Coil
- Form stable

Technical Data

PEX designation code 5006
Chlorine resistance rating CL5
UV resistance extended

ASTM F876, ASTM F877

Model 2808US

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	150	red	15.000	1	35120¹	6
3/4	150	red	24.000	1	35140¹	6
1	150	red	39.000	1	35160¹	6

¹⁾ center pull coil

Elbows



Viega PEX Press elbow 90°

Zero Lead

- Bronze
- Press connection

Model 2816ZL

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.085	10	93520	6
3/4	3/4	0.153	10	93540	6
1	1	0.212	10	93560	6
1 1/4	1 1/4	0.359	5	93570	6
1 1/2	1 1/2	0.840	5	93580	6
2	2	1.681	1	93590	6



Viega PEX Press elbow 90°

Smart Connect feature, Zero Lead

- Polymer
- Press connection

Model V5616

P1	P2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.023	25	49210	6
1/2	1/2	0.029	25	49220	6
3/4	3/4	0.047	25	49240	6
1	1	0.080	10	49260	6
1 1/4	1 1/4	0.171	5	49270	6
1 1/2	1 1/2	0.220	5	49280	6
2	2	0.350	5	49290	6



Viega PEX Press elbow 90°

Zero Lead

- Bronze
- Press connection, male pipe thread

Model 2814ZL

P	MPT	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.198	10	92520	6
1/2	3/4	0.311	10	92525	6
3/4	3/4	0.295	10	92540	6
3/4	1	0.748	10	92545	6
3/4	1 1/4	1.210	2	92565	6
1	1	0.743	10	92560	6
1	1 1/4	1.201	2	92570	6
1 1/4	1 1/4	1.270	2	92757	6
1 1/2	1 1/2	1.415	2	92580	6
2	2	2.878	2	92590	6



Viega PEX Press elbow 90°

Zero Lead

- Bronze
- Press connection, female copper tube size

Model 2814.5ZL

P	C	Wt [lb]	Quantity	Part No	DG
1/2	3/4	0.326	10	99308	6
3/4	3/4	0.320	10	99309	6



**Viega PEX Press elbow 90°
Zero Lead**
- Bronze
- Press connection, street
Model 2814.6ZL

P	FTG	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.179	10	99310	6



**Viega PEX Press elbow 90°
Zero Lead**
- Bronze
- Press connection, street, female copper tube size
Note
Copper connection can be used as either male or female connection.
Model 2814.7ZL

P	FTG	C	Wt [lb]	Quantity	Part No	DG
1/2	3/4	1/2	0.317	10	99307	6
3/4	3/4	1/2	0.311	10	99311	6



**Viega PEX Press adapter elbow 90°
Drop ear
Zero Lead**
- For fire sprinkler systems
- Bronze
- Press connection, female pipe thread
Note
For use with black ViegaPEX Ultra only.
UL listed for NFPA 13D systems
Model 2814.2ZL

P1	P2	FPT	Wt [lb]	Quantity	Part No	DG
3/4		1/2	0.289	1	94635	6
3/4	3/4	1/2	0.339	1	94646	6
1		1/2	0.339	1	94640*	6

* = Available while supplies last



**Viega PEX Press elbow 90°
Drop ear
Zero Lead**
- Bronze
- Press connection, female pipe thread
Model 2825.5ZL

P	FPT	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.190	10	94505	6
1/2	1/2	0.203	10	94520	6
3/4	1/2	0.226	10	94535	6
3/4	3/4	0.271	10	94540	6



**Viega PEX Compression Elbow 90°
Zero Lead**
- For dishwasher, connecting 3/8" compression to 3/4" hose supply connection
- Equipped with ferrule Part No 53015
- Copper
- Hose connection
Model V5053

CTS	Hose	Wt [lb]	Quantity	Part No	DG
3/8	3/4	0.230	1	46743	2

Tees



**Viega PEX Press tee
Zero Lead**
- Bronze
- Press connection
Model 2818ZL

P1	P2	P3	Wt [lb]	Quantity	Part No	DG
1/2	3/8	3/8	0.101	10	94021 ¹	6
1/2	1/2	1/2	0.107	10	94020	6
1/2	1/2	3/4	0.194	10	94022	6
3/4	1/2	1/2	0.177	10	94032	6
3/4	1/2	3/4	0.179	10	94034	6
3/4	3/4	1/2	0.185	10	94036	6
3/4	3/4	3/4	0.178	10	94040	6
1	1/2	1/2	0.282	10	94037	6
1	1/2	1	0.233	10	94039	6
1	3/4	1/2	0.287	10	94038	6
1	3/4	3/4	0.201	10	94052	6
1	3/4	1	0.242	10	94053	6
1	1	1/2	0.216	10	94050	6
1	1	3/4	0.262	10	94056	6
1	1	1	0.296	10	94060	6
1 1/4	1	3/4	0.527	5	94071	6
1 1/4	1	1	0.569	5	94073	6
1 1/4	1 1/4	3/4	0.547	5	94072	6
1 1/4	1 1/4	1	0.588	5	94074	6
1 1/4	1 1/4	1 1/4	0.716	5	94070	6
1 1/2	1	3/4	0.627	5	94081	6
1 1/2	1	1	0.740	5	94082	6
1 1/2	1 1/2	3/4	0.681	5	94083	6
1 1/2	1 1/2	1	0.767	5	94084	6
1 1/2	1 1/2	1 1/4	0.862	5	94085	6
1 1/2	1 1/2	1 1/2	0.932	5	94080	6
2	1 1/2	1	1.697	5	94091 ¹	6
2	1 1/2	1 1/4	1.737	5	94092 ¹	6
2	1 1/2	1 1/2	1.741	5	94093 ¹	6
2	2	2	1.772	1	94090	6

¹⁾ Available while supplies last



Viega PEX Press tee
Smart Connect feature, Zero Lead
 - Polymer
 - Press connection
Model V5618

P1	P2	P3	Wt [lb]	Quantity	Part No	DG
3/8	3/8	3/8	0.035	25	49200	6
1/2	3/8	3/8	0.036	25	49322	6
1/2	1/2	3/8	0.045	25	49332	6
1/2	1/2	1/2	0.042	25	49520	6
1/2	1/2	3/4	0.052	25	49334	6
3/4	1/2	1/2	0.052	25	49433	6
3/4	1/2	3/4	0.061	25	49434	6
3/4	3/4	1/2	0.059	25	49443	6
3/4	3/4	3/4	0.068	25	49540	6
1	1/2	1/2	0.068	10	49533	6
1	1/2	1	0.097	10	49535	6
1	3/4	1/2	0.074	10	49543	6
1	3/4	3/4	0.084	10	49544	6
1	3/4	1	0.104	10	49545	6
1	1	1/2	0.088	10	49553	6
1	1	3/4	0.102	10	49554	6
1	1	1	0.115	10	49560	6
1 1/4	1	3/4	0.142	5	49754	6
1 1/4	1	1	0.158	5	49755	6
1 1/4	1 1/4	3/4	0.182	5	49774	6
1 1/4	1 1/4	1	0.195	5	49775	6
1 1/4	1 1/4	1 1/4	0.250	5	49570	6
1 1/2	1	3/4	0.170	5	49854	6
1 1/2	1	1	0.195	5	49855	6
1 1/2	1 1/4	3/4	0.233	5	49874	6
1 1/2	1 1/4	1	0.254	5	49875	6
1 1/2	1 1/4	1 1/4	0.290	5	49877	6
1 1/2	1 1/2	3/4	0.233	5	49884	6
1 1/2	1 1/2	1	0.245	5	49885	6
1 1/2	1 1/2	1 1/4	0.290	5	49887	6
1 1/2	1 1/2	1 1/2	0.326	5	49580	6
2	1 1/2	3/4		5	49984	6
2	1 1/2	1	0.315	5	49985	6
2	1 1/2	1 1/4	0.365	5	49987	6
2	1 1/2	1 1/2	0.390	5	49988	6
2	2	3/4	0.335	5	49994	6
2	2	1	0.360	5	49995	6
2	2	1 1/4	0.405	5	49997	6
2	2	1 1/2	0.435	5	49998	6
2	2	2	0.500	5	49590	6



Viega PEX Press tee
Zero Lead
 - For fire sprinkler systems
 - Bronze
 - Press connection, female pipe thread
 - Mounts to horizontal surfaces
Note
 For use with black ViegaPEX Ultra only.
UL listed for NFPA 13D systems
Model 2818.2ZL

P1	P2	FPT	Wt [lb]	Quantity	Part No	DG
3/4	3/4	1/2	0.270	1	94636	6
1	3/4	1/2	0.370	1	94638	6
1	1	1/2	0.408	1	94639	6



Viega PEX Press tee
Zero Lead
 - For fire sprinkler systems
 - Bronze
 - Press connection, female pipe thread
 - Mounts to vertical surfaces
Note
 For use with black ViegaPEX Ultra only.
UL listed for NFPA 13D systems
Model 2818.3ZL

P1	P2	FPT	Wt [lb]	Quantity	Part No	DG
3/4	3/4	1/2	0.454	1	94736	6
1	3/4	1/2	0.505	1	94738	6
1	1	1/2	0.551	1	94739	6

Adapters



**Viega PEX Press adapter
Zero Lead**
- Bronze
- Press connection, male pipe thread
Model 2811ZL

P	MPT	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.101	10	90506	6
1/2	1/2	0.099	10	90521	6
1/2	3/4	0.152	10	90526	6
3/4	1/2	0.110	10	90542	6
3/4	3/4	0.156	10	90541	6
3/4	1	0.281	10	90546	6
3/4	1 1/4	0.485	2	90562	6
1	3/4	0.183	10	90556	6
1	1	0.289	10	90561	6
1	1 1/4	0.514	2	90566	6
1 1/4	1 1/4	0.551	2	90571	6
1 1/2	1 1/2	0.672	2	90581	6
2	2	1.095	5	90591	6



**Viega PEX Press adapter
Zero Lead**
- Bronze
- Press connection, female pipe thread
Model 2812ZL

P	FPT	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.100	10	91520	6
1/2	3/4	0.132	10	91525	6
3/4	1/2	0.106	10	91541	6
3/4	3/4	0.139	10	91540	6
1	3/4	0.168	10	91545	6
1	1	0.240	10	91560	6
1 1/4	1 1/4	0.436	5	91570	6
1 1/2	1 1/2	0.518	5	91580	6
2	2	0.814	5	91590	6



**Viega PEX Press adapter
Zero Lead**
- For fire sprinkler systems
- Bronze
- Press connection, female pipe thread
Note
For use with black ViegaPEX Ultra only.
UL listed for NFPA 13D systems
Model 2812.2ZL

P	FPT	Wt [lb]	Quantity	Part No	DG
3/4	1/2	0.242	1	94632	6



**Viega PEX Press adapter
Smart Connect feature, Zero Lead**
- For transitioning between Viega PEX Press
and Viega ProPress
- Bronze
- Press connection
Components
EPDM sealing elements
Note
ProPress tool and jaw required
Model 2813PZL

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.075	10	99620	6
1/2	3/4	0.114	10	99626	6
3/4	1/2	0.077	10	99630	6
3/4	3/4	0.113	10	99640	6
1	3/4	0.136	10	99645	6
1	1	0.185	10	99660	6
1 1/4	1	0.231	5	99665	6
1 1/4	1 1/4	0.284	5	99670	6
1 1/2	1	0.276	5	99675	6
1 1/2	1 1/2	0.445	5	99680	6
2	1	0.459	5	99685	6
2	2	0.719	5	99690	6



**Viega PEX Press adapter
Zero Lead**
- Bronze
- Press connection, female copper tube size
Model 2813.5ZL

P	C	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.061	10	92006	6
1/2	1/2	0.064	10	92021	6
1/2	3/4	0.098	10	92026	6
3/4	1/2	0.066	10	92036	6
3/4	3/4	0.116	10	92041	6
3/4	1	0.172	10	92045	6
1	1	0.187	10	92060	6
1 1/4	1 1/4	0.331	5	92070	6
1 1/2	1 1/2	0.450	5	92080	6
2	2	0.609	5	92090	6



**Viega PEX Press adapter
Zero Lead**
- Bronze
- Press connection, street
Note
ProPress tool and jaw required
Model 2813.1ZL

P	FTG	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.066	10	97520	6
1/2	3/4	0.097	10	97525	6
3/4	1/2	0.079	10	97535	6
3/4	3/4	0.100	10	97540	6
3/4	1	0.154	10	97545	6
1	1	0.174	10	97560	6
1 1/4	1 1/4	0.303	5	97570	6
1 1/2	1 1/2	0.434	5	97580	6
2	2	0.696	5	97590 ¹⁾	6

¹⁾ For use with solder fittings only.



**Viega PEX Press adapter
Zero Lead**
- Bronze
- Press connection
Note
2" ProPress tool and jaw required
Model 2813.3ZL

P1	FTG	Wt [lb]	Quantity	Part No	DG
2	2	0.736	5	97690 ¹⁾	6

¹⁾ For use with ProPress fittings only.



**Viega PEX Press adapter
Zero Lead**
- Bronze
- Press connection, polybutylene (PB)
connection
Note
Does not include ring for PB connection
Model 2813.2ZL

P	PB	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.051	10	97820	6
3/4	3/4	0.073	10	97840	6



**Viega PEX Press adapter
Zero Lead**
- Bronze
- Press connection, flare connection
Model 2892ZL

P	Flare	Wt [lb]	Quantity	Part No	DG
3/4	3/4	0.275	10	97140	6
1	3/4	0.326	10	97160	6
1	1	0.414	10	97165	6



**Viega PEX Press tailpiece
Zero Lead**
- Bronze
- Press connection, female union BSP
Model 2893ZL

P	F BSP	Wt [lb]	Quantity	Part No	DG
3/4	1	0.195	10	96140	6
1	1	0.240	10	96160	6
1	1 1/4	0.340	10	96165	6

Couplings



**Viega PEX Press coupling
Zero Lead**
- Bronze
- Press connection
Model 2815ZL

P1	P2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.040	10	93000	6
1/2	3/8	0.048	10	93005	6
1/2	1/2	0.053	10	93020	6
3/4	1/2	0.068	10	93050	6
3/4	3/4	0.072	10	93040	6
1	3/4	0.115	10	93055	6
1	1	0.130	10	93060	6
1 1/4	3/4	0.187	5	93071	6
1 1/4	1	0.207	5	93065	6
1 1/4	1 1/4	0.260	5	93070	6
1 1/2	3/4	0.234	5	93072	6
1 1/2	1	0.240	5	93073	6
1 1/2	1 1/4	0.289	5	93075	6
1 1/2	1 1/2	0.313	5	93080	6
2	1 1/2	0.491	5	93091	6
2	2	0.580	5	93090	6



Viega PEX Press coupling
Smart Connect feature, Zero Lead
 - Polymer
 - Press connection
Model V5615

P1	P2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.022	25	49402	6
1/2	3/8	0.024	25	49342	6
1/2	1/2	0.027	25	49403	6
3/4	1/2	0.034	25	49343	6
3/4	3/4	0.040	25	49404	6
3/4	1 1/4	0.101	5	49347	6
3/4	1 1/2	0.118	5	49348	6
1	3/4	0.055	10	49354	6
1	1	0.068	10	49405	6
1	1 1/4	0.112	5	49357	6
1	1 1/2	0.133	5	49358	6
1 1/4	1 1/4	0.151	5	49407	6
1 1/4	1 1/2	0.165	5	49378	6
1 1/2	1 1/2	0.189	5	49408	6
2	1 1/2	0.245	5	49398	6
2	2	0.280	5	49409	6



Viega PEX Press test plug
Zero Lead
 - Bronze
 - Press connection
Model 2856ZL

P	Wt [lb]	Quantity	Part No	DG
3/8	0.022	10	95000 ¹	6
1/2	0.035	10	95121 ¹	6
3/4	0.057	10	95141 ¹	6
1	0.107	10	95161 ¹	6

¹⁾ Available while supplies last



Viega PEX Press test plug
Smart Connect feature, Zero Lead
 - Polymer
 - Press connection
Model V5656

P	Wt [lb]	Quantity	Part No	DG
3/8	0.011	25	49722	6
1/2	0.015	25	49723	6
3/4	0.022	25	49744	6
1	0.036	10	49765	6
1 1/4	0.151	1	49770	6
1 1/2	0.189	1	49780	6
2	0.280	1	49790	6

Valves



Viega PEX Press stop valve
Straight
Zero Lead
 - Chrome-plated brass
 - Press connection, compression
 - 1/4 turn
Model 2842.3ZL

P	CTS	Wt [lb]	Quantity	Part No	DG
3/8	1/4	0.319	10	94023	6
1/2	1/4	0.308	10	94031	6



Viega PEX Press stop valve
Angled
Zero Lead
 - Chrome-plated brass
 - Press connection, compression
 - 1/4 turn
Model 2842.4ZL

P	CTS	Wt [lb]	Quantity	Part No	DG
3/8	1/4	0.229	10	93515	6
1/2	1/4	0.320	10	93511	6



Viega PEX Press ball valve
Zero Lead
 - Brass
 - Press connection
 - Full port
Model 2842.2ZL

P1	P2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.310	10	94500	6
1/2	1/2	0.299	10	94521	6
3/4	3/4	0.332	10	94541	6



**Viega ProPress valve
Zero Lead**

- For copper manifolds
- Brass
- Press connection, street

Note

1/2" ProPress tool and jaw required

Model 2842.1ZL

P	FTG	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.223	10	95002	6




**Viega PEX Press wall hydrant
Zero Lead**

- Chrome-plated brass
- Press connection

Model 2888.0ZL

P	L [in]	Wt [lb]	Quantity	Part No	DG
1/2	10	1.356	5	97120	6
3/4	10	1.316	5	97121	6

Viega ManaBlocs



**Viega ManaBloc distribution manifold
Smart Connect feature, Zero Lead**

- Press connection
- Color coded ports for hot and cold water

Components

1/4 turn valves, T-handle valve key

Note

Does not include supply connections

Model V5630

Adapter	Port(s)	d	hot	cold	Wt [lb]	Quantity	Part No	DG
polymer	14	3/8	6	8	5.543	1	49142	2
polymer	14	1/2	6	8	5.613	1	49143	2
polymer	18	1/2	8	10	6.523	1	49183	2
polymer	24	1/2	9	15	8.218	1	49243	2
polymer	30	1/2	12	18	9.832	1	49303	2
polymer	36	1/2	14	22	13.336	1	49363	2



**Viega ManaBloc distribution manifold
Smart Connect feature, Zero Lead**

- Press connection
- Combination port sizes, color coded ports for hot and cold water

Components

1/4 turn valves, T-handle valve key

Note

Does not include supply connections

Model V5640

Adapter	Port(s)	d1	hot1	cold1	d2	hot2	cold2	Wt [lb]	Quantity	Part No	DG
polymer	18	3/8	6	7	1/2	2	3	6.758	1	49186	2
polymer	24	3/8	7	11	1/2	2	4	8.173	1	49246	2
polymer	30	3/8	10	12	1/2	2	6	10.147	1	49306	2
polymer	36	3/8	11	15	1/2	3	7	11.807	1	49366	2



**Viega MiniBloc zoning manifold
Smart Connect feature, Zero Lead**

- For combination systems
- Press connection
- Blue color coded ports for cold water

Components

1/4 turn valves, T-handle valve key, optional red valve caps

Note

Does not include supply connections

Model V5650

Adapter	Port(s)	d	Wt [lb]	Quantity	Part No	DG
polymer	3	1/2	2.159	1	49033	2
polymer	4	1/2	2.354	1	49043	2
polymer	6	1/2	2.456	1	49063	2
polymer	8	1/2	3.689	1	49083	2



Viega MiniBloc zoning manifold
Smart Connect feature, Zero Lead
 - For combination systems
 - Press connection
 - Color coded ports for hot and cold water
Components
 ¼ turn valves, T-handle valve key

Note
 Does not include supply connections

Model V5660

Adapter	Port(s)	d	hot	cold	Wt [lb]	Quantity	Part No	DG
polymer	5	½	2	3	2.589	1	49453	2
polymer	7	½	3	4	3.442	1	49473	2
polymer	10	½	4	6	4.807	1	49410	2



Viega PEX Press port adapter
Smart Connect feature, Zero Lead
 - For connecting distribution lines to Viega ManaBloc and Viega MiniBloc
 - Polymer
 - Press connection, Viega ManaBloc port connection
Model V5613.1

P	Port	Wt [lb]	Quantity	Part No	DG
¾	½	0.047	6	49224	2
½	½	0.050	6	49234	2



Viega PEX Press port adapter
Zero Lead
 - For connecting distribution lines to Viega ManaBloc and Viega MiniBloc
 - Bronze
 - Press connection, Viega ManaBloc port connection
Model 2877.3ZL

P	Port	Wt [lb]	Quantity	Part No	DG
¾	½	0.095	6	96101	2
½	½	0.102	6	96120	2



Viega PEX Press supply adapter
Smart Connect feature, Zero Lead
 - For connecting PEX supply lines to Viega ManaBloc and Viega MiniBloc
 - Polymer
 - Press connection, Viega ManaBloc supply connection
Model V5613.2

P	Supply	Wt [lb]	Quantity	Part No	DG
¾	1	0.098	5	49414	2
1	1	0.118	5	49416	2



Viega PEX Press supply adapter
Zero Lead
 - For connecting PEX supply lines to Viega ManaBloc and Viega MiniBloc
 - Bronze
 - Press connection, Viega ManaBloc supply connection
Model 2877.8ZL

P	Supply	Wt [lb]	Quantity	Part No	DG
¾	1	0.214	5	96141	2
1	1	0.236	5	96161	2
1¼	1	0.293	5	96171	2



Viega ManaBloc supply adapter
Zero Lead
 - For connecting CTS-sized supply lines to Viega ManaBloc or Viega MiniBloc
 - Equipped with insert stiffener Model V5086
 - Brass
 - Compression, Viega ManaBloc supply connection
Model V5032ZL

CTS	Supply	Wt [lb]	Quantity	Part No	DG
¾	1	0.395	5	46346	2



Viega ManaBloc supply adapter
Zero Lead
 - For connecting FPT supply lines to Viega ManaBloc and Viega MiniBloc
 - Brass
 - Male pipe thread, Viega ManaBloc supply connection
Model V5033ZL

MPT	Supply	Wt [lb]	Quantity	Part No	DG
3/4	1	0.329	5	46646	2
1	1	0.399	5	46656	2



Port nut
Zero Lead
 - Not suitable for Viega ManaBloc distribution manifold Model V5030, V5030.2, Viega MiniBloc zoning manifold Model V5031
 - Plastic
Model V5039.8

d	Wt [lb]	Quantity	Part No	DG
1/2	0.260	6	53006	2



Port cap
Zero Lead
 - For Viega ManaBloc, Viega MiniBloc
 - Plastic
Model V5087

d	Wt [lb]	Quantity	Part No	DG
3/8	0.020	6	36204	2
1/2	0.037	6	36205	2



Supply cap
Zero Lead
 - For Viega ManaBloc, Viega MiniBloc
 - Brass
Model V5036.10

d	Wt [lb]	Quantity	Part No	DG
1	0.082	5	53601	2



Viega ManaBloc mounting set
 - For mounting Viega ManaBloc between studs
 - Steel
 - Pre-drilled to mount on 16" center studs
Components
 (2) mounting straps, (4) screws
Model V5038

Wt [lb]	Quantity	Part No	DG
0.681	1	45716	2



Replacement kit
 - For Viega ManaBloc and Viega MiniBloc valve stems, ports 1/2" or 3/8"
 - 1/4 turn
Components
 Red valve, blue valve, valve removal tool, T-handle valve key
Model 2870.91

Wt [lb]	Quantity	Part No	DG
0.150	1	51602	2



T-handle valve key
 - For Viega ManaBloc, Viega MiniBloc
Model V5039.7

Wt [lb]	Quantity	Part No	DG
0.040	1	50601	2



Viega ManaBloc access panel

- Plastic

Note

Can be mounted to open vertically or horizontally

Model V5099

W [in]	L [in]	max. Ports	Wt [lb]	Quantity	Part No	DG
14	18	14	1.350	1	50718	2
14	26	16	0.050	1	50726	2
14	30	24	2.434	1	50730	2
14	39	36	3.249	1	50739	2
14	39	36	4.999	1	50839^{2,1}	2

¹⁾ Available while supplies last

²⁾ transparent



Viega ManaBloc access panel

- Metal

- 3 hour fire rating

Components

(2) knurled knobs, (2) keys

Note

Can be mounted to open vertically or horizontally

UL listed

Model V5099.1

W [in]	L [in]	max. Ports	Wt [lb]	Quantity	Part No	DG
14	40	30	26.258	1	50740	2
14	48	36	31.641	1	50748¹	2

¹⁾ Available while supplies last

Manifolds



Viega PEX Press manifold

Smart Connect feature, Zero Lead

- Only use with lock clip Part No 58075

- Polymer

- Press connection

- Flow through

Note

Does not include mounting hardware

Model V5636

Outlet(s)	P1	P2	P3	Wt [lb]	Quantity	Part No	DG
2	3/4	3/4	1/2	0.202	10	49152	6
3	3/4	3/4	1/2	0.255	10	49153	6
4	3/4	3/4	1/2	0.318	10	49054	6
4	1	3/4	1/2	0.330	10	49254	6
6	1	1	1/2	0.455	10	49256	6
8	1	1	1/2	0.576	5	49258	6



Viega PEX Press manifold

Smart Connect feature, Zero Lead

- Only use with lock clip Part No 58075

- Polymer

- Press connection

- Closed

Note

Does not include mounting hardware

Model V5636.1

Outlet(s)	P1	P2	Wt [lb]	Quantity	Part No	DG
4	3/4	1/2	0.300	10	49004	6
6	1	1/2	0.428	10	49206	6

Stub-Outs



Viega PEX Press tub elbow 90°

Zero Lead

- Brazed copper

- Press connection, street

Model 2820.0ZL

P	FTG	L1 [in]	L2 [in]	Wt [lb]	Quantity	Part No	DG
1/2	1/2	3	6	0.261	25	92221	6



Viega PEX Press stub-out 90°

Zero Lead

- Brazed copper

- Press connection, street

Model 2820.1ZL

P	FTG	L1 [in]	L2 [in]	Wt [lb]	Quantity	Part No	DG
3/8	1/2	3 1/2	8	0.306	25	92406	6
1/2	1/2	3 1/2	8	0.309	25	92421	6
3/4	3/4	3 1/2	8	0.545	25	92441	6



Viega PEX Press stub-out 90°
 - Brazed copper
 - Press connection, street
Components
 Wall plate
Model 2820.4ZL

P	FTG	L1 [in]	L2 [in]	Wt [lb]	Quantity	Part No	DG
3/8	1/2	3 1/2	8	0.327	25	92305	6
1/2	1/2	3 1/2	8	0.371	25	92321	6



Viega PEX Press stub-out Zero Lead
 - Brazed copper
 - Press connection, street
Components
 Wall plate
Model 2820.2ZL

P	FTG	L [in]	Wt [lb]	Quantity	Part No	DG
1/2	1/2	8	0.256	25	92609	6
1/2	1/2	15	0.422	25	92616	6

Lav adapters



Viega PEX Press lav adapter Smart Connect feature, Zero Lead
 - Polymer
 - Press connection, lav connection
Model V5613.3

P	Lav	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.050	1	49324	6
1/2	1/2	0.055	1	49333	6
3/4	3/4	0.080	1	49344	6



New

Viega PEX Press adapter Zero Lead
 - Equipped with ferrule Part No 53005
 - Bronze
 - Press connection, compression
Components
 Brass ferrule
Model 2895ZL

P	CTS	Wt [lb]	Quantity	Part No	DG
3/8	1/4		1	97112	6
1/2	1/4		1	97113	6

Closest adapters



Viega PEX Press closet adapter Smart Connect feature, Zero Lead
 - Polymer
 - Press connection, closet connection
Model V5613.4

P	Closest	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.060	1	49223	6
1/2	1/2	0.072	1	49233	6

Outlet boxes



Viega PEX Press outlet box Zero Lead
 - For washing machine
 - Color coded handles
Components
 (2) 1/4 turn brass valves, water hammer arrestors
Model 2872.6ZL

P	Wt [lb]	Quantity	Part No	DG
1/2	1.633	1	97212	6



Viega PEX Press outlet box Zero Lead
 - For ice maker
Components
 1/4 turn brass valve, water hammer arrestor
Model 2872.7ZL

P	Wt [lb]	Quantity	Part No	DG
1/2	1.050	1	97220	6



**Viega PEX Press outlet box
Zero Lead**
- For washing machine
- Color coded handles
Components
(2) ¼ turn brass valves
Model 2872.1US

P	Wt [lb]	Quantity	Part No	DG
½	1.549	1	97001	6



**Viega PEX Press outlet box
Zero Lead**
- For ice maker
Components
¼ turn brass valve
Model 2872.0ZL

P	Wt [lb]	Quantity	Part No	DG
½	0.870	1	98000	6



**Tubing
Zero Lead**
- Only for cold water applications
- For ice maker
- High density polyethylene (HDPE)
Model V5052

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	100	white	1.200	1	43100	1



Box frame
- For washing machine
- Plastic
Model 2885.0ZL

Wt [lb]	Quantity	Part No	DG
0.160	1	97103	6



Box frame
- For ice maker
- Plastic
Model 2873.7ZL

Wt [lb]	Quantity	Part No	DG
0.150	1	97102	6

Tools



Viega PEX Press hand tool
- Ratcheting design, color coded handles
Model 2882US

d	Version	Wt [lb]	Quantity	Part No	DG
¾	green	3.446	1	50000	6
½	yellow	3.409	1	50020	6
¾	blue	3.374	1	50040	6
1	orange	3.564	1	50060	6



Viega PEX Press starter tool set
- Equipped with tubing cutter Model 2889.2US,
Viega PEX Press hand tool case
Model 2880.3, Viega PEX Press hand tool
Part No 50020, 50040
Model 2880.2

for d	Wt [lb]	Quantity	Part No	DG
½, ¾	13.601	1	56000	6



Viega PEX Press complete plumbing tool set
 - Equipped with prep tool Model 2858, tubing cutter Model 2889.2US, Viega PEX Press hand tool Part No 50000, 50020, 50040, 50060
Model 2880.6US

for d	Wt [lb]	Quantity	Part No	DG
3/8, 1/2, 3/4, 1	22.709	1	56010	6



Tubing bender
 - Suitable for Viega FostaPEX tubing Model 2805US, 2806US, 2808US
 - Will not kink tubing
Components
 Formers, case
Model 2889.0US

for d	Wt [lb]	Quantity	Part No	DG
1/2, 5/8, 3/4, 1	8.623	1	56015¹	6

¹⁾ Available while supplies last



Prep tool
 - For removing PE and aluminum layer from Viega FostaPEX tubing
Model 2858

for d	Wt [lb]	Quantity	Part No	DG
1/2, 3/4	1.150	1	54030	6
3/8, 1	1.500	1	54050	6



Blade
 - Spare part for prep tool Model 2858
 - Steel
Model 2858.1

	Wt [lb]	Quantity	Part No	DG
	0.013	2	54075	6



Compact press tool kit
 - For Viega PEX Press connections 3/8" - 1 1/2", Viega ProPress connections up to 1"
 - Not for 2" Viega PEX Press connections
 - Equipped with battery charger Model 2999.81, rechargeable battery Model 2999.8, PEX press jaw compact Part No 56053, 56055, 56056
Components
 Ridgid 210-B tool
Model 2999.6

for d	Wt [lb]	Quantity	Part No	DG
1/2, 3/4, 1	23.993	1	57051	6



Compact press tool kit
 - For Viega PEX Press connections 3/8" - 1 1/2", Viega ProPress connections up to 1"
 - Not for 2" Viega PEX Press connections
 - Equipped with battery charger Model 2999.81, rechargeable battery Model 2999.8
Components
 Ridgid 210-B tool
Model 2999.7

	Wt [lb]	Quantity	Part No	DG
	15.601	1	57057	6



PEX press jaw Compact
 - For Ridgid compact tools, PEX tubing
 - Steel
Model 2884.7US

Press Jaws	Wt [lb]	Quantity	Part No	DG
3/8	2.299	1	56052	6
1/2	2.299	1	56053	6
3/4	2.364	1	56055	6
1	2.469	1	56056	6
1 1/4	2.999	1	56060	6
1 1/2	2.769	1	56061	6



PEX press jaw Standard
 - For RIDgid standard tools, PEX tubing
 - Steel
Model 2899.7US

Press Jaws	Wt [lb]	Quantity	Part No	DG
1/2	3.799	1	56073	6
3/4	3.119	1	56075	6
1	3.899	1	56076	6
1 1/4	4.099	1	56080	6
1 1/2	4.299	1	56081	6
2	9.237	1	56082	6



Tubing cutter
 - For PEX tubing
 - Suitable for Viega FostaPEX tubing
 Model 2805US, 2806US, 2808US
 - Steel
 - Ratcheting design
Model 2840

max d	Wt [lb]	Quantity	Part No	DG
1 1/4	0.590	1	53541¹⁾	5
1 1/2	0.954	1	53551¹⁾	5
2	1.150	1	53561	5

¹⁾ Available while supplies last



Blade
 - Spare part for tubing cutter Part No 53541
 - Steel
Model V5057.1

for d	Wt [lb]	Quantity	Part No	DG
1 1/4	0.190	1	53542¹⁾	5

¹⁾ Available while supplies last



Tubing cutter
 - For PEX tubing
 - Plastic
Model 2889.2US

max d	Wt [lb]	Quantity	Part No	DG
1	0.351	1	21304	5



Tubing cutter
 - For PEX tubing
 - Plastic
Model V5055

max d	Wt [lb]	Quantity	Part No	DG
1 1/2	0.401	1	21307	5



Blade
 - Suitable for tubing cutter Model V5055
 - Steel
Model V5055.1

	Wt [lb]	Quantity	Part No	DG
	0.080	1	21317	5



Wheel cutter
 - For PEX tubing
 - Steel
Model V5059

max d	Wt [lb]	Quantity	Part No	DG
2	0.780	1	53641¹⁾	5

¹⁾ Available while supplies last



Blade
 - Spare part for wheel cutter Model V5059
 - Steel
Model V5059.1

	Wt [lb]	Quantity	Part No	DG
	0.010	1	53642¹⁾	5


¹⁾ Available while supplies last

Accessories



Viega PEX Press sleeve
 - Only for Viega PEX Press polymer fittings
 - Stainless steel
Model V5615.3


d	Wt [lb]	Quantity	Part No	DG
3/8	0.008	10	49901	6
1/2	0.012	10	49902	6
3/4	0.014	10	49903	6
1	0.025	10	49904	6
1 1/4	0.053	10	49905	6
1 1/2	0.065	10	49906	6
2	0.085	10	49607	6



**Lav riser
Zero Lead**
- Does not include lav nut Model V5089
- Equipped with ferrule Model V5085
- PEX
Model V5080

CTS	O.D.	L	Wt [lb]	Quantity	Part No	DG
1/4	3/8	12	0.030	100	58112¹	2
1/4	3/8	15	0.035	100	58115¹	2
1/4	3/8	20	0.048	100	58120	2
1/4	3/8	30	0.071	100	58130	2
1/4	3/8	36	0.085	100	58136	2

¹⁾ Available while supplies last



**Closet riser
Zero Lead**
- Does not include ballcock nut Model V5089.1
- Equipped with ferrule Model V5085
- PEX
Model V5081


CTS	O.D.	L	Wt [lb]	Quantity	Part No	DG
1/4	3/8	12	0.031	100	57112	2
1/4	3/8	15	0.035	100	57115¹	2
1/4	3/8	20	0.050	100	57120	2
1/4	3/8	30	0.080	100	57130¹	2
1/4	3/8	36	0.085	100	57136¹	2

¹⁾ Available while supplies last




**Lav nut
Zero Lead**
- Suitable for lav riser Model V5080
Model V5089

FPT	Wt [lb]	Quantity	Part No	DG
1/2	0.017	100	33705	2



**Ballcock nut
Zero Lead**
- Suitable for closet riser Model V5081
- Plastic
Model V5089.1


FPT	Wt [lb]	Quantity	Part No	DG
3/4	0.023	100	53017	2



**Ferrule
Zero Lead**
- For Viega ManaBloc compression connections, risers, valves
- Plastic
Model V5085


CTS	O.D.	Wt [lb]	Quantity	Part No	DG
1/8	1/4	0.001	100	53000	2
1/4	3/8	0.001	100	53005	2
3/8	1/2	0.001	50	53015	2
1/2	5/8	0.001	100	53020	2
3/4	7/8	0.003	100	53040¹	2

¹⁾ Available while supplies last




**Insert stiffener
Zero Lead**
- For Viega ManaBloc compression connections, risers
- Stainless steel
Model V5086

CTS	O.D.	Wt [lb]	Quantity	Part No	DG
1/4	3/8	0.001	100	56100	2
3/8	1/2	0.003	50	56110	2
1/2	5/8	0.005	50	56120	2
3/4	7/8	0.010	50	56140	2




**Escutcheon
Single
Zero Lead**
- Not for Viega FostaPEX
- Plastic
Model V5088

d	Version	Wt [lb]	Quantity	Part No	DG
3/8	white	0.012	50	53115	2
1/2	white	0.012	50	53120	2



**Escutcheon
Double
Zero Lead**
- Not for Viega FostaPEX
- Plastic
Model V5088.1

d	Version	Wt [lb]	Quantity	Part No	DG
3/8	white	0.016	25	53116	2
1/2	white	0.016	25	53121	2



Sleeve
- Chrome-plated steel
- Finishing
Model 2800.5US

d	L [in]	Wt [lb]	Quantity	Part No	DG
3/8	3 1/2	0.050	10	52500	2
1/2	3 1/2	0.054	10	52520	2



**Bend support
Drop ear**
- Not for Viega FostaPEX
- Plastic-coated steel
Model 2850.1US

for d	Wt [lb]	Quantity	Part No	DG
3/8, 1/2	0.210	25	50520	2



**Bend support
Snap in**
- Not for Viega FostaPEX
- Suitable for bracket Model 2850.4US
- Plastic
Model 2850.3US

for d	Wt [lb]	Quantity	Part No	DG
1/2	0.559	100	51021	2



Bracket
- For mounting on 16" center studs
- Suitable for bend support snap in Model 2850.3US
- Steel
- Mounting holes on 2" centers
Model 2850.4US

d	L [in]	Wt [lb]	Quantity	Part No	DG
1/2	18	0.560	50	51022	2



Bend support
- Not for Viega FostaPEX
- Plastic
Model 2850.2US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.062	25	51000	2
1/2	0.083	25	51020	2
5/8, 3/4	0.155	25	51040	2
1	0.273	25	51060	2
1 1/4	0.440	5	51070	2



Bend support
- For slab
- Not for Viega FostaPEX
- Plastic
Model 2851US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.090	10	15106	4
1/2	0.106	10	15107	4
5/8, 3/4	0.254	10	15108	4
1	0.830	1	15111	4



**Tubing clamp
Turn out**
- For 3/8" tubing and 1/2" tubing with standard or stub-out elbows
- Not for Viega FostaPEX
- Plastic
- Trim tapered tip to use with 1/2" tubing
Model V5071

max d	Wt [lb]	Quantity	Part No	DG
1/2	0.099	25	52130	2



Full clamp
- Plastic
Components
Nail
Model V5092

for d	Wt [lb]	Quantity	Part No	DG
1/2	0.012	100	52220 ¹⁾	2
3/4	0.019	50	52240 ¹⁾	2

¹⁾ Available while supplies last



J-clamp tubing fasteners
 - Plastic
Components
 Nail
Model 2860US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.006	100	52000	2
1/2	0.008	100	52020	2
3/4	0.013	100	52040	2
1	0.021	100	52060	2



Economy PEX tubing clamp
 - Not for Viega FostaPEX
 - Plastic
Model V5095

for d	Wt [lb]	Quantity	Part No	DG
1/4	0.002	100	52100 ¹	2
3/8	0.002	100	52110	2
1/2	0.003	100	52120	2
3/4	0.004	50	52140	2

¹) Available while supplies last



Snap clip
Single
 - Not for Viega FostaPEX
 - Plastic
Model 2862US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.006	100	58015	2
1/2	0.011	100	58020	2
3/4	0.010	100	58040	2
1	0.014	50	58060	2



Snap clip
Double
 - Not for Viega FostaPEX
 - Plastic
Model 2862.1US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.012	50	58016	2
1/2	0.012	50	58021	2



Lock clip
 - Plastic
Model 2863US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.014	100	58071	2
1/2	0.013	100	58072 ¹	2
3/4	0.015	50	58073 ²	2
1	0.025	50	58074	2
1 1/4	0.030	50	58075	2
1 1/2	0.040	25	58076	2
2	0.050	15	58077	2

¹) Suitable for ViegaPEX Barrier tubing Part No 11445, 11450

²) Suitable for Viega FostaPEX tubing Part No 35030, 35031, 35530



Multi-clip
 - Plastic
Components
 Mounting screw
Model 2867US

max d	Wt [lb]	Quantity	Part No	DG
1	0.029	100	52006	2
2	0.090	25	52007	2



Multi-clip
 - Plastic
Components
 Strut clamp
Model 2867.1US

max d	Wt [lb]	Quantity	Part No	DG
2	0.090	25	52017	2



U-channel fastener
- Plastic
- Pre-drilled holes
Model 2864US

W [in]	L [ft]	Wt [lb]	Quantity	Part No	DG
1/2	6 1/2	1.100	16	15310	4



Suspension clip tubing fasteners
- Plastic
Model 2861US

for d	Wt [lb]	Quantity	Part No	DG
1/2	0.009	50	55020	2
3/4	0.012	50	55040	2
1	0.018	50	55060	2
1 1/4	0.022	50	55070	2
1 1/2	0.031	25	55080	2
2	0.036	25	55090	2



Tubing clamp
- Plastic
Model 2868US

for d	Wt [lb]	Quantity	Part No	DG
2	0.044	25	56090	2



Tubing insulator
- Plastic
- Fits 1 3/8" hole
Model V5094

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.018	50	55100	2
3/8, 1/2, 3/4, 1	0.014	25	55165¹⁾	2
1/2	0.019	50	55120	2
3/4	0.014	50	55140	2
1	0.013	50	55160	2

¹⁾ Available while supplies last



Zip tie
- Plastic
Model V5097

L [in]	Wt [lb]	Quantity	Part No	DG
14	0.013	100	43714	2



Pipethon strap
- Plastic
Model V5097.1

Wt [lb]	Quantity	Part No	DG
0.060	20	43701	2



Uncoiler
- Not for 1" tubing or larger, Viega FostaPEX,
center pull coil

Components

Movable metal frame, (2) coil hubs, tube guide

Note

Max. coil size for 3/8" and 1/2" tubing is 1000 ft.
Max. coil size for 3/4" tubing is 500 ft.

Model V5061

Wt [lb]	Quantity	Part No	DG
70.980	1	53509	5

PEX Crimp



PEX Crimp

Offering the reliability and quality needed for potable water systems, Viega PEX Crimp fittings are part of our complete plumbing solution. Matched with our revolutionary Viega ManaBloc water distribution system and the highest rated PEX tubing in the industry, Viega PEX Crimp fittings are a time-tested method of joining PEX.

FEATURES AND BENEFITS

- EcoBrass® fittings provide better corrosion resistance than other brasses
- High-performance PolyAlloy fittings are made in the USA
- Peace of mind from durable materials and quality manufacturing
- In sizes 3/8" to 1"
- Comprehensive 10-year transferable warranty

CODES AND STANDARDS

- ASTM E84: Specification for Surface Burning Characteristics
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for PEX Insert Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- AWWA C904: Cross-linked Polyethylene (PEX) Pressure Pipe for water service
- CAN/ULC S101: Standard Method of Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Method of Test for Surface Burning Characteristics
- CSA International: Canadian Standard Association
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- ICC: International Plumbing Code
- IAPMO: Uniform Plumbing Code
- NSF/ANSI 61: Drinking Water System Components - Health Effects
- NSF/ANSI 61G: Lead Content Evaluation Procedure to meet < 0.25% average lead content
- NSF/ANSI 14: Plastics Piping System Components and Related Materials
- NSPC: National Standard Plumbing Code
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service

ZERO LEAD

References to Zero Lead throughout this publication means product meeting the requirements of NSF 61-G through testing under NSF/ANSI Standard 372 (0.25% or less percent maximum weighted average lead content).

Index

Tubing	108
Elbows	111
Tees	112
Adapters	113
Couplings	114
Valves	114
Viega ManaBlocs	116
Manifolds	121
Stub-Outs	121
Lav adapters	121
Closet adapters	122
Outlet boxes	123
Tools	124
Accessories	125

Tubing



ViegaPEX tubing

Zero Lead

- PEX

- Coil

Technical Data

PEX designation code 5006
Chlorine resistance rating CL5
UV resistance 60 days

ASTM F876, ASTM F877

Model V5001

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	red	5.000	1	32101 ¹	1
3/8	500	red	21.000	1	32105 ¹	1
3/8	1000	red	42.000	1	32100	1
1/2	100	red	5.800	1	32121 ¹	1
1/2	300	red	17.100	1	32123 ¹	1
1/2	500	red	28.000	1	32125 ¹	1
1/2	1000	red	58.000	1	32120	1
3/4	100	red	11.000	1	32141 ¹	1
3/4	300	red	32.100	1	32143 ¹	1
3/4	500	red	53.000	1	32145 ¹	1
3/4	1000	red	106.000	1	32140 ²	1
1	100	red	16.900	1	33323 ¹	1
1	300	red	50.700	1	32163	1
1	500	red	88.000	1	32165	1

¹) center pull coil
²) Available while supplies last



ViegaPEX tubing

Zero Lead

- PEX

- Straight length

Technical Data

PEX designation code 5006
Chlorine resistance rating CL5
UV resistance 60 days

ASTM F876, ASTM F877

Model V5001.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	red	0.540	5	33272	1
1/2	20	red	1.060	5	33120	1
3/4	10	red	1.020	5	33275	1
3/4	20	red	2.040	5	33145	1
1	20	red	3.420	5	33270	1



ViegaPEX tubing

Zero Lead

- PEX

- Coil

Technical Data

PEX designation code 5006
Chlorine resistance rating CL5
UV resistance 60 days

ASTM F876, ASTM F877

Model V5002

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	blue	5.000	1	32201 ¹	1
3/8	500	blue	21.000	1	32205 ¹	1
3/8	1000	blue	42.000	1	32200	1
1/2	100	blue	5.300	1	32221 ¹	1
1/2	300	blue	17.100	1	32223 ¹	1
1/2	500	blue	26.500	1	32225 ¹	1
1/2	1000	blue	55.000	1	32220	1
3/4	100	blue	11.000	1	32241 ¹	1
3/4	300	blue	32.100	1	32243 ¹	1
3/4	500	blue	53.000	1	32245 ¹	1
3/4	1000	blue	106.000	1	32240 ²	1
1	300	blue	50.700	1	32263	1
1	500	blue	88.000	1	32265	1

¹) center pull coil
²) Available while supplies last



ViegaPEX tubing

Zero Lead

- PEX

- Straight length

Technical Data

PEX designation code 5006
Chlorine resistance rating CL5
UV resistance 60 days

ASTM F876, ASTM F877

Model V5002.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	blue	0.540	5	33274	1
1/2	20	blue	1.060	5	33240	1
3/4	10	blue	1.020	5	33277	1
3/4	20	blue	2.040	5	33265	1
1	20	blue	3.420	5	33271	1



ViegaPEX tubing
Zero Lead
 - For installation between studs
 - PEX
 - ManaPac
Components
 Recycled plastic reels
Technical Data
 PEX designation code 5006
 Chlorine resistance rating CL5
 UV resistance 60 days
ASTM F876, ASTM F877
Model V5004

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	2	red/blue	58.000	1	32300	1
3/8	500	1	blue	28.000	1	32905	1
3/8	500	1	red	28.000	1	32805	1
1/2	300	2	red/blue	48.000	1	32326	1
1/2	300	1	blue	23.100	1	32923	1
1/2	300	1	red	23.100	1	32823	1



ViegaPEX tubing
Zero Lead
 - PEX
 - Coil
Technical Data
 PEX designation code 5006
 Chlorine resistance rating CL5
 UV resistance 60 days
ASTM F876, ASTM F877
Model V5003

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/4	100	white	3.200	1	32011	1
1/4	500	white	14.000	1	32015	1
3/8	100	white	5.000	1	32001¹	1
3/8	500	white	21.000	1	32005¹	1
3/8	1000	white	42.000	1	32000	1
1/2	100	white	6.000	1	32021¹	1
1/2	300	white	17.100	1	32023¹	1
1/2	500	white	28.000	1	32025¹	1
1/2	1000	white	55.000	1	32020	1
3/4	100	white	11.000	1	32041¹	1
3/4	300	white	32.100	1	32043¹	1
3/4	500	white	53.000	1	32045¹	1
3/4	1000	white	106.000	1	32040²	1
1	100	white	17.000	1	32061¹	1
1	300	white	51.900	1	32063	1
1	500	white	88.000	1	32065	1

¹⁾ center pull coil
²⁾ Available while supplies last



ViegaPEX tubing
Zero Lead
 - PEX
 - Straight length
Technical Data
 PEX designation code 5006
 Chlorine resistance rating CL5
 UV resistance 60 days
ASTM F876, ASTM F877
Model V5003.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	white	0.540	5	33273	1
1/2	20	white	1.080	5	33020	1
3/4	10	white	1.020	5	33276	1
3/4	20	white	2.060	5	33045	1
1	20	white	3.420	5	33061	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5005

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	red	21.000	1	32505	1
1/2	100	red	6.000	1	32521	1
1/2	300	red	17.100	1	32523	1
1/2	500	red	28.000	1	32525	1
1/2	1000	red	55.000	1	32520	1
3/4	100	red	11.000	1	32541	1
3/4	300	red	32.100	1	32543	1
3/4	500	red	53.000	1	32545	1
1	100	red	17.000	1	32551	1
1	300	red	51.900	1	32553	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5005.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	red	0.550	50	33529	1
1/2	20	red	1.180	50	33520	1
3/4	10	red	0.550	25	33549	1
3/4	20	red	2.020	25	33540	1
1	20	red	3.480	5	33551	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Coil

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5006

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	blue	21.000	1	32605	1
1/2	100	blue	6.000	1	32621	1
1/2	300	blue	15.900	1	32623	1
1/2	500	blue	28.000	1	32625	1
1/2	1000	blue	55.000	1	32620	1
3/4	100	blue	11.000	1	32641	1
3/4	300	blue	30.900	1	32643	1
3/4	500	blue	53.000	1	32645	1
1	100	blue	17.000	1	32651	1
1	300	blue	51.900	1	32653	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Straight length

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5006.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	blue	0.550	50	33629	1
1/2	20	blue	1.180	50	33620	1
3/4	10	blue	0.550	25	33649	1
3/4	20	blue	2.020	25	33645	1
1	20	blue	3.480	5	33651	1



ViegaPEX Ultra tubing

Zero Lead

- For installation between studs
- PEX
- ManaPac

Components

Recycled plastic reels

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5008

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	2	red/blue	116.000	1	33300	1
3/8	500	1	blue	28.000	1	33905	1
3/8	500	1	red	28.000	1	33805	1
1/2	300	2	red/blue	48.000	1	33326	1
1/2	300	1	blue	23.100	1	33923	1
1/2	300	1	red	23.100	1	33823	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Coil

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5007

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	white	21.000	1	32405	1
1/2	100	white	6.000	1	32421	1
1/2	300	white	17.100	1	32423	1
1/2	500	white	28.000	1	32425	1
3/4	100	white	11.000	1	32441	1
3/4	300	white	32.100	1	32443	1
3/4	500	white	53.000	1	32445	1
1	100	white	17.000	1	32461	1
1	300	white	51.900	1	33362	1
1	500	white	88.000	1	32465	1



ViegaPEX Ultra tubing

Zero Lead

- PEX
- Straight length

Technical Data

PEX designation code 5306
Chlorine resistance rating CL5
UV resistance 6 months

ASTM F876, ASTM F877

Model V5007.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	white	0.550	50	33429	1
1/2	20	white	1.100	50	33420	1
3/4	10	white	0.550	25	33459	1
3/4	20	white	2.100	25	33405	1
1	20	white	3.480	5	33461	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5009

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	black	21.000	1	32705 ¹⁾	1
1/2	100	black	5.500	1	32721	1
1/2	300	black	16.500	1	32723	1
1/2	500	black	29.000	1	32725	1

¹⁾ Available while supplies last



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
UL listed for NFPA 13D systems, ASTM F876,
ASTM F877
Model V5009.1

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/4	100	black	10.500	1	34741	1
3/4	300	black	31.500	1	34743	1
3/4	500	black	52.500	1	34745	1
1	100	black	17.400	1	34761	1
1	500	black	87.000	1	34765	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5009.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	20	black	1.100	50	33720	1



ViegaPEX Ultra tubing
Zero Lead
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 Chlorine resistance rating CL5
 UV resistance 6 months
UL listed for NFPA 13D systems, ASTM F876,
ASTM F877
Model V5009.51

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/4	20	black	2.100	25	35745	1
1	20	black	3.480	5	35761	1

Elbows



Viega PEX Crimp elbow 90°
Zero Lead
 - Brass
 - Crimp connection
Model V5016ZL

Crimp1	Crimp2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.028	50	46922	2
1/2	1/2	0.045	50	46933	2
3/4	1/2	0.068	25	46243	2
3/4	3/4	0.085	25	46944	2
1	1	0.160	10	46955	2



Viega PEX Crimp elbow 90°
Zero Lead
 - PolyAlloy
 - Crimp connection
Model V5216

Crimp1	Crimp2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.007	50	43210	3
1/2	1/2	0.010	50	43220	3
3/4	3/4	0.021	25	43240	3
3/4	1/2	0.016	25	43242	3
1	1	0.046	10	43260	3



**Viega PEX Crimp elbow 90°
Zero Lead**
- Brass
- Crimp connection, male pipe thread
Model V5014ZL

Crimp	MPT	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.104	10	46822 ¹⁾	2
1/2	3/8	0.103	10	46232	2
1/2	1/2	0.196	10	46821	2
3/4	3/4	0.240	10	46245 ¹⁾	2

¹⁾ Available while supplies last



**Viega PEX Crimp elbow 90°
Drop ear
Zero Lead**
- Brass
- Crimp connection, female pipe thread
Model V5027ZL

Crimp	FPT	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.193	10	46233	2
3/4	3/4	0.309	10	46244	2



**Viega PEX Compression Elbow 90°
Zero Lead**
- For dishwasher, connecting 3/8" compression to 3/4" hose supply connection
- Equipped with ferrule Part No 53015
- Copper
- Hose connection
Model V5053

CTS	Hose	Wt [lb]	Quantity	Part No	DG
3/8	3/4	0.230	1	46743	2



**Viega PEX Crimp elbow 90°
Zero Lead**
- Copper
- Crimp connection, female copper tube size
Model V5021

Crimp	C	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.048	50	44305 ¹⁾	2
1/2	1/2	0.048	50	44325	2
3/4	3/4	0.111	25	44345	2

¹⁾ Available while supplies last



**Viega PEX Crimp elbow 90°
Zero Lead**
- Copper
- Crimp connection, street
Model V5020

Crimp	FTG	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.045	50	44302 ¹⁾	2
1/2	1/2	0.045	50	44320	2
3/4	3/4	0.100	25	44340	2

¹⁾ Available while supplies last

Tees



**Viega PEX Crimp tee
Zero Lead**
- Brass
- Crimp connection
Model V5018ZL

Crimp1	Crimp2	Crimp3	Wt [lb]	Quantity	Part No	DG
3/8	3/8	3/8	0.038	50	46500	2
1/2	1/2	1/2	0.055	50	46520	2
1/2	1/2	3/4	0.080	25	46524	2
3/4	1/2	1/2	0.079	25	46433	2
3/4	1/2	3/4	0.102	25	46435	2
3/4	3/4	1/2	0.082	25	46443	2
3/4	3/4	3/4	0.102	25	46540	2
3/4	3/4	1	0.139	10	46445	2
1	3/4	3/4	0.150	10	46544	2
1	3/4	1	0.170	10	46545	2
1	1	1/2	0.208	10	46553	2
1	1	3/4	0.153	10	46554	2
1	1	1	0.185	10	46560	2



**Viega PEX Crimp tee
Zero Lead**
- PolyAlloy
- Crimp connection
Model V5218

Crimp1	Crimp2	Crimp3	Wt [lb]	Quantity	Part No	DG
3/8	3/8	3/8	0.005	50	43500	3
1/2	1/2	1/2	0.014	50	43520	3
1/2	1/2	3/4	0.019	25	43334	3
3/4	1/2	1/2	0.021	25	43433	3
3/4	1/2	3/4	0.026	25	43434	3
3/4	3/4	1/2	0.023	25	43443	3
3/4	3/4	3/4	0.029	25	43540	3
3/4	3/4	1	0.038	10	43445	3
1	3/4	3/4	0.047	10	43544	3
1	3/4	1	0.054	10	43545	3
1	1	1/2	0.043	10	43553	3
1	1	3/4	0.046	10	43554	3
1	1	1	0.059	10	43560	3

Adapters


**Viega PEX Crimp adapter
Zero Lead**
- Brass
- Crimp connection, male pipe thread
Model V5011ZL

Crimp	MPT	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.102	50	46302	2
1/2	1/2	0.101	50	46321	2
1/2	3/4	0.131	25	46324	2
3/4	1/2	0.094	25	46342	2
3/4	3/4	0.139	25	46340	2
3/4	1	0.202	10	46446	2
1	3/4	0.138	10	46361	2
1	1	0.235	10	46366	2



**Viega PEX Crimp adapter
Zero Lead**
- Brass
- Crimp connection, female pipe thread
Model V5012ZL

Crimp	FPT	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.101	25	46323	2
1/2	1/2	0.090	25	46333	2
1/2	3/4	0.139	25	46334	2
3/4	3/4	0.216	25	46344	2
3/4	1	0.217	10	46345	2
1	1	0.262	10	46355	2



**Viega PEX Crimp adapter
Zero Lead**
- Brass
- Crimp connection, polybutylene (PB)
connection

Note

Use Viega PEX Crimp ring model V5019.9 for PB connection

Model V5017ZL

Crimp	PB	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.022	100	46620	2
1/2	1/2	0.031	100	46630	2
3/4	3/4	0.057	50	46641	2
1	1	0.075	10	46650	2



**Viega PEX Crimp adapter
Zero Lead**
- Brass
- Crimp connection, polyethylene (PE)
connection

Note

Use standard stainless steel hose clamp for PE connection (not included)

Model V5047ZL

Crimp	PE	Wt [lb]	Quantity	Part No	DG
3/4	3/4	0.104	25	46145	2
1	1	0.157	10	46156	2



**Viega PEX Crimp adapter
Zero Lead**
- Brass
- Crimp connection, female copper tube size
Model V5045ZL

Crimp	C	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.036	50	46635	2
3/4	3/4	0.076	25	46645	2
1	1	0.108	10	40655 ¹⁾	2

¹⁾ copper



**Viega PEX Crimp adapter
Zero Lead**
- Brass
- Crimp connection, street
Model V5046ZL

Crimp	FTG	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.034	50	46633	2
3/4	3/4	0.064	25	46644	2
1	1	0.103	10	60651¹⁾	2

¹⁾ copper



**Viega PEX Crimp adapter
Zero Lead**
- Brass
- Crimp connection, female copper tube size, street
Note
Copper connection can be used as either male or female connection.
Model V5024ZL

Crimp	C	FTG	Wt [lb]	Quantity	Part No	DG
3/8	1/4	3/8	0.024	50	46621¹⁾	2
3/8	3/8	1/2	0.032	50	46622	2
1/2	1/4	3/8	0.032	50	46631¹⁾	2
1	3/4	1	0.182	10	46654	2

¹⁾ Available while supplies last

Couplings



**Viega PEX Crimp coupling
Zero Lead**
- Brass
- Crimp connection
Model V5015ZL

Crimp1	Crimp2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.019	100	46422	2
1/2	3/8	0.023	100	46432	2
1/2	1/2	0.026	100	46434	2
3/4	1/2	0.041	50	46441	2
3/4	3/4	0.047	50	46444	2
1	3/4	0.070	10	46454	2
1	1	0.064	10	46455	2



**Viega PEX Crimp coupling
Zero Lead**
- PolyAlloy
- Crimp connection
Model V5215

Crimp1	Crimp2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.004	50	43402	3
1/2	1/2	0.006	100	43403	3
1/2	3/8	0.006	50	43332	3
3/4	1/2	0.010	50	43343	3
3/4	3/4	0.012	50	43404	3
1	1/2	0.019	10	43353	3
1	3/4	0.021	10	43354	3
1	1	0.024	10	43355	3



**Viega PEX Crimp test plugs
Zero Lead**
- PLS
- Crimp connection
Model V5058

Crimp	Wt [lb]	Quantity	Part No	DG
3/8	0.003	100	43702	2
1/2	0.004	100	43723	2
3/4	0.008	50	43744	2
1	0.015	50	43765	2

Valves



**Viega PEX Crimp ball valve
Zero Lead**
- Brass
- Crimp connection
- 1/4 turn, full port
Model V5037ZL

Crimp1	Crimp2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.306	10	46010	2
1/2	1/2	0.277	10	46031	2
3/4	3/4	0.395	10	46044	2
1	1	0.711	10	46060	2



**Viega PEX Crimp ball valve
Zero Lead**
- Chrome-plated brass
- Crimp connection
- 1/4 turn, full port
Model V5023ZL

Crimp1	Crimp2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.277	10	46021	2



**Viega PEX Crimp valve
Zero Lead**
- PolyAlloy
- Crimp connection
- ¼ turn
Model V5236

Crimp1	Crimp2	Wt [lb]	Quantity	Part No	DG
½	½	0.066	10	43030	3
¾	¾	0.080	10	43040	3



**Viega PEX Crimp stop valve
Straight
Zero Lead**
- Equipped with Viega PEX Crimp ring
Model V5019.9, ferrule Part No 53005
- Chrome-plated brass
- Crimp connection
- ¼ turn
Model V5026ZL

Crimp	CTS	Wt [lb]	Quantity	Part No	DG
¾	¼	0.321	1	46001	2
½	¼	0.295	1	46022	2



**Viega PEX Crimp stop valve
Angled
Zero Lead**
- Equipped with Viega PEX Crimp ring
Model V5019.9, ferrule Part No 53005
- Chrome-plated brass
- Crimp connection
- ¼ turn
Model V5064ZL

Crimp	CTS	Wt [lb]	Quantity	Part No	DG
¾	¼	0.340	1	46002	2
½	¼	0.330	1	46025	2



**Viega PEX Crimp stop valve
Straight
Zero Lead**
- PolyAlloy
- Crimp connection, lav connection
- ¼ turn
Model V5036.30

Crimp	Lav	Wt [lb]	Quantity	Part No	DG
¾	½	0.090	10	43023	3
½	½	0.090	10	43031	3



**Viega PEX Crimp stop valve
Straight
Zero Lead**
- PolyAlloy
- Crimp connection, closet connection
- ¼ turn
Model V5036.31

Crimp	Closet	Wt [lb]	Quantity	Part No	DG
¾	½	0.100	10	43002	3
½	½	0.097	10	43003	3



**Viega PEX Crimp adapter
Straight
Zero Lead**
- For ice maker
- Brass
- Crimp connection
Model V5051ZL


Crimp	CTS	Wt [lb]	Quantity	Part No	DG
½	⅝	0.081	1	46322	2



**Viega PEX Crimp tee
Zero Lead**
- For ice maker
- Brass
- Crimp connection
Model V5062ZL

Crimp1	Crimp2	CTS	Wt [lb]	Quantity	Part No	DG
½	½	⅝	0.150	1	46521	2

Viega ManaBlocs



Viega ManaBloc distribution manifold

Zero Lead

- Crimp connection
- Color coded ports for hot and cold water

Components


¼ turn valves, T-handle valve key

Note

Does not include supply connections

Model V5030.5

Adapter	Port(s)	d	hot	cold	Wt [lb]	Quantity	Part No	DG
PolyAlloy	14	¾	6	8	7.598	1	50142	2
PolyAlloy	14	½	6	8	5.415	1	50143	2
PolyAlloy	24	½	9	15	7.718	1	50243	2
PolyAlloy	30	½	12	18	9.668	1	50303	2
PolyAlloy	36	½	14	22	11.275	1	50363	2



Viega ManaBloc distribution manifold

Zero Lead

- Crimp connection
- Combination port sizes, color coded ports for hot and cold water

Components

¼ turn valves, T-handle valve key

Note

Does not include supply connections

Model V5030.51

Adapter	Port(s)	d1	hot1	cold1	d2	hot2	cold2	Wt [lb]	Quantity	Part No	DG
PolyAlloy	18	¾	6	7	½	2	3	6.328	1	51618	2
PolyAlloy	24	¾	7	11	½	2	4	8.007	1	50624	2
PolyAlloy	30	¾	10	12	½	2	6	9.833	1	50630	2
PolyAlloy	36	¾	11	15	½	3	7	11.481	1	50636	2



Viega MiniBloc zoning manifold

Zero Lead

- Crimp connection
- Blue color coded ports for cold water

Components


¼ turn valves, T-handle valve key, optional red valve caps

Note

Does not include supply connections

Model V5031.5

Adapter	Port(s)	d	Wt [lb]	Quantity	Part No	DG
PolyAlloy	3	½	2.119	1	50033	2
PolyAlloy	4	½	1.919	1	50043	2
PolyAlloy	6	½	2.874	1	50063	2
PolyAlloy	8	½	3.199	1	50083	2



Viega MiniBloc zoning manifold

Zero Lead

- Crimp connection
- Color coded ports for hot and cold water

Components

¼ turn valves, T-handle valve key

Note

Does not include supply connections

Model V5067

Adapter	Port(s)	d	hot	cold	Wt [lb]	Quantity	Part No	DG
PolyAlloy	5	½	2	3	2.523	1	51063	2
PolyAlloy	7	½	3	4	3.244	1	51073	2
PolyAlloy	10	½	4	6	4.005	1	51003	2



Viega MiniBloc zoning manifold

Zero Lead

- For combination systems
- Crimp connection
- Color coded ports for hot and cold water

Components

¼ turn valves, T-handle valve key

Note

Does not include supply connections

Model V5066ZL

Adapter	Port(s)	d	hot	cold	Wt [lb]	Quantity	Part No	DG
brass	5	½	2	3	2.819	1	42063	2
brass	7	½	3	4	3.837	1	42073	2
brass	10	½	4	6	4.587	1	42003	2



Viega PEX Crimp port adapter

Zero Lead

- For connecting distribution lines to Viega ManaBloc and Viega MiniBloc
- PolyAlloy
- Crimp connection, Viega ManaBloc port connection

Model V5039.1

Crimp	Port	Wt [lb]	Quantity	Part No	DG
⅜	⅜	0.040	6	51133	2
⅜	½	0.040	6	50023	2
½	⅜	0.026	6	51123	2
½	½	0.040	6	50133	2



Viega PEX Crimp port adapter

Zero Lead

- For connecting distribution lines to Viega ManaBloc and Viega MiniBloc
- Brass
- Crimp connection, Viega ManaBloc port connection

Model V5039ZL

Crimp	Port	Wt [lb]	Quantity	Part No	DG
⅜	½	0.085	6	46624	2
½	½	0.090	6	46634	2



Viega PEX Crimp supply adapter

Zero Lead

- For connecting PEX supply lines to Viega ManaBloc and Viega MiniBloc
- PolyAlloy
- Crimp connection, Viega ManaBloc supply connection

Model V5213

P	Supply	Wt [lb]	Quantity	Part No	DG
¾	1	0.095	5	50141	2
1	1	0.100	5	50151	2



Viega PEX Crimp supply adapter

Zero Lead

- For connecting PEX supply lines to Viega ManaBloc and Viega MiniBloc
- Brass
- Crimp connection, Viega ManaBloc supply connection

Model V5034ZL

Crimp	Supply	Wt [lb]	Quantity	Part No	DG
¾	1	0.198	5	46414	2
1	1	0.206	5	46416	2



Viega ManaBloc distribution manifold

Zero Lead

- Compression connection
- Color coded ports for hot and cold water

Components

¼ turn valves, T-handle valve key

Note

Does not include supply connections

Model V5030

Adapter	Port(s)	d	hot	cold	Wt [lb]	Quantity	Part No	DG
compression	14	3/8	6	8	5.280	1	36142	2
compression	18	3/8	8	10	6.201	1	36182	2
compression	24	3/8	9	15	7.774	1	36242	2
compression	30	3/8	12	18	9.117	1	36302	2
compression	36	3/8	14	22	10.958	1	36362	2
compression	14	1/2	6	8	5.578	1	36144	2
compression	18	1/2	8	10	6.463	1	36183	2
compression	24	1/2	9	15	8.158	1	36243	2
compression	30	1/2	12	18	9.887	1	36303	2
compression	36	1/2	14	22	11.537	1	36363	2



Viega ManaBloc distribution manifold

Zero Lead

- Compression connection
- Combination port sizes, color coded ports for hot and cold water

Components

¼ turn valves, T-handle valve key

Note

Does not include supply connections

Model V5030.2

Adapter	Port(s)	d1	hot1	cold1	d2	hot2	cold2	Wt [lb]	Quantity	Part No	DG
compression	24	3/8	7	11	1/2	2	4	7.918	1	36624	2
compression	30	3/8	10	12	1/2	2	6	9.823	1	36630	2
compression	36	3/8	11	15	1/2	3	7	11.397	1	36636	2



Viega MiniBloc zoning manifold

Zero Lead

- Compression connection
- Blue color coded ports for cold water

Components

¼ turn valves, T-handle valve key, optional red valve caps

Note

Does not include supply connections

Model V5031

Adapter	Port(s)	d	Wt [lb]	Quantity	Part No	DG
compression	3	3/8	2.024	1	36032	2
compression	4	3/8	2.189	1	36042	2
compression	6	3/8	2.354	1	36062	2
compression	8	3/8	3.549	1	36082	2
compression	3	1/2	2.119	1	36033	2
compression	4	1/2	2.344	1	36043	2
compression	6	1/2	2.519	1	36063	2
compression	8	1/2	3.299	1	36083	2



Viega ManaBloc lock-in nut

Zero Lead

- For use with Viega ManaBloc compression connections
- Spare part for Viega ManaBloc distribution manifold Model V5030, V5030.2, Viega MiniBloc zoning manifold Model V5031
- Plastic
- Compression

Model V5036.24

CTS	Wt [lb]	Quantity	Part No	DG
3/8	0.020	100	36002	2
1/2	0.040	100	36003	2



Viega ManaBloc lock-in insert
Zero Lead
 - For use with Viega ManaBloc compression connections
 - Plastic
Model V5036.25

CTS	O.D.	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.002	100	36402	2
1/2	5/8	0.002	100	36403	2



Ferrule
Zero Lead
 - For Viega ManaBloc compression connections, risers, valves
 - Plastic
Model V5085

CTS	O.D.	Wt [lb]	Quantity	Part No	DG
1/8	1/4	0.001	100	53000	2
1/4	3/8	0.001	100	53005	2
3/8	1/2	0.001	50	53015	2
1/2	5/8	0.001	100	53020	2
3/4	7/8	0.003	100	53040 ¹⁾	2

¹⁾ Available while supplies last



Insert stiffener
Zero Lead
 - For Viega ManaBloc compression connections, risers
 - Stainless steel
Model V5086

CTS	O.D.	Wt [lb]	Quantity	Part No	DG
1/4	3/8	0.001	100	56100	2
3/8	1/2	0.003	50	56110	2
1/2	5/8	0.005	50	56120	2
3/4	7/8	0.010	50	56140	2



Viega ManaBloc wrench
 - For Viega ManaBloc compression connections
 - Chrome-plated steel
Model V5036.23

for d	Wt [lb]	Quantity	Part No	DG
3/8, 1/2	0.600	1	50631	5



Viega ManaBloc supply adapter
Zero Lead
 - For connecting CTS-sized supply lines to Viega ManaBloc or Viega MiniBloc
 - Equipped with insert stiffener Model V5086
 - Brass
 - Compression, Viega ManaBloc supply connection
Model V5032ZL

CTS	Supply	Wt [lb]	Quantity	Part No	DG
3/4	1	0.395	5	46346	2



Viega ManaBloc supply adapter
Zero Lead
 - For connecting FPT supply lines to Viega ManaBloc and Viega MiniBloc
 - Brass
 - Male pipe thread, Viega ManaBloc supply connection
Model V5033ZL

MPT	Supply	Wt [lb]	Quantity	Part No	DG
3/4	1	0.329	5	46646	2
1	1	0.399	5	46656	2



Port nut
Zero Lead
 - Not suitable for Viega ManaBloc distribution manifold Model V5030, V5030.2, Viega MiniBloc zoning manifold Model V5031
 - Plastic
Model V5039.8

d	Wt [lb]	Quantity	Part No	DG
1/2	0.260	6	53006	2



Port cap
Zero Lead
 - For Viega ManaBloc, Viega MiniBloc
 - Plastic
Model V5087

d	Wt [lb]	Quantity	Part No	DG
3/8	0.020	6	36204	2
1/2	0.037	6	36205	2



**Supply cap
Zero Lead**
- For Viega ManaBloc, Viega MiniBloc
- Brass
Model V5036.10

d	Wt [lb]	Quantity	Part No	DG
1	0.082	5	53601	2



Viega ManaBloc mounting set
- For mounting Viega ManaBloc between studs
- Steel
- Pre-drilled to mount on 16" center studs
Components
(2) mounting straps, (4) screws
Model V5038

	Wt [lb]	Quantity	Part No	DG
	0.681	1	45716	2



Replacement kit
- For Viega ManaBloc and Viega MiniBloc valve stems, ports 1/2" or 3/8"
- 1/4 turn
Components
Red valve, blue valve, valve removal tool, T-handle valve key
Model 2870.91

	Wt [lb]	Quantity	Part No	DG
	0.150	1	51602	2



T-handle valve key
- For Viega ManaBloc, Viega MiniBloc
Model V5039.7

	Wt [lb]	Quantity	Part No	DG
	0.040	1	50601	2



Viega ManaBloc access panel
- Plastic
Note
Can be mounted to open vertically or horizontally
Model V5099

W [in]	L [in]	max. Ports	Wt [lb]	Quantity	Part No	DG
14	18	14	1.350	1	50718	2
14	26	16	0.050	1	50726	2
14	30	24	2.434	1	50730	2
14	39	36	3.249	1	50739	2
14	39	36	4.999	1	50839 ^{2,1}	2

¹) Available while supplies last
²) transparent



Viega ManaBloc access panel
- Metal
- 3 hour fire rating
Components
(2) knurled knobs, (2) keys
Note
Can be mounted to open vertically or horizontally
UL listed
Model V5099.1

W [in]	L [in]	max. Ports	Wt [lb]	Quantity	Part No	DG
14	40	30	26.258	1	50740	2
14	48	36	31.641	1	50748 ¹	2

¹) Available while supplies last

Manifolds



Viega PEX Crimp manifold
Zero Lead
 - Only use with lock clip Part No 58075
 - PolyAlloy
 - Crimp connection
 - Flow through
Note
 Does not include mounting hardware
Model V5031.2

Crimp1	Crimp2	Crimp3	Outlet(s)	Wt [lb]	Quantity	Part No	DG
3/4	3/4	1/2	2	0.135	10	65152	2
3/4	3/4	1/2	3	0.197	10	65153	2
3/4	3/4	1/2	4	0.249	10	65154	2
1	3/4	1/2	4	0.140	10	65254	2
1	1	1/2	6	0.309	10	65256	2
1	1	1/2	8	0.396	5	65258	2



Viega PEX Crimp manifold
Zero Lead
 - Only use with lock clip Part No 58075
 - PolyAlloy
 - Crimp connection
 - Closed
Note
 Does not include mounting hardware
Model V5031.22

Crimp1	Crimp2	Crimp3	Outlet(s)	Wt [lb]	Quantity	Part No	DG
closed	3/4	1/2	4	0.217	10	65104	2
closed	1	1/2	6	0.302	10	65206	2

Stub-Outs



Viega PEX Crimp stub-out 90°
Zero Lead
 - Copper
 - Crimp connection, street
Model V5070

Crimp	FTG	L1 [in]	L2 [in]	Wt [lb]	Quantity	Part No	DG
3/8	1/2	3 1/2	8	0.295	50	44208	2
1/2	1/2	3 1/2	6	0.195	50	44226	2
1/2	1/2	3 1/2	8	0.235	50	44228	2
3/4	1/2	3 1/2	8	0.432	50	44240	2



Viega PEX Crimp stub-out 90°
Zero Lead
 - Copper
 - Crimp connection, street
Components
 Wall plate
Model V5070.1

Crimp	FTG	L1 [in]	L2 [in]	Wt [lb]	Quantity	Part No	DG
3/8	1/2	3 1/2	8	0.286	25	44209	2
1/2	1/2	3 1/2	6	0.234	25	44227	2
1/2	1/2	3 1/2	8	0.277	25	44229	2

Lav adapters



Viega PEX Crimp lav adapter
Zero Lead
 - Brass
 - Crimp connection, lav connection
Components
 Plastic nut
Model V5075ZL

Crimp	Lav	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.074	1	46023	2
1/2	1/2	0.073	1	46033	2



Viega PEX Crimp lav adapter

Zero Lead

- Equipped with Viega PEX Crimp ring Model V5019.9, ferrule Part No 53005
- Brass
- Crimp connection, compression

Components

- Brass ferrule

Model V5077ZL

Crimp	CTS	Wt [lb]	Quantity	Part No	DG
3/8	1/4	0.120	1	46032	2
1/2	1/4	0.115	1	46331	2



Viega PEX Crimp lav adapter

Zero Lead

- PolyAlloy
- Crimp connection, lav connection

Model V5263

Crimp	Lav	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.025	1	43323	3
1/2	1/2	0.025	1	43333	3
3/4	3/4	0.040	1	43344	3



Viega PEX Crimp lav elbow 90°

Zero Lead

- PolyAlloy
- Crimp connection, lav connection

Components

- Plastic nut

Model V5255

Crimp	Lav	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.027	50	43232	3
1/2	1/2	0.029	50	43233	3
3/4	3/4	0.053	25	43244	3



Viega PEX Crimp lav elbow 90°

Zero Lead

- Copper
- Crimp connection, lav connection

Components

- Plastic nut

Model V5076

Crimp	Lav	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.085	1	44201	2



Cone seal

Zero Lead

- Spare part for Viega PEX Crimp lav adapter Model V5075ZL, V5263, Viega PEX Crimp lav elbow 90° Model V5255, Viega PEX Crimp stop valve straight Model V5036.30, Viega PEX Press lav adapter Model V5613.3

Model V5084.1

d	Wt [lb]	Quantity	Part No	DG
1/2	0.002	100	43721	2
3/4	0.004	100	43740	2

Closest adapters



Viega PEX Crimp closet adapter

Zero Lead

- Brass
- Crimp connection, closet connection

Components

- Plastic nut

Model V5072ZL

Crimp	Closest	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.070	1	46223	2
1/2	1/2	0.085	1	46234	2



Viega PEX Crimp closet adapter

Zero Lead

- PolyAlloy
- Crimp connection, closet connection

Components

- Plastic nut

Model V5257

Crimp	Closest	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.036	1	43300	3
1/2	1/2	0.035	1	43320	3



Cone seal
Zero Lead
 - Spare part for Viega PEX Crimp closet adapter Model V5072ZL, V5257, Viega PEX Press closet adapter Model V5613.4
Model V5084

d	Wt [lb]	Quantity	Part No	DG
1/2	0.005	100	43820	2



Viega PEX Crimp swivel connector
Zero Lead
 - For hot water heater
 - Copper
 - Crimp connection, female pipe thread
Model V5048ZL

Crimp	FPT	L [in]	Wt [lb]	Quantity	Part No	DG
3/4	3/4	18	0.570	25	46764	2

Outlet boxes



Viega PEX Crimp outlet box
Zero Lead
 - For ice maker
Components
 1/4 turn brass valve, water hammer arrestor
Model 2872.8ZL

Crimp	Wt [lb]	Quantity	Part No	DG
3/8	1.060	1	46710	2
1/2	1.080	1	46720	2



Viega PEX Crimp outlet box
Zero Lead
 - For washing machine
 - Color coded handles
Components
 (2) 1/4 turn brass valves, water hammer arrestors
Model 2872.9ZL

Crimp	Wt [lb]	Quantity	Part No	DG
1/2	1.640	1	46730	2



Viega PEX Crimp outlet box
Zero Lead
 - For ice maker
Components
 1/4 turn brass valve
Model V5073

Crimp	Wt [lb]	Quantity	Part No	DG
3/8		1	43700	2
1/2	1.095	1	43722	2



Viega PEX Crimp outlet box
Zero Lead
 - For washing machine
 - Color coded handles
Components
 (2) 1/4 turn brass valves
Model V5073.5

Crimp	Wt [lb]	Quantity	Part No	DG
1/2	2.344	1	43720	2



Tubing
Zero Lead
 - Only for cold water applications
 - For ice maker
 - High density polyethylene (HDPE)
Model V5052

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/8	100	white	1.200	1	43100	1

Tools



Viega PEX Crimp hand tool
Full circle
 - Soft touch
Model V5082.5

for d	Wt [lb]	Quantity	Part No	DG
3/8	3.404	1	41700 ¹⁾	5
1/2	3.309	1	41720	5
1/2, 3/4	4.569	1	41724	5
3/4	3.474	1	41740	5
1	4.599	1	41760	5

¹⁾ Available while supplies last



Viega PEX Crimp hand tool
 - Compact angled, color coded handles
Model V5082.4

d	Version	Wt [lb]	Quantity	Part No	DG
3/8	green	2.519	1	41703	5
1/2	yellow	2.442	1	41723	5
3/4	blue	2.734	1	41744	5



Viega PEX Crimp caliper
Model V5054

for d	Wt [lb]	Quantity	Part No	DG
3/8, 1/2, 3/4	0.085	1	53507	5
1	0.065	1	53511	5



Tubing cutter
 - For PEX tubing
 - Suitable for Viega FostaPEX tubing
 Model 2805US, 2806US, 2808US
 - Steel
 - Ratcheting design
Model 2840

max d	Wt [lb]	Quantity	Part No	DG
1 1/4	0.590	1	53541 ¹⁾	5
1 1/2	0.954	1	53551 ¹⁾	5
2	1.150	1	53561	5

¹⁾ Available while supplies last



Blade
 - Spare part for tubing cutter Part No 53541
 - Steel
Model V5057.1

for d	Wt [lb]	Quantity	Part No	DG
1 1/4	0.190	1	53542 ¹⁾	5

¹⁾ Available while supplies last



Tubing cutter
 - For PEX tubing
 - Plastic
Model 2889.2US

max d	Wt [lb]	Quantity	Part No	DG
1	0.351	1	21304	5



Tubing cutter
 - For PEX tubing
 - Plastic
Model V5055

max d	Wt [lb]	Quantity	Part No	DG
1 1/2	0.401	1	21307	5



Blade
 - Suitable for tubing cutter Model V5055
 - Steel
Model V5055.1

	Wt [lb]	Quantity	Part No	DG
	0.080	1	21317	5



Wheel cutter
 - For PEX tubing
 - Steel
Model V5059

max d	Wt [lb]	Quantity	Part No	DG
2	0.780	1	53641 ¹⁾	5

¹⁾ Available while supplies last



Blade
 - Spare part for wheel cutter Model V5059
 - Steel
Model V5059.1

	Wt [lb]	Quantity	Part No	DG
	0.010	1	53642 ¹⁾	5

¹⁾ Available while supplies last

Accessories



Viega PEX Crimp ring
 - Only for Viega PEX Crimp fittings,
 Viega PEX Crimp tools
 - Copper
Model V5019.9

d	Wt [lb]	Quantity	Part No	DG
$\frac{3}{8}$	0.011	100	43600	2
$\frac{1}{2}$	0.013	100	43620	2
$\frac{3}{4}$	0.018	100	43640	2
1	0.022	50	43660	2



**Lav riser
 Zero Lead**
 - Does not include lav nut Model V5089
 - Equipped with ferrule Model V5085
 - PEX
Model V5080

CTS	O.D.	L	Wt [lb]	Quantity	Part No	DG
$\frac{1}{4}$	$\frac{3}{8}$	12	0.030	100	58112 ¹⁾	2
$\frac{1}{4}$	$\frac{3}{8}$	15	0.035	100	58115 ¹⁾	2
$\frac{1}{4}$	$\frac{3}{8}$	20	0.048	100	58120	2
$\frac{1}{4}$	$\frac{3}{8}$	30	0.071	100	58130	2
$\frac{1}{4}$	$\frac{3}{8}$	36	0.085	100	58136	2

¹⁾ Available while supplies last



**Closet riser
 Zero Lead**
 - Does not include ballcock nut Model V5089.1
 - Equipped with ferrule Model V5085
 - PEX
Model V5081

CTS	O.D.	L	Wt [lb]	Quantity	Part No	DG
$\frac{1}{4}$	$\frac{3}{8}$	12	0.031	100	57112	2
$\frac{1}{4}$	$\frac{3}{8}$	15	0.035	100	57115 ¹⁾	2
$\frac{1}{4}$	$\frac{3}{8}$	20	0.050	100	57120	2
$\frac{1}{4}$	$\frac{3}{8}$	30	0.080	100	57130 ¹⁾	2
$\frac{1}{4}$	$\frac{3}{8}$	36	0.085	100	57136 ¹⁾	2

¹⁾ Available while supplies last



**Lav nut
 Zero Lead**
 - Suitable for lav riser Model V5080
Model V5089

FPT	Wt [lb]	Quantity	Part No	DG
$\frac{1}{2}$	0.017	100	33705	2



**Ballcock nut
 Zero Lead**
 - Suitable for closet riser Model V5081
 - Plastic
Model V5089.1

FPT	Wt [lb]	Quantity	Part No	DG
$\frac{3}{4}$	0.023	100	53017	2



**Ferrule
 Zero Lead**
 - For Viega ManaBloc compression
 connections, risers, valves
 - Plastic
Model V5085

CTS	O.D.	Wt [lb]	Quantity	Part No	DG
$\frac{1}{8}$	$\frac{1}{4}$	0.001	100	53000	2
$\frac{1}{4}$	$\frac{3}{8}$	0.001	100	53005	2
$\frac{3}{8}$	$\frac{1}{2}$	0.001	50	53015	2
$\frac{1}{2}$	$\frac{5}{8}$	0.001	100	53020	2
$\frac{3}{4}$	$\frac{7}{8}$	0.003	100	53040 ¹⁾	2

¹⁾ Available while supplies last



**Insert stiffener
Zero Lead**
- For Viega ManaBloc compression connections, risers
- Stainless steel
Model V5086

CTS	O.D.	Wt [lb]	Quantity	Part No	DG
1/4	3/8	0.001	100	56100	2
3/8	1/2	0.003	50	56110	2
1/2	5/8	0.005	50	56120	2
3/4	7/8	0.010	50	56140	2



**Escutcheon
Single
Zero Lead**
- Not for Viega FostaPEX
- Plastic
Model V5088

d	Version	Wt [lb]	Quantity	Part No	DG
3/8	white	0.012	50	53115	2
1/2	white	0.012	50	53120	2



**Escutcheon
Double
Zero Lead**
- Not for Viega FostaPEX
- Plastic
Model V5088.1

d	Version	Wt [lb]	Quantity	Part No	DG
3/8	white	0.016	25	53116	2
1/2	white	0.016	25	53121	2



Sleeve
- Chrome-plated steel
- Finishing
Model 2800.5US

d	L [in]	Wt [lb]	Quantity	Part No	DG
3/8	3 1/2	0.050	10	52500	2
1/2	3 1/2	0.054	10	52520	2



**Bend support
Drop ear**
- Not for Viega FostaPEX
- Plastic-coated steel
Model 2850.1US

for d	Wt [lb]	Quantity	Part No	DG
3/8, 1/2	0.210	25	50520	2



**Bend support
Snap in**
- Not for Viega FostaPEX
- Suitable for bracket Model 2850.4US
- Plastic
Model 2850.3US

for d	Wt [lb]	Quantity	Part No	DG
1/2	0.559	100	51021	2



Bracket
- For mounting on 16" center studs
- Suitable for bend support snap in Model 2850.3US
- Steel
- Mounting holes on 2" centers
Model 2850.4US

d	L [in]	Wt [lb]	Quantity	Part No	DG
1/2	18	0.560	50	51022	2



Bend support
- Not for Viega FostaPEX
- Plastic
Model 2850.2US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.062	25	51000	2
1/2	0.083	25	51020	2
5/8, 3/4	0.155	25	51040	2
1	0.273	25	51060	2
1 1/4	0.440	5	51070	2


Bend support

- For slab
- Not for Viega FostaPEX
- Plastic

Model 2851US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.090	10	15106	4
1/2	0.106	10	15107	4
5/8, 3/4	0.254	10	15108	4
1	0.830	1	15111	4


Tubing clamp
Turn out

- For 3/8" tubing and 1/2" tubing with standard or stub-out elbows
- Not for Viega FostaPEX
- Plastic
- Trim tapered tip to use with 1/2" tubing

Model V5071

max d	Wt [lb]	Quantity	Part No	DG
1/2	0.099	25	52130	2


Full clamp

- Plastic

Components

Nail

Model V5092

for d	Wt [lb]	Quantity	Part No	DG
1/2	0.012	100	52220 ¹	2
3/4	0.019	50	52240 ¹	2

¹⁾ Available while supplies last

J-clamp tubing fasteners

- Plastic

Components

Nail

Model 2860US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.006	100	52000	2
1/2	0.008	100	52020	2
3/4	0.013	100	52040	2
1	0.021	100	52060	2


Economy PEX tubing clamp

- Not for Viega FostaPEX
- Plastic

Model V5095

for d	Wt [lb]	Quantity	Part No	DG
1/4	0.002	100	52100 ¹	2
3/8	0.002	100	52110	2
1/2	0.003	100	52120	2
3/4	0.004	50	52140	2

¹⁾ Available while supplies last

Snap clip
Single

- Not for Viega FostaPEX
- Plastic

Model 2862US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.006	100	58015	2
1/2	0.011	100	58020	2
3/4	0.010	100	58040	2
1	0.014	50	58060	2


Snap clip
Double

- Not for Viega FostaPEX
- Plastic

Model 2862.1US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.012	50	58016	2
1/2	0.012	50	58021	2



Lock clip
- Plastic
Model 2863US

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.014	100	58071	2
1/2	0.013	100	58072¹	2
3/4	0.015	50	58073²	2
1	0.025	50	58074	2

¹) Suitable for ViegaPEX Barrier tubing Part No 11445, 11450

²) Suitable for Viega FostaPEX tubing Part No 35030, 35031, 35530



Multi-clip
- Plastic
Components
Mounting screw
Model 2867US

max d	Wt [lb]	Quantity	Part No	DG
1	0.029	100	52006	2



U-channel fastener
- Plastic
- Pre-drilled holes
Model 2864US

W [in]	L [ft]	Wt [lb]	Quantity	Part No	DG
1/2	6 1/2	1.100	16	15310	4



Suspension clip tubing fasteners
- Plastic
Model 2861US

for d	Wt [lb]	Quantity	Part No	DG
1/2	0.009	50	55020	2
3/4	0.012	50	55040	2
1	0.018	50	55060	2



Tubing insulator
- Plastic
- Fits 1 1/2" hole
Model V5094

for d	Wt [lb]	Quantity	Part No	DG
3/8	0.018	50	55100	2
3/8, 1/2, 3/4, 1	0.014	25	55165¹	2
1/2	0.019	50	55120	2
3/4	0.014	50	55140	2
1	0.013	50	55160	2

¹) Available while supplies last



Zip tie
- Plastic
Model V5097

L [in]	Wt [lb]	Quantity	Part No	DG
14	0.013	100	43714	2



Pipethon strap
- Plastic
Model V5097.1

	Wt [lb]	Quantity	Part No	DG
	0.060	20	43701	2



Uncoiler
- Not for 1" tubing or larger, Viega FostaPEX, center pull coil
Components
Movable metal frame, (2) coil hubs, tube guide
Note
Max. coil size for 3/8" and 1/2" tubing is 1000 ft.
Max. coil size for 3/4" tubing is 500 ft.
Model V5061

	Wt [lb]	Quantity	Part No	DG
	70.980	1	53509	5

Viega Terms and Conditions



The following standard Terms and Conditions apply to all sales of products by Viega LLC unless otherwise modified in Order Confirmation or Delivery Note. Any contrary terms in purchase orders or purchaser standard terms and conditions are rejected and acceptance of the order by Viega LLC is conditioned upon these terms and conditions or as set out specifically in the Viega order confirmation.

Terms of Payment: Terms are 2% 10th prox., net 30 days. Payable in U.S. or Canadian dollars depending on point of delivery.

Price Changes: All published prices are subject to change. Viega historically has given reasonable notice (normally 30 days or more) of an effective date for those changes, but reserves the right, under unusual circumstances, to give shorter notice.

Sales Orders: Purchase orders submitted to Viega shall specify Viega part numbers as well as product description from a Viega catalog. All such offers to purchase are subject to Viega LLC acceptance, which shall be by order confirmation provided to the customer by Viega. Customer is responsible for reviewing the order confirmation and reporting any necessary changes to Viega Customer Service immediately. Mistakes on orders due to inaccurate or incomplete information from the customer and not changed by the customer will be the customer's responsibility and/or subject to Viega's return policy.

Terms of Shipment: Viega prepays freight on all shipments. Customer is not billed for freight on orders of \$2,500 net or greater. Excess freight charges resulting from special requested routing or

specifying non-Viega designated common carriers will be billed to the customer. Stainless pipe is prepaid at \$5,000 net and above and can not be combined with other Viega materials to qualify. Stainless fittings may be combined with other Viega products to meet freight requirements and are prepaid at \$2,500 net.

Restrictions: Orders from U.S. customers with a "Ship to" Canada location will not be accepted and U.S. customers are not authorized to sell product to Canada.

Freight Delivery and Risk of Loss in Transit: All prices are FOB shipment point.

Returns: All returns are subject to Viega's return policy. No material may be returned without our written permission and return material authorization (RMA) number. Any items with a purchase date older than one year will not be allowed for return. We will accept cataloged and resalable items only. No returns will be allowed for broken bags or bundles, items outside of original packaging, discontinued, damaged, or non-cataloged merchandise. Any material which is authorized to be returned will be subject to a minimum fifteen percent (15%) restocking fee. For more information on returns and the complete return policy go to www.viega.us.

These standard terms and conditions are those in effect on the date of publication of this catalog. Viega reserves the right to change these terms and conditions by posting such changes on www.viega.us.

Viega LLC

301 N. Main, 9th Floor, Wichita, KS 67202

Phone: 1-800-976-9819

insidesales@viega.us

724994_CAT_USA_0514

©2014, FostaPEX®, MegaPress®, ProPress®, and Viega® are registered trademarks of Viega GmbH & Co. Climate Mat®, Climate Panel®, Climate Trak®, ManaBloc®, Smart Connect®, Snap Panel®, XL® and XL-C® are registered trademarks of Viega LLC. MiniBloc™, PolyAlloy™, ProRadiant™, SmartLoop™ and Zero Lead™ are trademarks of Viega LLC; Eco Brass® is a registered trademark of Chase Brass and Ingot Metal Co.; RIDGID® is a registered trademark of RIDGID, Inc.

**The global leader
in plumbing, heating
and pipe joining systems**

