

# Tubular Plastic

## Trip Lever 500-TL

## Trip Lever 500-TQ QUICK ADJUST®

For most tubs 14" - 16" high

## Trip Lever 550-TL

For most tubs up to 24" high

Durable 1.5" Tubular Plastic PVC or ABS

### SPECIFICATIONS

#### FEATURES:

- Designed for heavy-duty use in hotels, motels, and rental property.
- Metal strainer body for cast iron or plastic tubs.
- Retainer plate for overflow ell.

#### APPROVALS:

- IAPMO, SBCCI
- Conforms to ANSI/ASTM F409-88.

Patents: <https://www.watcomfg.com/watco/patents/>

#### OPERATION:

- Move trip lever, located on Overflow Plate, up to close drain and down to open drain.

#### THREAD SIZE (Strainer Body and Drain Ell):

- 1½" – 11½ NPSM (Coarse Thread)
- 1.865" Major Diameter (outside thread diameter)
- 11.5 threads per inch

#### PIPING:

- PVC       ABS

#### OPTIONS:

- Removable tailpiece and "O" Ring Seal (Code "RT-2")
- Condensate Drain (Code "CD")
- Brass Drop Cylinder (Code "BD")
- Special lengths available:
  - Overflow extension (add code "EXlength")  
example: EX6
  - Drain extension (add code "Dlength") example: D4



## Model 500-TQ

Same as 500 Trip Lever except Quick Adjust® has scale label on the overflow pipe.  
For most tubs 14"-16" high



See price list for complete item numbers and available options.

When ordering, please specify complete item number and any applicable option codes.

**WATCO**



Always a step ahead

For More Information Contact:  
WATCO Manufacturing Company  
1220 South Powell Road  
Independence, MO 64057-2724  
Ph. 816-796-3900 • FAX 816-796-0875  
[www.watcomfg.com](http://www.watcomfg.com)

Tub Closure:	Trip Lever
CP- Chrome Plated	•
BB- Brushed Bronze	•
BN- Brushed Nickel	•
BZ- Oil-Rubbed Bronze	•
CB- Chrome Brushed	•
NP- Nickel Polished	•
PB- Polished Brass	•
WH- White	•
WI- Wrought Iron	•