

Independent, controlled feed makes this the preferred tool for PVC taps.

- Manual power recommended for taps on PVC.
- Chips are flushed out of the line using the bleed-off valve.



• Shell cutter and drill retaining bit keep hold of the coupon.



"Lightweight and fast!"


"It's easy to feel when the shell cutter cuts into and through the pipe wall."

"The coupon is retained and can be inspected."



Feed Tap[™] Drilling Machine

- Compact and lightweight with independent feed control.
- Drills through 3/4" 2" pressurized ductile iron, cast iron, steel or plastic pipe.
- Kits available for AWWA, 110 Compression, and NPT.
- Powered by either drill motor or manually with manual recommended for PVC.



Feed Tap Kits

Catalog No.	Item Code	Description	
FTB	09160	Feed Tap™ Base Machine	
FTBB	09169	Feed Tap™ Main Unit, CRPD25 and TMTC6 – no case	
FT2000UNIV	09165	Complete Feed Tap™ Kit ³/₄"- 2"	
FTP2000UNIV	09168	Complete Feed Tap™ Kit 3/4" - 2" for Plastic Pipe Only	
FT2000CC110	09161	AWWA/110 Comp Feed Tap™ Kit 3/4" - 2"	
FT2000	09162	AWWA Feed Tap™ Kit 3/4" - 2"	
FT2000110	09163	110 Comp Feed Tap™ Kit ³/₄" - 2"	
FT2000NPT	09164	NPT Feed Tap™ Kit 3/4" - 2"	
FT2000CCNPT	09166	AWWA/110 Comp ³ / ₄ " - 1" — NPT 1 ¹ / ₂ " - 2" Feed Tap™ Kit	
FT1000CC110	09167	AWWA/110 Comp Feed Tap™ Kit 3/4" - 1"	

NOTE: Feed Tap^w is designed to be used with corporation stops and bronze gate valves up to 2". For use with 2" iron body gate valves, contact Reed.



videos.reedmfgco.com/feedtap







Assemble unit.



Open corp stop valve.



Turn independent feed until the pilot drill touches the pipe.



Attach drill.



Make the tap, then reverse the process.



Inspect coupon.





CORPORATION ADAPTERS

Catalog	Item	Description	Description Weight	
No.	Code	Description	lbs	kg
FT75CC110	09170	3/4" AWWA and 110 Comp	.60	.27
FT100CC110	09171	1" AWWA and 110 Comp	.55	.25
FT150	09172	1 ¹ / ₂ " AWWA	1.20	.55
FT200	09174	2" AWWA	1.40	.64
FT150110	09173	1 ¹ / ₂ " 110 Comp	1.35	.61
FT200110	09175	2" 110 Comp	1.40	.64
FT75NPT	99117	3/ ₄ " NPT	.45	.20
FT100NPT	99118	1" NPT	.45	.20
FT150NPT	99109	1 ¹ / ₂ " NPT	.80	.36
FT200NPT	99112	2" NPT	.80	.36

HEAVY-DUTY SHELL CUTTERS

The attachment thread is $\frac{1}{2}$ " - 20". Each tooth has carbide inserts. These Reed shell cutters cut up to 2" deep and fit most standard arbors and competitive machines.

Catalog	Item	Shell Cutter Size Inches*		Neight	
No.	Code	onen outter oize mones	lbs	kg	
FTSC688	99132	11/16"	.09	.04	
FTSC875	99134	⁷ /8"	.15	.07	
FTSC1438	99137	1 7/16"	.41	.19	
FTSC1750	99138	1 3/4"	.57	.26	

^{*}Check manufacturer's fitting specifications for proper hole diameter.

MISCELLANEOUS

Catalog No.	Item Code	Description
CS01RTCH	40232	Ratchet Wrench
FTAA	09113	Arbor Assembly used with 1 7/16" or 1 3/4" Shell Cutter
CRPD25	99129	¹ /4" diameter Carbide Tipped Coupon Retaining Drill Bit
MCR3/8	08358	Magnetic Coupon Retainer Set, 3/8"
MCR1/4	08359	Magnetic Coupon Retainer Set, 1/4"
FTPLAA	04423	Adapter used with 1 - 1/2" & 2" PVC/PE Shell Cutters
FTSA1/2	48207	Socket Adapter, 1/2" Drive
SCKT1/2	48208	7/16" Socket, 1/2" Drive
FTPLSAA	94198	Adapter used with 3/4" & 1" PVC/PE Shell Cutters

TAPPING COMPOUND

escription	Item Code	Catalog No.
kg) Resealable Can	98425	TMTC
Squeeze Bottle	99140	TMTC6