



PULLER, CABLE

Super Tugger Cable Puller Power Unit, Includes force gauge and vise chains

Cat No: 6001

UPC No: 783310296270

Description

- Pull up to 6,500 lbs. (28.9 kN) with less than 27 lbs. (120 N) of operator effort
- Unique floor mounting attachment for quick, reliable setup
- Leaf-type mounting chains won't twist when tightening
- Heat-treated steel serrated gripper feet for secure mounting to conduit
- Force Gauge included to constantly monitor the pull
- Right-angle sheave allows the operator to stand out of the direct line of force
- Audio alarm high force warning and circuit breaker shut off at maximum force for added safety
- Tapered capstan and patented rope guidance system for better control of the rope when feeding onto the capstan
- Patented

Specifications

- Accessory : 35098 UPC 35098 Double-Braided Composite Rope 3/4 IN x 300 FT (19.100 MM x 91.000 M), 35100 UPC 35100 Double-Braided Composite Rope 3/4 IN x 600 FT (19.100 MM x 182.000 M), 35101 UPC 35101 Double-Braided Composite Rope 3/4 IN x 1,200 FT (19.100 MM x 365.0 M)
- Drive Motor : 1-1/2 hp, 120 VAC, 16 Hz, 20 Amp
- Includes : Force Gauge And Vise Chains
- Pulling Force : 6500.000 LB (28.900 KN) Maximum, 4500.000 LB (20.000 KN) Continuous
- Pulling Rope : 3/4 IN (19.100 MM) Double-Braided Composite, Rated At 26000 LB (115.600 KN)
- Pulling Speeds : 16.5 FTPM At No Load, (8.800 KN) - 11 (3.4) At 2000 LB, (17.900 KN) - 7.5 (2.3) At 4000 LB, (26.700 KN) - 6 (1.8) At 6000 LB
- Sub Brand : Super Tugger
- Weight : 108.000 LB (49.000 KG)