



UL RECOGNIZED COMPONENT ROTARY SWITCHES



2 SPEED



2 GANG



8 POSITION



PUSH BUTTON

DIAL P/N	DESCRIPTION / PACKAGING	PKG	CTN QTY	CTN WT
----------	-------------------------	-----	---------	--------

WALL SWITCHES FOR COOLERS - UL RECOGNIZED

6 Position rotary wall switches for single speed and 2 speed coolers. When used with single speed motors, only 4 of the 6 switch positions are used. Switches include: mounting screws and wiring diagram.

DIAL P/N	DESCRIPTION / PACKAGING	PKG	CTN QTY	CTN WT
▲7109	Two Speed Wall Switch	Bag	100	20.4
▲7110	Two Speed Wall Switch	Bag	10	2.0
▲71105	Two Speed Wall Switch	▲ Bag	20	3.8
▲7112	Two Speed Wall Switch	Card	10	2.3
▲7115	Two Speed Wall Switch -Metal	Card	10	2.8
▲7131	Two Speed Wall Switch-2 Gang Metal	Card	10	2.7

8 POSITION COOLER SWITCHES - UL RECOGNIZED

8 position cooler switch for 2 or 3 speed coolers with ceiling grilles or window view coolers. Use with Arctic Circle®, Arvin®, McGraw®, and Wright® coolers. Short shafts have 5/8" stem, long shafts have 23/8" stem. Rated 25 amps at 115 volts for 1/3 to 1 HP cooler motors. When used with 2 speed motors, only 6 of the 8 switch positions are used.

DIAL P/N	DESCRIPTION / PACKAGING	PKG	CTN QTY	CTN WT
7212	Two or 3 Speed Short Shaft Switch	Bulk	10	1.0
▲7219	Two or 3 Speed Short Shaft Switch	▲ Clam	6	0.7

WINDOW VIEW PUSH BUTTON SWITCH

DIAL P/N	DESCRIPTION / PACKAGING	PKG	CTN QTY	CTN WT
▲7361	Two Speed Push Button Switch	Clam	6	1.4