

# NEW

## ROLOCK EXPANDER

### Expander head ROLOCK

Twist & lock system for quick and easy change between nominal diameters





### Expander head standard

Standard screwable expander head, still compatible with the ROLOCK Expander





#### Australia

	Cu	Al	Fe	Inox	A mm	 g wt	ROLOCK No.	Standard
1/4"	1.0	1.0	1.0	1.0	6.0	100	-	<b>100B-04</b>
5/16"	1.0	1.0	1.0	1.0	6.0	120	<b>12408</b>	<b>11008</b>
3/8"	1.0	1.0	1.0	1.0	7.4	120	<b>12452</b>	<b>11052</b>
1/2"	1.2	1.2	1.2	1.0	11.0	120	<b>12453</b>	<b>11053</b>
5/8"	1.2	1.2	1.2	1.0	14.0	120	<b>12454</b>	<b>11054</b>
3/4"	1.2	1.2	1.2	1.0	18.1	120	<b>12455</b>	<b>11055</b>
7/8"	1.2	1.2	1.2	1.0	18.0	140	<b>12456</b>	<b>11056</b>
1"	1.5	1.5	1.5	-	15.8	150	<b>12457</b>	<b>11057</b>
1.1/8"	1.6	1.6	1.6	-	17.0	390	<b>12458</b>	<b>11058</b>
1.1/4"	1.6	-	-	-	17.0	410	<b>12459</b>	<b>11059</b>
1.3/8"	1.6	-	-	-	17.0	430	<b>12435</b>	<b>11035</b>
1.1/2"	1.6	-	-	-	17.0	450	<b>12438</b>	<b>11038</b>
1.5/8"	1.6	-	-	-	17.5	470	<b>12462</b>	<b>11062</b>
2"*	1.6	-	-	-	17.0	550	-	<b>11364</b>

\*2" expander head (11364) must be used with Expander Adaptor (11007)

#### New Zealand


 mm	Cu	Al	Fe	Inox	A mm	 g wt	ROLOCK No.	Standard
8	1.0	1.0	1.0	1.0	6.0	120	<b>12408</b>	<b>11008</b>
10	1.0	1.0	1.0	1.0	7.4	120	<b>12410</b>	<b>11010</b>
12	1.2	1.2	1.2	1.0	11.0	120	<b>12412</b>	<b>11012</b>
15	1.2	1.2	1.2	1.0	14.0	120	<b>12415</b>	<b>11015</b>
22*	1.2	1.2	1.2	1.0	18.1	120	<b>12422</b>	<b>11022</b>
28*	1.5	1.2	1.2	-	18.0	140	<b>12428</b>	<b>11028</b>
35	1.6	-	-	-	15.8	150	<b>12435</b>	<b>11035</b>
42	1.5	-	-	-	17.0	390	<b>12442</b>	<b>11042</b>




\*22mm (11015) suitable for NZ 20mm pipe & 28mm (11028) suitable for NZ 25mm pipe

### Expander Adaptor

To increase the application area of the ROCAM® EXPANDER Power Torque

Allows the use of the 2" expander heads with copper pipe (soft) up to 67 mm and/or 2.1/2"!



Model	 max. mm / inch	 max. mm	 No. Adaptor
Type S,	67 mm - 2.1/2"	2.0	630 <b>11007</b>