

# **CUT SHEET**

# SUPER SERVICE BLUE SDR-9 CTS 250psi PE4710 ASTM D-2737 NSF CERTIFIED

### **Products**

Product Number	Diameter	Weight <sup>1</sup>
4SSCTS-075-### <sup>2</sup>	3/4"	10.3
4SSCTS-100-### <sup>2</sup>	1"	16.9
4SSCTS-125-### <sup>2</sup>	1-1/4"	25.0
4SSCTS-150-### <sup>2</sup>	1-1/2"	34.8
4SSCTS-200-### <sup>2</sup>	2"	59.4

<sup>&</sup>lt;sup>1</sup> Weights are per 100' of pipe.

## **Specifications**

Diameter	O.D.	Calc I.D.	Min. Wall
3/4"	0.875" ±0.004"	~0.681"	0.097" +0.010"
1"	1.125" ±0.005"	~0.875"	0.125" +0.012"
1-1/4"	1.375" ±0.005"	~1.069"	0.153" +0.015"
1-1/2"	1.625" ±0.006"	~1.263"	0.181" +0.018"
2"	2.125" ±0.006"	~1.653"	0.236" +0.024"

### Standards & Certifications

NSF/ANSI Standard #14, NSF/ANSI Standard #61

ANSI/AWWA C901-17 specifications for polyethylene (PE) pressure pipe, tubing, and fittings (3/4" to 3" for water)

ASTM D-1248 specification for polyethylene (PE) plastics molding and extrusion materials

ASTM D-3350 specification for polyethylene (PE) plastics pipe and fittings material

ASTM D-2737 specification for polyethylene (PE) plastic tubing

Interstate Plastic, Inc. HDPE pressure pipe and tubing are in compliance with the Trade Agreement Act (19 USC 2501) and are proudly made in the USA in beautiful Post Falls, ID

# Interstate Plastic, Inc.

3375 E Seltice Way PO Box 398 Post Falls, ID 83877

P: (208) 773-4538 (800) 776-7537 F: (208) 773-9400 (888) 206-3012 NSF - pw



<sup>&</sup>lt;sup>2</sup> Replace ### with the length of pipe. i.e. 4SSCTS-075-300 for a 3/4" x 300' coil.