F100F Media Air Cleaner



Application: Duct mounted

Description: Entry level Media air cleaner, 4 inch extended Media. Efficiency Standard: Efficiency ratings are based on American Society of Heating, Refrigerating and Air-Conditioning Engineers Standard 52.2-1999. Efficiency ranges are defined for small particles, E1=0.3 to 1.0 microns; medium particles, E2=1.0 to 3.0 microns; and large particles, E3=3.0 to 10.0 microns.

Fractional Efficiency: E1=32%, E2=72%, E3=96%

Minimum Efficiency Reporting Value (Media Filters Only): MERV 11

Static Pressure Drop (in. w.c.): 0.23 at 500 FPM


Underwriters Laboratories, Inc: Filter Element: UL Listed, UL900, Class 2

Replacement Parts:

FC100A1003/U-F16X20 Media Air Filter - MERV 11 FC100A1011/U-20X20 Media Air Filter - MERV 11 FC100A1029/U-16X25 Media Air Filter - MERV 11 FC100A1037/U-20X25 Media Air Filter - MERV 11 FC100A1045/U-21.5X27.5 Media Air Filter - MERV 11 FC100A1052/U-20X12.5 Media Air Filter - MERV 11 FC200E1003/U-16x20 Charged-Media Filer - MERV 13 FC200E1011/U-20x20 Charged-Media Filter - MERV 13 FC200E1029/U-16x25 Charged-Media Filer - MERV 13 FC200E1037/U-220x25 Charged-Media Filter - MERV 13 The F100F Media Air Cleaner captures a significant amount of the airborne particles from the air circulated through the unit. Recommended as the basic minimum air quality product. The F100F Media Air Cleaner includes cabinet, access door and FC100A pleated media filter.

- High efficiency media filter captures particles as small as 0.3 microns
- Applicable to all gas, oil and electric forced air furnaces and to compressor cooling up to 5 tons
- Mounts in the return air duct
- Rugged zinc-coated, roll-formed cabinet resists corrosion and can support weight of residential furnace and evaporator coil
- Requires no electrical connections
- Mounts in any position
- Requires no maintenance except periodic media filter replacement
- Quick and easy media filter replacement
- Later upgrade to higher performing media or electronic air cleaner is easy

Pressure Drop of FC100 Filter



1\text{\frac{1}{1}} WHEN FIRST INSTALLED. PRESSURE DROP INCREASES AS FILTER BECOMES LOADED. REPLACE FILTER WHEN PRESSURE DROP REACHES 0.5 IN. WC. (0.1 kPa).

2 AVAILABLE ONLY IN UNITED STATES.

M14709

57

F100 Media Air Cleaner with MERV 11 Filter

	Product Number	Air Cleaner Size-Dimensions, Approximate		Airflow MaxCapacity		
		(inch)	(mm)	(cfm)	(m ³ /hr)	Replacement Filters
*	F100F2002/U	16 in. x 25 in.	406 mm x 635 mm	1400 cfm	2380 m ³ /hr	FC100A1029, FC200E1029, POPUP1625
*	F100F2010/U	20 in. x 25 in.	508 mm x 635 mm	2000 cfm	3400 m ³ /hr	FC100A1037, FC200E1037, POPUP2025
*	F100F2028/U	16 in. x 20 in.	406 mm x 508 mm	1200 cfm	2040 m ³ /hr	FC100A1003, FC200E1003, POPUP1620
*	F100F2036/U	20 in. x 20 in.	508 mm x 508 mm	1400 cfm	2380 m ³ /hr	FC100A1011, FC200E1011, POPUP2020
*	F100F2044/U	25 in. x 20 in.	635 mm x 508 mm	2000 cfm	3400 m ³ /hr	FC100A1037, FC200E1037, FC100C1017
*	F100F2051/U	25 in. x 22 in.	635 mm x 559 mm	2000 cfm	3400 m ³ /hr	FC100A1037, FC200E1037, FC100C1017

F100 Media Air Cleaner Boot Only

		Air Cleaner Size-Dimensions, Approximate		Airflow Max. Capacity		
	Product Number	(inch)	(mm)	(cfm)	(m ³ /hr)	Replacement Filters
	F100B1016/U	16 in. x 25 in.	406 mm x 635 mm	1400 cfm	2380 m³/hr	FC100A1029, FC200E1029, FC100C1009, POPUP1625
*	F100B1024/U	20 in. x 20 in.	508 mm x 508 mm	1400 cfm	2380 m ³ /hr	FC100A1011, FC200E1011, POPUP2020
*	F100B1032/U	20 in. x 25 in.	508 mm x 635 mm	2000 cfm	3400 m ³ /hr	FC100A1037, FC200E1037, FC100C1017, POPUP2025
*	F100B1040/U	25 in. x 22 in.	635 mm x 559 mm	2000 cfm	3400 m ³ /hr	FC100A1037, FC200E1037, FC100C1017

70-6910 Honeywell