

COMBUSTION AIR SYSTEM

Model: CAS-2B, 2C & 2W



ITEMS INCLUDED IN KIT:

- 1- Air Boot®
- 1- Set of Gaskets
- 1- 4" VRV
- 1- 4" IAH Hood
- 1- Burner Coupling Set
- 2- Mounting Bolts
- 1- Flow Restrictor Pan
(CAS-2B ONLY)

INSTALLER SUPPLIED ITEMS:

- Duct Piping and Elbows
- 90° Elbows; ¼" NPT
Female x ¼" NPT Male
for routing oil line

This product is designed for use on the following burners, for the purpose of routing combustion air directly to the burner, with the added safety feature of the vacuum relief valve.

NOTE: For burner inputs up to 2.0 GPH at 100 PSI input pressure or equivalent.

The Air Boot® models CAS-2B, CAS-2C and CAS-2W are for use only on the designated burner(s) as described in these instructions only when the specific burner includes this Air Boot® when shipped from the burner manufacturer, or where the burner instructions specifically reference the models CAS-2B, CAS-2C or CAS-2W Air Boot® as an optional air intake system.

CAS-2B	BECKETT-AF/AFG
CAS-2C	CARLIN-EZ-1/CRD/FRD
CAS-2W	WAYNE-MSR

NOTE: This product brings combustion air only to the burner; must have adequate venting air in accordance with NFPA-31.

READ THESE INSTRUCTIONS CAREFULLY AND COMPLETELY BEFORE PROCEEDING WITH THE INSTALLATION.

This device **MUST** be installed by a qualified agency in accordance with the manufacturer's installation instructions. The definition of a qualified agency is: any individual, firm, corporation or company which either in person or through a representative is engaged in, and is responsible for, the installation and operation of HVAC appliances, who is experienced in such work, familiar with all the precautions required, and has complied with all the requirements of the authority having jurisdiction.

Please retain these instructions after installation.

Installed By: _____ Phone: _____ Installation Date: _____



FIELD CONTROLS

www.fieldcontrols.com