## Product datasheet Characteristics

# QO130M200PRB



#### Main

Man	
Product or component type	Load Center
Range of product	QO
Load center type	Main breaker
Line Rated Current	200 A
Number of spaces	30
Short-circuit current	22 kA
Number of circuits	30
Number of tandem circuit breakers	0
Phase	1 phase

#### Complementary

AWG gauge	AWG 4250 kcmil (aluminium/copper)	
NEMA degree of protection	NEMA 3R outdoor	
Cover type	Surface cover	
Device composition	Grounding bar (ordered separately)	
Electrical connection	Lugs	
Wiring configuration	3-wire	
Material	Tin plated copper busbar	
Enclosure material	Welded galvannealed steel	
Surface finish	Baked enamel grey	
Box number	6R	
Product certifications	UL listed	
Height	29.84 in (758 mm)	
Width	14.76 in (375 mm)	

### Environment

#### **Offer Sustainability**

Not Green Premium product	Not Green Premium product
Compliant - since 1248 - Schneider Electric declaration of conformity	Compliant - since 1248 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

