


CTS CPVC Technical  
**CTS Product Dimensions**



### Transition Coupling

IPS Socket x CTS Socket

NSF® Certified Lead Free




| Part Number | Size | L       | M       | M1      | N   | Approx. Wt. (Lbs.) |
|-------------|------|---------|---------|---------|-----|--------------------|
| 4141-007    | 3/4  | 1-27/32 | 1- 5/16 | 1- 3/32 | 1/8 | .04                |
| 4141-010    | 1    | 2- 5/32 | 1-19/32 | 1- 3/8  | 1/8 | .07                |

### Cap

Socket

NSF® Certified Lead Free




| Part Number | Size  | M       | W       | Approx. Wt. (Lbs.) |
|-------------|-------|---------|---------|--------------------|
| 4147-005    | 1/2   | 27/32   | 21/32   | .01                |
| 4147-007    | 3/4   | 1-3/32  | 7/8     | .02                |
| 4147-010    | 1     | 1- 3/8  | 1- 9/32 | .03                |
| 4147-012    | 1-1/4 | 1-21/32 | 1-9/16  | .06                |
| 4147-015    | 1-1/2 | 1-15/16 | 1-7/8   | .10                |
| 4147-020    | 2     | 2- 9/16 | 2-7/16  | .22                |

### GripLoc™ Cap

WARNING: DO NOT INSERT FINGERS

Grip Socket - Uses No Solvent Cement

NSF® Certified Lead Free



| Part Number | Size | M      | W       | Approx. Wt. (Lbs.) |
|-------------|------|--------|---------|--------------------|
| GL4147-005  | 1/2  | 1-5/16 | 1-1/4   | .04                |
| GL4147-007  | 3/4  | 1-7/16 | 1-17/32 | .06                |
| GL4147-010  | 1    | 1-3/4  | 2       | .12                |

Note: The GripLoc™ is water tight, permanent and cannot be removed.