

**6-YEAR**

Reliance®

Water Heaters
Your neighborhood water heater source.

**6-Year Electric**

- Available in 19.9- to 50-gallons nominal capacity, First Hour Delivery up to 62 gallons
- Tall, Medium, Lowboy, and Table Top choices to meet a wide variety of installation space requirements
- Glass-lined tank with anode rod protects against corrosion
- 4500 Watt heating elements
- Factory-Installed Temperature & Pressure (T&P) Relief Valve

6-Year Limited Warranty Tank/Parts, 1-Year Limited Warranty Labor†

Product Type	Model Number	Nominal Capacity (Gallons)	Rated Storage Volume (Gallons)	First Hour Delivery (Gallons)	Element Wattage (Standard)	Recovery 90° Rise - (Gallons per Hour)	Uniform Energy Factor	Diameter (Inches)	Height to top of tank (Inches)	Est. Yearly Energy Cost
Tall	6 50 EOHRT	50	46	62	5500/5500	25	0.92	20 1/2	60 1/2	\$419
Tall	6 50 EORT	50	46	62	4500/4500	21	0.92	20 1/2	60 1/2	\$419
Medium	6 50 EOHRS	50	46	57	5500/5500	25	0.92	23	49 1/4	\$424
Medium	6 50 EORS	50	46	57	4500/4500	21	0.92	23	49 1/4	\$424
Lowboy	6 50 EOLS	51	48	54	4500/4500	21	0.92	26 1/2	36	\$424
Tall	6 40 EOHRT	40	36	53	5500/5500	25	0.92	18	61 1/4	\$424
Tall	6 40 EORT*	40	36	53	4500/4500	21	0.92	18	61 1/4	\$424
Medium	6 40 EOHRS	40	37	55	5500/5500	25	0.92	20 1/2	50	\$424
Medium	6 40 EORS*	40	37	55	4500/4500	21	0.92	20 1/2	50	\$424
Medium	6 40 EORSS	40	37	55	4500	21	0.92	20 1/2	50	\$424
Lowboy	6 40 EOMS**	38	35	54	4500/4500	21	0.93	26	33 1/2	\$419
Lowboy	6 40 EOLS	38	35	50	4500/4500	21	0.89	26	33 1/2	\$303
Table Top	6 38 EOTT	38	35	55	4500/4500	21	0.90	24 x 25	36	\$433
Lowboy	6 36 EOLS	36	33	51	4500/4500	21	0.92	24	32	\$424
Tall	6 30 EORT*	30	27	48	4500/4500	21	0.89	19	46 1/2	\$302
Medium	6 30 EORS*	30	27	47	4500/4500	21	0.89	22	39 3/4	\$302
Medium	6 30 EORSS	30	27	47	4500	21	0.89	22	39 3/4	\$302
Lowboy	6 30 EOLS	28	26	44	4500/4500	21	0.90	24	31 1/4	\$299
Lowboy	6 20 EOLS	19.9	19	N/A	4500	21	N/A	20	30	N/A

Shipped with Factory Insulation Blanket

Lowboy	6 50 EOLBS	48	44	60	4500/4500	21	0.93	26 1/2	34	\$419
Lowboy	6 40 EOMBS E**	38	35	57	4500/4500	21	0.94	24	31 3/4	\$414
Lowboy	6 40 EOLBS	38	35	51	4500/4500	21	0.92	23	32	\$424
Medium	6 30 EORBS	30	27	50	4500/4500	21	0.90	20	39 1/4	\$299
Mobile Home	6 30 EMHBS E**	30	27	49	3800/3800	17	0.90	20	39	\$299
Lowboy	6 30 EOLBS	28	26	43	4500/4500	21	0.89	20	30 1/4	\$303
Compact	6 30 EOMBD E**	28	26	47	4500/4500	21	0.90	22	30 1/4	\$299
Compact	6 30 EOMBS E**	28	26	47	4500	21	0.90	22	30 1/4	\$299
Compact	6 30 EOMBS K***Δ	28	26	47	1650	8	0.90	22	30	\$299

†For complete information consult written warranty.

*Add "G" to end of model for top T&P configuration. Example: 6 30 EORT becomes 6 30 EORT G. **Side water connections. Δ Configured for 120V AC power.

Models shipped from the factory with an insulation blanket have a "B" as the second to last character in the model number not counting the voltage designation letters K and E for compact models.

For example: 6 30 EOLBS, 6 30 EOMBS K, or 6 30 EOMBS E. Not all models have derivatives with factory supplied insulation blankets, see section of table above for models available with an insulation blanket.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.