



Hydraulic Regal[®] 940 XL Model Flushometer

Models Available □Regal 940 XL-TP

□ Regal 940 XL-TP Trap Primer Elbow □ Regal 940 XL-YI Two Wall Bumpers (for open front seat without cover)

Description

Concealed Hydraulically Operated Regal® XL Water Closet Flushometer for floor mounted back spud bowls.

Flush Cycle

Model 940-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

Specifications

Quiet, Concealed, Diaphragm Type, Rough Brass Closet Flushometer for either left or right hand supply with the following features:

- ADA Compliant Non-Hold-Open feature type Actuator (specify Actuator type listed below)
- 1" I.P.S. Wheel Handle Bak-Chek™ Angle Stop
- Adjustable Tailpiece
- Vacuum Breaker Flush Connection
- Double Slip Elbow Flush Connection for 11/2" Exposed Back Spud
- Exposed Parts Chrome Plated
- Spud Coupling, Wall and Spud Flanges
- Sweat Solder Adapter with Cover Tube
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation.
- Low Consumption flush accuracy controlled by Para-Flo™ Inside Parts Kit
- Stop Seat and Vacuum Breaker to be molded from PERMEX[™] Rubber Compound for Chloramine Resistance.

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

L Dimension

Specify the "L" Dimension for the proper length of the Flush Connection. The "L" Dimension is equal to the Wall Thickness (to the nearest whole inch) plus 234".

Actuator Types: (please check one)

- Fixture Wall Actuator (HY-33-A) (rear access required)
- MP Metal Partition Actuator (HY-49-A)
- □ SW Side Wall Mounted Actuator (HY-72-A)
- □ **MBFW** Metal Button Fixture Wall Actuator (HY-100-A) (rear access required)
- □ **MBPM** Metal Button Panel Mount (HY-108-A)

Accessories

See Accessories Section of the Sloan catalog for available accessories

Fixtures

Consult Sloan for Sloan brand matching fixture options.





This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.

