


**PERFORMANCE**


"V" Twin Style Pump runs cooler and provides 12.5 CFM at 100 PSI for faster recovery time

**POWER**


Powerful Honda® GX160 4-stroke engine for increased performance and superior reliability

**CAPACITY**


10-gallon twin tanks provide air supply to multiple nailers

**PERFORMANCE YOU NEED**

**BIG BORE™**
**MAC5501G**

**5.5 HP\* BIG BORE™ GAS AIR COMPRESSOR**  
 "V" Twin Style Pump runs cooler and provides 12.5 CFM at 100 PSI

- Powerful Honda GX160 4-stroke engine for increased performance and superior reliability
- 10-gallon twin tanks provide air supply to multiple nailers
- Cast iron pump with Big Bore™ cylinder and piston is engineered to provide faster recovery time for improved performance
- Industrial-grade recoil starter with ergonomic grip and recoil rope design for faster, easier starts

Model MAC5501G Includes: (2) 1/4" Universal Quick Coupler, Male (447013-E)

Maximum Horsepower	5-1/2 HP
Running Horsepower	5.5 HP
Tank	10 gal.
Performance:	40 PSI (14 CFM), 90 PSI (12.5 CFM)
Maximum Pressure	135 PSI
Overall Length	46"
Net Weight	190 lbs.
Shipping Weight	233 lbs.
Pump	Oil lubricated


**MAC5200**

**3.0 HP\* BIG BORE™ AIR COMPRESSOR**  
 Powerful Enough to Run Two Framing Nailers

- Cast iron pump with Big Bore™ cylinder and piston is engineered to provide faster recovery time for improved performance
- Powerful 3.0 HP\* motor produces 6.5 CFM at 90 PSI for increased productivity
- Pump is oil lubricated for cooler running temperatures and reduced wear
- Durable cast iron cylinder reduces wear and increases pump life
- Folding handle with low-profile design for easy storage

Model MAC5200 Includes: Air Compressor Oil (181122-A), 1/4" Universal Quick Coupler, Male (447013-E)

Maximum Horsepower	3 HP
Running Horsepower	2.1 HP
Tank	5.2 gal.
Performance:	40 PSI (6.9 CFM), 90 PSI (6.5 CFM)
Maximum Pressure	140 PSI
Net Weight	88 lbs.
Shipping Weight	107 lbs.
Pump	Oil lubricated


**BIG BORE™**
**MAC2400**

**2.5 HP\* BIG BORE™ AIR COMPRESSOR**  
 Pump Runs at Lower RPM Resulting in Lower Noise (79dB)

- Cast iron pump with Big Bore™ cylinder and piston is engineered to provide faster recovery time for improved performance
- Powerful 2.5 HP 4-Pole motor produces 4.2 CFM at 90 PSI for increased productivity and lower noise
- Roll-cage construction provides complete protection to withstand extreme jobsite environments
- Low AMP draw reduces incidences of tripped breakers at start up
- Copper finned discharge tubing for increased heat dissipation and reduced water in the tank

Model MAC2400 Includes: Air Compressor Oil (181122-A), 1/4" Universal Quick Coupler, Male (447013-E)

Maximum Horsepower	2-1/2 HP
Running Horsepower	2.1 HP
Tank (twin stacked)	4.2 gal.
Performance:	40 PSI (4.8 CFM), 90 PSI (4.2 CFM)
Maximum Pressure	130 PSI
Net Weight	77 lbs.
Shipping Weight	86.3 lbs.
Pump	Oil lubricated


**BIG BORE™**
**MAC700**

**2.0 HP\* BIG BORE™ AIR COMPRESSOR**  
 Low Noise, Low AMP Draw and High Output

- Cast iron pump with Big Bore™ cylinder and piston is engineered to provide faster recovery time for improved performance
- Powerful 2.0 HP 4-Pole motor produces 3.3 CFM at 90 PSI for increased productivity and lower noise
- Pump runs at lower RPM (1,730) resulting in lower noise (80dB) and improved pump durability
- Low AMP draw reduces incidences of tripped breakers at start up
- Roll-bar handle for portability and additional protection

Model MAC700 Includes: Air Compressor Oil (181122-A), 1/4" Universal Quick Coupler, Male (447013-E)

Maximum Horsepower	2 HP
Running Horsepower	1.7 HP
Tank	2.6 gal.
Performance:	40 PSI (3.8 CFM), 90 PSI (3.3 CFM)
Maximum Pressure	130 PSI
Net Weight	52 lbs.
Shipping Weight	60.5 lbs.
Pump	Oil lubricated


**AC001**

**COMPACT AIR COMPRESSOR**  
 Low Noise and Less Weight

- Powerful 1/6 maximum horsepower\* induction motor provides up to 125 PSI
- Lightweight design (23.1 lbs.) for increased job site portability
- Low noise for operator comfort; ideal for indoor use
- Low AMP draw reduces incidents of tripped breakers at start-up
- Roll cage construction for extra protection of pump and motor assembly

Model AC001 Includes: 1/4" Universal Quick Coupler, Male (447013-E)

Motor	1/6 HP
Running Horsepower	1/6 HP
Tank	1 gal.
Performance:	40 PSI (.58 CFM), 90 PSI (.45 CFM)
Maximum Pressure	125 PSI
Net Weight	23.1 lbs.
Shipping Weight	26.9 lbs.
Pump	Oil-less

\*Maximum horsepower