



INCLUDES
(1) Hex Wrench
(1) Hammer Cart
(2) Flat Chisels
(2) Bull Points

NEW HM1812X3

70 lb. ADVANCED AVT® BREAKER HAMMER
Hits Like Air Without the Vibration

- Efficient 15 AMP motor with improved hammer mechanism delivers 53.9 ft.lbs./72.8 joules of impact energy
- Advanced AVT® is a mechanical counterbalance, vibration absorbing housing and rubberized fixed handles designed to more effectively reduce vibration
- Soft start is designed to suppress start-up reaction for greater accuracy on start up
- L.E.D. light indicates electrical failure or notifies the user approximately 8 hours before brushes need to be replaced

Model HM1812X3 Includes: Hex Wrench (783203-B), Premium Hammer Cart (T-02892), (2) 1-1/8" x 20-1/2" Flat Chisel, 1-1/8" Hex (D-21369), (2) 16" Self Sharpening Bull Point, 1-1/8" Hex (B-45559)

Blows Per Minute	870 BPM
Impact Energy	53.9 ft.lbs. / 72.8 J
AMPS	15
Noise Level	106 dB
Vibration (m/s²)	6.5
Cord Length (ft)	16.4'
Overall Length	33-1/4"
Net Weight	69.1 lbs.
Shipping Weight	140 lbs.
Bit Type	1-1/8" Hex



INCLUDES
(1) Hex Wrench
(1) Hammer Cart
(2) Flat Chisels
(2) Bull Points

HM1810X3

70 lb. AVT® BREAKER HAMMER
Anti-Vibration Technology for 2X Less Vibration

- Efficient 15 AMP motor with improved hammer mechanism delivers 46.5 ft.lbs. of impact energy
- Anti-Vibration Technology is an internal counterbalance system that greatly reduces vibration
- Fixed movement handles for more control and better accuracy
- AC/DC switch for use with alternative power source
- L.E.D. power light indicates switch failure or cord damage

Model HM1810X3 Includes: Hex Wrench (783203-B), Premium Hammer Cart (T-02892), (2) 1-1/8" x 20-1/2" Flat Chisel, 1-1/8" Hex (D-21369), (2) 20-1/2" Bull Point, 1-1/8" Hex (D-21353)

Blows Per Minute	1,100 BPM
Impact Energy	46.5 ft.lbs. / 63 J
AMPS	15
Noise Level	107 dB
Vibration (m/s²)	9
Cord Length (ft)	16.4'
Overall Length	32-1/2"
Net Weight	71.3 lbs.
Shipping Weight	141.3 lbs.
Bit Type	1-1/8" Hex



HM1317CB

42 lb. AVT® DEMOLITION HAMMER
Anti-Vibration Technology for 2X Less Vibration

- Powerful 14 AMP motor delivers 25.7 ft.lbs. of impact energy to handle the most demanding applications
- Variable speed control dial enables user to match the speed to the application for greater versatility
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced
- L.E.D. power light indicates switch failure or cord damage
- Rubberized ergonomic soft grip provides more comfort

Model HM1317CB Includes: 20-1/2" Bull Point, 1-1/8" Hex (D-21353), Tool Case w/Wheels

Blows Per Minute (variable speed)	730 - 1,450 BPM
Impact Energy	25.7 / 34.9 J
AMPS	14
Noise Level	101 dB
Vibration (m/s²)	7
Cord Length (ft)	16.4'
Overall Length	32-1/2"
Net Weight	41.9 lbs.
Shipping Weight	60.39 lbs.
Bit Type	1-1/8" Hex



HM1500B

42 lb. DEMOLITION HAMMER
Rugged All Metal Housing for Longer Tool Life

- Powerful 13.5 AMP motor delivers 18.4 ft.lbs. of impact energy
- Pneumatic compression system automatically adjusts air in the cylinder to minimize power loss and deliver unmatched power-to-weight ratio
- "Soft no-load" function automatically reduces the speed of the motor when idling
- Makita Motor Advantage engineered for more power and longer tool life
- Automatic brush cut-off protects commutator from damage for longer tool life

Model HM1500B Includes: Steel Tool Case

Blows Per Minute	1,300 BPM
Impact Energy	18.4 / 25 J
AMPS	13.5
Noise Level	101 dB
Vibration (m/s²)	26
Cord Length (ft)	17"
Overall Length	31-3/4"
Net Weight	44.1 lbs.
Shipping Weight	66.7 lbs.
Bit Type	1-1/8" Hex



HM1307CB

35 lb. DEMOLITION HAMMER
Electronic Controller for Operator Convenience

- Powerful 14 AMP motor delivers 25.7 lbs. of impact energy to handle the most demanding applications
- Constant Speed Control automatically applies additional power to the motor to maintain consistent speed under load for the most challenging jobs
- Soft Start suppresses start-up reaction for smoother start-ups and better accuracy
- L.E.D. Service Light notifies the user approximately 8 hours before the brushes need to be replaced
- L.E.D. Power Lights indicate switch failure or cord damage

Model HM1307CB Includes: 20-1/2" Bull Point, 1-1/8" Hex (D-21353), Tool Case

Blows Per Minute (variable speed)	730 - 1,450 BPM
Impact Energy	25.7 / 34.9 J
AMPS	14
Noise Level	101 dB
Vibration (m/s²)	12
Overall Length	32-1/2"
Net Weight	38.2 lbs.
Shipping Weight	56.422 lbs.
Bit Type	1-1/8" Hex



HM1214C

27 lb. AVT® DEMOLITION HAMMER
Anti-Vibration Technology for 2X Less Vibration

- Powerful 14 AMP motor delivers 19 ft.lbs. of impact energy to handle the most demanding applications
- Anti-Vibration Technology is an internal counterbalance system that greatly reduces vibration
- Constant speed control automatically applies additional power to the motor to maintain speed under load
- Soft start suppresses start-up reaction for more precision and better accuracy

Model HM1214C Includes: Side Handle (135283-4), 12" Bull Point, SDS-MAX (751423-A), Hammer Bit Grease (194683-7), Tool Case

Blows Per Minute (variable speed)	950 - 1,900 BPM
Impact Energy	19 / 25.7 J
AMPS	14
Noise Level	101 dB
Vibration (m/s²)	8
Overall Length	27-1/2"
Net Weight	27.1 lbs.
Shipping Weight	46.284 lbs.
Bit Type	Accepts SDS-MAX



HM1203C

20 lb. DEMOLITION HAMMER
Compact Power with Less Weight

- Powerful 14 AMP motor delivers 18.8 ft.lbs. of impact energy to handle the most demanding applications
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs
- Variable speed control dial enables user to match the speed to the application for greater versatility
- Soft start suppresses start-up reaction for precision and better accuracy
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced

Model HM1203C Includes: Side Handle (135283-4), 12" Bull Point, SDS-MAX (751423-A), Hammer Bit Grease (194683-7), Tool Case

Blows Per Minute (variable speed)	950 - 1,900 BPM
Impact Energy	18.8 / 25.5 J
AMPS	14
Noise Level	95 dB
Vibration (m/s²)	15.5
Overall Length	22-3/4"
Net Weight	20.3 lbs.
Shipping Weight	36 lbs.
Bit Type	Accepts SDS-MAX



HM1211B

20 lb. DEMOLITION HAMMER
Air Cushion Design for Powerful Performance

- Powerful 10 AMP motor for fast and efficient operation
- Comfortable rubber D-shaped grip side handle absorbs vibration; secures in four positions for operator comfort
- One-touch latch bit retainer for quick bit changes
- Automatic brush cut-off protects commutator from damage for longer tool life
- Factory grease packed for reduced maintenance
- AC/DC switch for use with alternative power source

Model HM1211B Includes: Hex Wrench (783202-0), Tool Case

Blows Per Minute	2,000 BPM
Impact Energy	10.5 ft.lbs. / 14.2 J
AMPS	10
Overall Length	19-5/16"
Net Weight	20.7 lbs.
Shipping Weight	33 lbs.
Bit Type	3/4" Hex - 21/32" Round

1-1/8" Hex Shank Dust Extracting Attachment

MAXIMUM EXTRACTION

Durable Construction for use on the Most Demanding Jobsites

Applications



Attaches to 1-1/8" demo bit 1" to 4" from the surface being demolished for efficient dust extraction

Convenience



Convenient hose holders keep the hose out of the way during use



197172-1

1-1/8" HEX SHANK DUST EXTRACTING ATTACHMENT

- Large opening allows for maximum dust extraction
- Durable plastic construction for long life
- Includes hose and hose holders
- For use with demolition hammers that utilize 1-1/8" hex shank bits

Premium Hammer Cart

CONVENIENT TRANSPORTATION

Conveniently Transports Breaker Hammers and Bits on the Jobsite

Capacity



Bit retainers firmly hold up to (4) 1-1/8" demolition steel bits

Convenience



Stair climber rails for convenient lifting up stairs, curbs, truck beds, and other elevated surfaces

Durability



Rugged 9" semi-pneumatic wheels roll smoothly through rough jobsite terrain

Control



Adjustable strap keeps hammer securely fastened to the cart during transportation

T-02892

PREMIUM HAMMER CART

- For use with 1-1/8" hex shank Breaker and Demolition Hammers (HM1307CB, HM1317CB, HM1500B, HM1810, HM1812)
- Ball bearing hubs allow the wheels to rotate quickly and smoothly
- Corrosion resistant coating adds a layer of protection against harsh elements
- High-quality steel for long life



Hammer Bit Grease

Description	Size	Part #
For greasing the shanks of bits before installing them in the hammer	100ml	194683-7

*For use with all brands and types of bits for rotary and demolition hammers

Hammer Grease

Description	Model	Part #
30 cc used to lubricate grease reservoir	All Hammers	A-90582

Oil Supply

Description	Model	Part #
Oil Supply 100 cc	HM1301	181118-7

Blow-Out Bulb

Description	Model	Part #
Blows chips and dust from drilled holes before setting anchor fasteners	All Hammers	765009-6