

THERMOPLASTIC AG CHEMICAL & TRANSFER PUMP

APPLICATIONS

Ideal for sprayer applications such as liquid fertilizers and agricultural chemicals*.

FEATURES & BENEFITS

- Powered by Kohler 3000 Series 6.5 hp engine
- Lightweight corrosion-resistant construction
- Easy to prime to 25'; no additional priming required after initial fill
- Integrated check valve
- Includes heavy-duty roll frame
- EPA certified
- Carbon ceramic mechanical seal with EPDM elastomers

**Not to be used for applying driveway sealant.*

Powered by

KOHLER



Powered by Kohler® is a registered trademark of Kohler Co.



Model	Item No.	UPC	cc	Intake	Discharge	Suction Lift	Max. Height	Max. Flow (GPM)	Fuel Tank (qt)	Engine
6RLPG-2K	617071	0 10121 14413 2	196	2" FNPT	2" FNPT	25'	140'	195	3.8	Kohler 3000 Series (196cc)

CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
6RLPG-2KRF	17.25"	20.5"	18"	47.5	3.68	8	4	2

6RLPG-2KRF

