



# The NEW DL579 Is An Essential Clamp Meter!



## We Made It Better!

- Easy access battery latches. No screwdriver needed.
- Test lead storage for convenience
- Added selection dial to navigate test functions
- Increased the range of Volts and Capacitance



## All The Pro Features You Love

- Same functionality as our popular DL389B
- 12 Key test functions
- More than 11 features

## Distinguished In The Marketplace

- 1-Year Limited Warranty
- Professional Safety Ratings

## Available For A Great Price!

**\$175<sup>95</sup>** TNP

DESIGNED BY  
MADE BY  
**UEI**



— BACKED BY —  
**UEI**  
QUALITY

**1**  
YEAR  
WARRANTY



### DL500 Series Clamp Meter Comparison 2022



Part #	DL569	DL579	DL589	DL599
UPC	053533509281	053533509274	053533509144	053533509137
TRMS		•	•	•
AC Volts	750V	750V	750V	1000V
DC Volts	1000V	1000V	1000V	1000V
AC current (amps)	400A	600A	600A	600A
DC current (amps)			600A	600A
Resistance (Ohms)	40kΩ	60MΩ	60MΩ	60MΩ
Continuity/Diode	•	•	•	•
Capacitance (Farads)		6000μF	2000μF	9999μF
AC/DC microamps		2000μA	2000μA	2000μA
Frequency (Hertz)		99.99Hz - 99.99kHz	99.99Hz - 99.99kHz	99.99Hz - 99.99kHz
Duty cycle		•	•	•
Low Z (impedance)		•	•	•
LRA inrush		•	•	•
Temperature (K-type input)		-328° to 2462°F	-328° to 2462°F	-328° to 2462°F
NCV (LED & Audible)		•	•	•
Min/Max	•	•	•	•
Hold	•	•	Peak Hold	Data/Peak
Ranging	Auto	Auto/Man	Auto/Man	Auto/Man
Display count	4000 (3 3/4 dgt)	6000 (3 5/6 dgt)	6000 (3 5/6 dgt)	6000 (3 5/6 dgt)
Auto power off	•	•	•	•
Low battery warning	•	•	•	•
Test lead storage	•	•	•	•
Dual display	•	•	•	•
High voltage alert	•	•	•	•
Auto Calibration	•	•	•	•
Easy access battery latches	•	•	•	•
Backlight		•	•	•
Magnetic mount/strap	Optional	Optional	•	•
Worklight			•	•
Temperature differential			•	•
DC Zero			•	•
Auto AC/DC selection for V/A				•
Wireless to app				•
3-Phase motor rotation test				•
Motor unbalanced test				•
Low pass filter				•
Safety Rating	CATIV 300V CATIII 600V	CATIV 300V CATIII 600V	CATIV 600V CATIII 1000V	CATIV 600V CATIII 1000V
Warranty	1-year limited	1-year limited	2-year limited	2-year limited

Safety Rated: CATIV 300V / CATIII 600V  
Certified to IEC 61010-1, 3rd edition



### Includes

- Test Leads (ATL55)
- Alligator Clips (AAC3)
- Temperature Probes (ATT29)
- Zippered Pouch Batteries 2 (AAA)
- Manual