



## UTL261

### Features:

- Data Hold
- Auto / Manual Ranging
- Backlit Display
- Max Capture
- Worklight
- 1 Year Limited Warranty

### Specifications:

- Display 3 1/2 digits 2000 count
- Automatic function indication screen
- Sample Rate: 3 times/sec digital data
- AC current: 2A/20A/200A ± 2%
- DC voltage: 600V ± 1%
- AC voltage: 600V ± 1.5%
- Resistance: 200Ω ± 1%
- Audible continuity
- Maximum conductor size: ø28mm



### General Specifications

- Display: LCD 3-1/2 Digits 2000 count
- Refresh Rate: 3 times/sec
- Overrange display: "OL"
- Power battery: DC1.5V x 3 SIZE AAA.
- Battery Life: Approx. 100 hours
- Clamp jaw opening: 1.02" (26mm)
- Operating Elevation Up to 6571.7 ft. (2000m)
- Operating Temperature: 32°F to 104°F (0°C to 40°C) at < 75% R.H
- Storage Temperature: 14°F to 140°F (-10°C to 60°C) at < 80% R.H
- Accuracy Temperature: Stated Accuracy at 73°F ± 41°F (23°C to ± 5°C) < 75% R.H
- Dimensions: 8.66 x 3.19 x 1.6" (220 x 81 x 41mm)
- Weight: about 0.63lbs. (286g) (battery installed)
- Certifications: CE, C-ETL-US
- Standards: IEC61010-1, IEC61010-2-032, Double Insulated
- Operating Category: 600V CAT III
- Pollution degree: 2.

### Includes



- Soft Carrying Case
- Test Leads
- 3 X 1.5V AAA Batteries
- Manual

### Specifications

#### DC Voltage Measurement

Range	Resolution	Accuracy
200mV	0.1mV	± (0.6% + 3 dgts)
2V	1mV	
20V	10mV	
200V	0.1V	
600V	100mV	± (0.8% + 3 dgts)

Input impedance: 10MΩ

Overload protection: 600V RMS

#### AC Voltage Measurement

Range	Resolution	Accuracy
200mV	0.1mV	± (2.0% + 3 dgts)
2V	1mV	± (0.8% + 5 dgts)
20V	10mV	
200V	0.1V	
600V	1V	

Input impedance: 10MΩ

Frequency Range: 50Hz to 60Hz

Overload protection: 600V RMS

#### Diode Test

Range	Max. Test Current	Open Circuit Voltage
0.5 to 2.7V	1mA	1.5V

Overload protection: 250V RMS

#### AC Current

Range	Resolution	Accuracy
2A	0.001A	± (2.0% + 5 dgts)
20A	0.01A	
200A	0.1A	
600mA	1A	

Frequency Range: 50Hz to 60Hz

Overload protection: 600A for 20 seconds

#### Resistance

Range	Resolution	Accuracy
200Ω	0.1Ω	± (0.8% + 4 dgts)
2kΩ	0.001kΩ	
20kΩ	0.01kΩ	
200kΩ	0.1kΩ	
2MΩ	0.001MΩ	
20MΩ	0.01MΩ	± (1.2% + 5 dgts)

Overload protection: 250V RMS

#### Continuity

Audible Threshold	Open Test Circuit	Resolution
≤ 60Ω	0.45V	100mΩ

Overload protection: 250V RMS

#### USA

1-800-547-5740 • Fax: (503) 643-6322  
www.utltest.net • Email: info@ueitest.com  
8030 SW Nimbus Ave.  
Beaverton, OR 97008

#### CANADA

1-877-475-0648 • Fax: (604) 278-8299  
www.utltest.net • Email: info@ueitest.com  
150-13571 Verdun Place  
Richmond, B.C. V6V 1W5

#### EUROPE

+44 1707 375550 • Fax: +44 1707 393277

