

**OPTIONS****Handle**

B32A (B32A)

**Control Stop**

Ground Joint (GJ)

1" Straight (E)

**Vacuum Breaker**

Less (XYV)

**Bumper**

Angle Stop Extended (YG)

Angle Stop (YO)

**Special Features**

Whitworth Thread (WWT)

**NOTES**For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard NAVAL 110 shown

**DESCRIPTION**

Naval Exposed Manual Water Closet Flushometer

**FEATURES**

- Non-hold-open oscillating handle, Bak-Chek™ control stop and self-cleaning Xpelor Metering By-Pass ensure reliable operation and accurate flush delivery
- Available with adjustable or ground joint supply stop (ground joint recommended for salt water applications)
- Factory set flush volume of either 1.6 gpf/6.0 Lpf or 3.5 gpf/13.2 Lpf with adjustment range of 1.5 gpf/5.7 Lpf to 7.0 gpf/26.5 Lpf
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037
- Sweat solder kit not provided, order separately if required.

**DOWNLOADS**

- [Naval Piston Type Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](http://sloan.com)