

Model

WETS 9002.9012-1.6/1.1 DF

Two Piece Floor Mounted Dual Flush Elongated Toilet Tank System

DESCRIPTION

Complete two piece, dual flush, vitreous china, elongated floor mounted toilet tank system.

Flush Cycle

Model WETS-9002.9012-1.6/1.1 (Full Flush 1.6 gpf / 6.0 Lpf) (Reduced Flush 1.1 gpf / 4.2 Lpf)

- ST-9002-A 1.6/1.1 gpf Bowl
- ST-9012-A 1.6/1.1 gpf Dual Flush Tank





SPECIFICATIONS

Quiet, two piece dual flush toilet tank with centered push button and vitreous china floor mounted elongated water closet and compact tank with the following features:

Two Piece Toilet System

- · Contemporary design
- · Polished chrome top mount actuator
- Quiet powerful gravity flush
- Siphon jet flushing action
- Elongated bowl
- 12" rough-in
- · 3" valve opening for better flush performance
- Vitreous china
- Integral trap
- Color matched floor caps
- Floor mount bolts included
- 2 1/8" fully glazed trapway
- Water pressure range: 25 to 80 PSI
- Easy top mount actuator
- Water spot area 7 ⁷/₈" x 6 ¹/₄"
- Tank and bowl must be ordered as two (2) separate items
- · Toilet seat not included
- Compatible with toilet seat models:
 Olsonite 10CT, Bemis 1955CT & Church
 Commercial 295CT
- · Water supply not included
- Toilet tank system is in compliance to the applicable sections of ASME A112.19.2/CSA B45.0/CSA B45.1

FEATURES

Performance

Sloan's toilet tank system incorporates a high performance Dual Flush valve to ensure an efficient and optimum flushing performance. 3" valve opening offers better waste removal and powerfully clears the bowl.

Colors and Accessories

Available in the color White with polished chrome top mount actuator. For additional information refer to our price book.

Functional

The tank valve provides a high efficient 1.6/1.1 gpf. Durable construction provides non-corrosive dependability. Adjustment screw allows water level adjustment for individual preference.

Economical

High Efficiency Toilet dual flush tank system provides additional savings in water usage. Reduces maintenance and operation costs. Designed for commercial use and also ideal for residential.

Warranty

3 year (limited)

Product Specification

Elongated toilet tank system shall be made of vitreous china. Toilet tank system shall be installed at required height of 29" from floor to top of tank fixture. Toilet tank system shall be floor mounted. Toilet tank system shall include floor mount bolts and caps. Toilet tank system shall use a dual flush1.6 gpf/1.1 gpf top mount actuator. Toilet tank system shall be Sloan model WETS-9002.9012-1.6/1.1.





Listed by I.A.P.M.O.

This space for Architect/Engineer approval	
Job Name	Date
Model Specified	Quantity
Variations Specified	
Customer/Wholesaler	
Contractor	
Architect	

Copyright © 2010 Sloan Valve Company Rev. 0b (07/10)

10500 Seymour Avenue Franklin Park, IL 60131

Phone: 1-800-9-VALVE-9 (982-5839) or 1-847-671-4300

Fax: 1-800-447-8329 or 1-847-671-4380 www.sloanvalve.com



Model

WETS 9002.9012-1.6/1.1
Two Piece Floor Mounted Dual Flush Elongated Toilet Tank System

DESCRIPTION

Complete two piece, dual flush, vitreous china, elongated floor mounted toilet tank system.

Flush Cycle

☐Model WETS-9002.9012-1.6/1.1 (Full Flush 1.6 gpf / 6.0 Lpf) (Reduced Flush 1.1 gpf / 4.2 Lpf)

- ST-9002-A 1.6/1.1 gpf Bowl
- ST-9012-A 1.6/1.1 gpf Dual Flush Tank

DIMENSIONS/ROUGH-IN





