

Electronic Faucet 590T0 & 590T1 Series

TECK®

 **DELTA**
COMMERCIAL

Specification: (example)

- **Battery** (4 'C' cell) or **Hardwire** (24 VAC) infrared electronic handwash system
- H₂OPTICS™ technology – no external adjustments required
- Chrome plated one piece **CAST** Hi-Rise spout with integral sensor
- Adjustable sensing range and timeout
- Audible low battery indicator
- Forged brass solenoid valve (control box No. 0 only)
- Tempered water supplied to solenoid valve, (except control box options No. 0 and 1)
- and... with... (specify battery or hardwire)
 - with... (add spout required)
 - with... (add outlet required)
 - with... (add control box required)
 - with... (transformer - specify separately - See Back Page)

Synergy®

H₂OPTICS™



590T0120

Engineer/Architect Approval

Model Specified:

Approval:

Date:

DESCRIPTION	PRODUCT NO.		
Hardwire	590T0		
Battery Operated	590T1		



SPOUT & SENSOR		OUTLET		CONTROL BOX	
0	<input checked="" type="checkbox"/>	0	<input checked="" type="checkbox"/>	0	<input checked="" type="checkbox"/>
1 Single Hole Deckmount Hi-Rise Spout with Integral Sensor	<input type="checkbox"/>	1	<input type="checkbox"/>	1 Surface Mount Housing* SEE Specification Drawing #13	<input type="checkbox"/>
2 Deckmount Hi-Rise Spout with Integral Sensor and 4" Forged Coverplate	<input type="checkbox"/>	2 Vandal Resistant 1.5 USGPM (5.7 L/min.) Laminar w/Agion® Antimicrobial	<input type="checkbox"/>	2 For RECESSED MOUNTING Components ASSEMBLED in 10" Box w/S/S Cover.* SEE Specification Drawing #14	<input type="checkbox"/>
3	<input type="checkbox"/>	3 Vandal Resistant 1.5 USGPM (5.7 L/min.) Flow Control Aerator	<input type="checkbox"/>	3	<input type="checkbox"/>
4	<input type="checkbox"/>	4	<input type="checkbox"/>	4	<input type="checkbox"/>
5	<input type="checkbox"/>	5 Vandal Resistant 0.5 USGPM (1.9 L/min.) Flow Control Non-Aerating Spray Outlet	<input type="checkbox"/>	5 For RECESSED MOUNTING Components & Mechanical Mixing Valve (1) ASSEMBLED in 10" Box w/S/S Cover. SEE Specification Drawing #15	<input type="checkbox"/>
6	<input type="checkbox"/>	6 Vandal Resistant 1.0 USGPM (3.8 L/min.) Flow Control Non-Aerating Spray Outlet	<input type="checkbox"/>	6	<input type="checkbox"/>
7	<input type="checkbox"/>	7	<input type="checkbox"/>	7 For RECESSED MOUNTING Components & Thermostatic Mixing Valve ASSEMBLED in 10" Box w/S/S Cover. SEE Specification Drawing #16	<input type="checkbox"/>
8 Deckmount Hi-Rise Spout with Integral Sensor and 8" Forged Coverplate	<input type="checkbox"/>	8	<input type="checkbox"/>	8	<input type="checkbox"/>
9	<input type="checkbox"/>	9	<input type="checkbox"/>	9	<input type="checkbox"/>

* Mixing Valve supplied by others.

(1) With Thermostatic Limit Stop.

Refer to www.specselect.com for individual models.

Flowrates are at 60 PSI.

Note: Use this page front and back, with specification drawing page referenced above, as product submittal sheets.


Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.

Approvals:

- CSA certified
- Complies to ASME A112.18.1
- ADA Compliant and meets Handicapped Accessibility Standard ASME A117.1 of less than 5 lbs. handle operating force.
- IAPMO listed
- Control Box Option 6 Mechanical Mixing Valve CSA certified
- Control Box Option 8 Thermostatic Mixing Valve CSA certified and meets ASSE 1016 and 1017

(Contact Delta Representative for State and/or Local Approvals.)


U.S. Patent #6, 826, 455.

FLOWRATE vs PRESSURE

OPERATION:

- Hands free (touchless) operation.
- Water flows when sensor is activated.
- Water flow stops upon de-activation of sensor.
- Auto shut-off feature that is selectable between 15 to 75 seconds. Factory set to 45 seconds. Will reset once obstruction is removed.
- Adjustable sensing distance 76 to 381mm (3" to 15") factory set to 229mm (9") (+/- 1.0")
- Low battery audible beep (for battery models only) will activate after faucet shuts off when approximately 1500 cycles remain.

NOTE: For optimum performance of this product, we recommend a system pressure between 20 and 80 PSI static. This product will operate up to a maximum of 125 PSI static per ANSI and CSA requirements. However, we do not recommend pressures above 80 PSI. Thermal expansion or leaking pressure reducing valves may require use of expansion tanks or relief valves to ensure your system never exceeds its maximum intended pressure setting.

Note: Measurements may vary - 6mm (0.25")


590T0 & 590T1 ELECTRONIC FAUCET OPTIONAL ACCESSORIES:

<input checked="" type="checkbox"/>	TRANSFORMERS:
060704A	110 to 24VAC Class II 20VA (Up to 5 Electronic Valves)
060771A	110 to 24VAC Class II 40VA (Up to 10 Electronic Valves)
060772A	110 to 24VAC Class II 100VA (Up to 25 Electronic Valves)
<input checked="" type="checkbox"/>	CORDS:
060690A	36" Cable Extension

Refer to www.specselect.com for individual models.

Product supplied as shown by solid lines. All items shown by dotted lines supplied by others.




COMPONENTS ONLY UNASSEMBLED

590T0 AND 590TI SERIES

✓	PRODUCT NO.				VALVE TYPE	COVER
	590T	0		0	Deckmount Handwash Hardwire	Surface Mounted, Vandal Proof Control Housing
	590T	I		0	Deckmount Handwash Battery	Surface Mounted, Vandal Proof Control Housing


590T0 and 590TI SERIES

Battery Operated box shown.
Hardwire Version comes
complete with Watertight
Connector and Hardwire
Converter 24VAC to 6VDC.



Note: Stainless Steel hose connection supplied
between Solenoid Valve and Spout

S/S HOSE



Note: Measurements may vary \pm 6mm (0.25")


TEMPERED WATER - ASSEMBLED CONTROL BOX
590T0 AND 590TI SERIES

✓	PRODUCT NO.	FAUCET TYPE	MOUNT TYPE	COVER
	*590T 0	Deckmount Handwash Hardwire	Recessed Mount	305mm (12") Stainless Steel
	*590T I	Deckmount Handwash Battery	Recessed Mount	305mm (12") Stainless Steel

*This product is supplied with Flexible Sensor Cord Conduit on Recessed Mount Installations.

**590T0 and 590TI
SERIES**

Battery Operated box shown.
Hardwire Version comes
complete with Watertight
Connector and Hardwire
Converter 24VAC to 6VDC.



Note: For wallhung sink installations, sensor conduit rough-in should be directly under basin to minimize sensor cord exposure.

Note: Measurements may vary $\pm 6\text{mm}$ (0.25")

MECHANICAL MIXING VALVE ASSEMBLED CONTROL BOX


590T0 AND 590TI SERIES

✓	PRODUCT NO.			FAUCET TYPE	MOUNT TYPE	COVER		
	*590T	0		6	Deckmount Handwash Hardwire	Recessed Mount	305mm (12")	Stainless Steel
	*590T	I		6	Deckmount Handwash Battery	Recessed Mount	305mm (12")	Stainless Steel

*This product is supplied with Flexible Sensor Cord Conduit on Recessed Mount Installations.

590T0 and 590TI SERIES

Battery Operated box shown.
Hardwire Version comes
complete with Watertight
Connector and Hardwire
Converter 24VAC to 6VDC.



Note: For wallhung sink installations, sensor conduit rough-in should be directly under basin to minimize sensor cord exposure.

Note: Measurements may vary \pm 6mm (0.25")


THERMOSTATIC MIXING VALVE ASSEMBLED CONTROL BOX
590T0 AND 590TI SERIES

✓	PRODUCT NO.			FAUCET TYPE	MOUNT TYPE	COVER		
	*590T	0		8	Deckmount Handwash Hardwire	Recessed Mount	305mm (12")	Stainless Steel
	*590T	I		8	Deckmount Handwash Battery	Recessed Mount	305mm (12")	Stainless Steel

*This product is supplied with Flexible Sensor Cord Conduit on Recessed Mount Installations.

**590T0 and 590TI
SERIES**

Battery Operated box shown.
Hardwire Version comes
complete with Watertight
Connector and Hardwire
Converter 24VAC to 6VDC.



Note: For wallhung sink installations, sensor conduit rough-in should be directly under basin to minimize sensor cord exposure.

Note: Measurements may vary $\pm 6\text{mm}$ (0.25")