

TH108 Series

Baseboards & convectors

With TRIAC switching, this digital non-programmable model delivers exceptional accuracy and silent operation in a stylish, easy-to-use design

MODELS & RATINGS

TH108	1500 W @ 120 V	12.5 A resistive	60 Hz	2 wires / SPST
	3000 W @ 240 V	12.5 A resistive	60 Hz	2 wires / SPST
TH108-A-347S3	4335 W @ 347 V	12.5 A resistive	60 Hz	2 wires / SPST (min. 2 A load)



NON-PROGRAMMABLE

SPECIFICATIONS

TEMPERATURE CONTROL
Microprocessor-optimized PIA
Heating cycles: 15 seconds
Accuracy: ± 0.15°C / 0.27°F

SWITCHING ACTION
TRIAC: Silent operation

TEMPERATURE SETTING
Manual
°C or °F selectable

DIMENSIONS (H•W•D)
120 x 115 x 26 mm / 4.8 x 4.5 x 1 inches

FEATURES

Ultimate temperature control – the most accurate type of thermostat on the market (± 0.15°C / 0.27°F)

On-screen heating power indicator gives at-a-glance verification of power being used


2-wire non-polarized connection means fast, hassle-free installation

Up/down buttons enable easy temp. setting

Also ideal for radiant ceilings

Battery free

INSTALLATION



T_A = Ambient Temperature

The advantages of TRIAC switching

Although the TH108 is non-programmable, its TRIAC precision still saves up to 10% on your heating bill. Here's how:

- Unsurpassed precision eliminates temperature swings
- No temperature swings means you are comfortable at a lower setpoint
- Comfort at a lower setpoint saves money on heating bills

