



## ADVANTAGES OF MAKITA<sup>®</sup> HIGH PRESSURE

### MORE POWER

High pressure compressor technology delivers 400 PSI

### LESS WEIGHT

Nailers are up to 30% less weight than conventional nailers


### BETTER PERFORMANCE

Dual-head (2-stage) pump compressor provides faster recovery time

### INCREASED EFFICIENCY

Low amp draw reduces tripped breakers and voltage drop during start-ups

### MORE POWER MORE CONSISTENCY



Drive larger nails (3-1/2" x .162" size) more consistently in engineered materials



### AC310H

#### 2.5 HP\* HIGH PRESSURE AIR COMPRESSOR High Pressure Technology Delivers 400 PSI Capacity

- Dual capacity: two universal couplers for conventional nailers and two couplers for high pressure nailers
- Low amp draw reduces incidences of tripped breakers and voltage drop during start-ups
- Efficient dual-head (2-stage) pump provides faster recovery time and improved performance
- Pump runs at lower RPM (1,720) resulting in lower noise and improved pump durability

**Model AC310H Includes:** (2) 1/4" High Pressure Universal Quick Coupler, Female (HY00000337), (2) High Pressure Quick Coupler (HY00000351)

|                                                       |            |
|-------------------------------------------------------|------------|
| Maximum Horsepower                                    | 2-1/2 HP   |
| Running Horsepower                                    | 1.9 HP     |
| Tank                                                  | 1.6 gal.   |
| Performance:                                          |            |
| 40 PSI (3.7 CFM), 90 PSI (3.6 CFM), 300 PSI (2.7 CFM) |            |
| Maximum Pressure                                      | 400 PSI    |
| Net Weight                                            | 79.4 lbs.  |
| Shipping Weight                                       | 88.16 lbs. |



### AN930H

15"

#### 3-1/2" HIGH PRESSURE FRAMING COIL NAILER Superior Power-to-Weight Ratio

- Up to 30% less weight (5.7 lbs.) and up to 30% smaller than conventional framing nailers
- "Tool-less" depth adjustment engineered for more precise flush and countersink nailing
- 2-mode trigger allows operator to select sequential or contact nailing options
- High capacity canister holds up to 300 nails for high production applications
- High Pressure technology enables nailer to operate at 170-320 PSI for more consistent flush nailing

**Model AN930H Includes:** (424390-1), Air Tool Oil (194381-3), Tool Case, Safety Goggles

|                           |                                                            |
|---------------------------|------------------------------------------------------------|
| Operating Air Pressure    | 170 - 320 PSI                                              |
| Nail Size                 | 1-3/4" - 3-1/2" .099" - .148" shank diameter wire collated |
| Nail Size (in. ga.)       | 1-3/4" to 3-1/2" ( ga.)                                    |
| Magazine Capacity (range) | 150 - 300                                                  |
| Dimensions (LxWxH)        | 11-1/4" x 5" x 13"                                         |
| Overall Length            | 11-1/4"                                                    |
| Net Weight                | 5.7 lbs.                                                   |
| Shipping Weight           | 12.4 lbs.                                                  |



### AN610H

15"

#### 2-1/2" HIGH PRESSURE SIDING COIL NAILER Delivers Precise Flush Nailing

- Innovative high pressure technology enables nailer to operate at 320 PSI for more consistent flush nailing
- "Tool-less" depth adjustment engineered for more precise flush and countersink nailing
- 2-mode selector switch allows operator to select sequential or contact nailing options
- Multi-directional exhaust port directs exhaust air away from operator
- High capacity canister holds up to 400 nails for high production applications

**Model AN610H Includes:** No-Mar Tip (421574-2), Air Tool Oil (194381-3), Tool Case, Safety Goggles (192517-8)

|                           |                                              |
|---------------------------|----------------------------------------------|
| Operating Air Pressure    | 140 - 320 PSI                                |
| Nail Size                 | 1-1/4" - 2-1/2" .080" - .113" shank diameter |
| Magazine Capacity (range) | 200 - 400                                    |
| Dimensions (LxWxH)        | 11-1/8" x 5-3/8" x 10-7/8"                   |
| Net Weight                | 4.2 lbs.                                     |
| Shipping Weight           | 7.94 lbs.                                    |



### PNEUMATICS

### AN923

21"

#### 3-1/2" FRAMING NAILER

Drives up to 3-1/2" x .162" (16d) Nails

- 3-Mode selector switch (contact, sequential, lock) allows user control over nailing options
- Large capacity air chamber for increased power to drive nails varying in length from 2" to 3-1/2"
- Built-in air filter minimizes dust and debris from entering tool
- Anti-dry mechanism stops tool when three nails remain in the magazine
- Solid rear-loading aluminum magazine for longer life

**Model AN923 Includes:** Pneumatic Nailer Oil (181434-7), Tool Hook (122742-7), Safety Goggles (191687-A), Air Fitting (311006-A)

|                           |                                                                   |
|---------------------------|-------------------------------------------------------------------|
| Operating Air Pressure    | 65 - 120 PSI                                                      |
| Nail Size                 | 2" - 3-1/2" .113" - .162" shank diameter plastic or wire collated |
| Magazine Capacity (range) | 64 - 74                                                           |
| Dimensions (LxWxH)        | 22" x 4-1/4" x 13-11/16"                                          |
| Net Weight                | 8.7 lbs.                                                          |
| Shipping Weight           | 12.3 lbs.                                                         |



### PNEUMATICS

### AN902

15"

#### 3-1/2" FRAMING COIL NAILER

More Power and Less Weight for Increased Versatility

- "Tool-less" depth adjustment engineered for more precise flush and countersink nailing
- Drives 1-3/4" to 3-1/2" coil framing nails
- Easy access nose design for clearing jammed nails
- Easy loading canister with nail size adjustment provides maximum versatility
- Rubberized handle for better fit and added comfort
- Contact mode trigger allows operator to control nailing operations

**Model AN902 Includes:** Pneumatic Nailer Oil (181434-7), Safety Goggles (191687-A), No-Mar Tip (BA00000372)

|                           |                                                            |
|---------------------------|------------------------------------------------------------|
| Operating Air Pressure    | 60 - 120 PSI                                               |
| Nail Size                 | 1-3/4" - 3-1/2" .099" - .148" shank diameter wire collated |
| Magazine Capacity (range) | 150 - 300                                                  |
| Dimensions (LxWxH)        | 12-1/2" x 5" x 14-7/8"                                     |
| Net Weight                | 7.7 lbs.                                                   |
| Shipping Weight           | 10.1 lbs.                                                  |



### PNEUMATICS

### AN611

15"

#### 2-1/2" SIDING COIL NAILER

"Tool-less" Depth Adjustment with 9 Settings

- "Tool-less" depth adjustment engineered for more precise flush and countersink nailing
- 3-mode selector switch (contact, sequential, lock) allows user control over nailing options
- Built-in air filter minimizes dust and debris from entering tool
- Multi-directional exhaust port directs exhaust air away from user
- Easy-loading canister with nail size adjustment provides maximum versatility

**Model AN611 Includes:** Pneumatic Nailer Oil (181434-7), Hex Wrench (783202-0), Safety Goggles (191687-A), Air Fitting (311006-A), Tool Case

|                           |                                              |
|---------------------------|----------------------------------------------|
| Operating Air Pressure    | 65 - 120 PSI                                 |
| Nail Size                 | 1-1/4" - 2-1/2" .080" - .099" shank diameter |
| Magazine Capacity (range) | 200 - 400                                    |
| Dimensions (LxWxH)        | 13-1/16" x 5" x 12-1/2"                      |
| Net Weight                | 5.1 lbs.                                     |
| Shipping Weight           | 10.15 lbs.                                   |

## High Pressure Accessories

### High Pressure Contractor Hose

- Up to 2X less weight than heavier hoses, ideal for trim roofing, framing and construction
- Highly flexible and less kinks for easy rolling and improved air flow
- Engineered to be more durable than vinyl hoses for longer life and improved performance
- All-weather resistant, engineered to maintain flexibility even under extreme weather conditions

| Size | Model                  | Part #  |
|------|------------------------|---------|
| 100' | AC310H, AN610H, AN930H | B-80020 |
| 50'  |                        | B-80014 |



### High Pressure Quick Coupler

| Size | Style | Model  | Part #     |
|------|-------|--------|------------|
| 1/4" | Male  | AC310H | HY00000351 |

### Wheel Kit for AC310H

- Solid rubberized wheels for easy job site portability
- Large rubberized handle for added control and comfort

| Model  | Part #     |
|--------|------------|
| AC310H | HY00000212 |

AC310H Sold Separately

\*Maximum horsepower