

DESCRIPTION

- Metal construction with various finishes identified by suffix
- Flexible supplies with 3/8" compression fittings
- Includes side spray with Duralock™ quick connect system
- 360° rotating spout

OPERATION

- Lever style handle
- Operates with less than 5 lbs. of force

FLOW

- Aerator is limited to 1.5 gpm max (5.7 L/min)

CARTRIDGE


- 1255™ Duralast® cartridge for Single-Handle Faucets
- Nonmetallic/nonferrous and stainless steel material

STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including NSF 61/9 & 372
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA ♿ for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
 - 10 year limited warranty when used in a multifamily installation
 - 5 year limited warranty when used in a commercial installation
- Visit www.moen.com/support for complete details and limitations



Belfield™
Single Handle Lever
Kitchen Faucet

Model: 7240 series less Side Spray

Model: 7245 series with Side Spray

NOTE: 7240 SERIES IS DESIGNED TO INSTALL THROUGH 1 HOLE OR 3 HOLES 1-1/4" (32mm) MIN. DIAM. AND 4" (102mm) ON CENTER.

NOTE: 7245 SERIES IS DESIGNED TO INSTALL THROUGH 2 HOLES OR 4 HOLES 1-1/4" (32mm) MIN. DIA. AND 4" (102mm) ON CENTER.

