

# Bolt Cutters



## Bolt Cutters

- Hardened alloy steel jaws are designed and manufactured to assure the longest possible blade life.
- One-step internal cam mechanism provides the quickest and simplest way to keep the cutting blades precisely aligned.
- Handles and grips designed to allow greater mechanical advantage for crisp, controlled cutting.

Catalog No.	Model No.	Description	Capacity/Metals						Weight	
			Soft (15RC) <sup>1</sup>		Medium (31RC) <sup>2</sup>		Hard (42RC) <sup>3</sup>		lb.	kg
			in.	mm	in.	mm	in.	mm		
14213	S14	Center Cut	<sup>5</sup> / <sub>16</sub>	7.9	<sup>1</sup> / <sub>4</sub>	6.4	<sup>3</sup> / <sub>16</sub>	4.8	1 <sup>1</sup> / <sub>4</sub>	1.00
14218	S18	Center Cut	<sup>3</sup> / <sub>8</sub>	9.5	<sup>5</sup> / <sub>16</sub>	7.9	<sup>1</sup> / <sub>4</sub>	6.4	3 <sup>3</sup> / <sub>8</sub>	1.50
14223	S24	Center Cut	<sup>7</sup> / <sub>16</sub>	11.0	<sup>3</sup> / <sub>8</sub>	9.5	<sup>5</sup> / <sub>16</sub>	7.9	5 <sup>7</sup> / <sub>8</sub>	2.70
14228	S30	Center Cut	<sup>1</sup> / <sub>2</sub>	12.7	<sup>7</sup> / <sub>16</sub>	11.0	<sup>3</sup> / <sub>8</sub>	9.5	8 <sup>7</sup> / <sub>8</sub>	4.00
14233	S36	Center Cut	<sup>9</sup> / <sub>16</sub>	14.3	<sup>1</sup> / <sub>2</sub>	12.7	<sup>7</sup> / <sub>16</sub>	11.0	13 <sup>1</sup> / <sub>2</sub>	6.10
14238	S42	Center Cut	<sup>11</sup> / <sub>16</sub>	17.5	<sup>5</sup> / <sub>16</sub>	14.3	<sup>1</sup> / <sub>2</sub>	12.7	18 <sup>1</sup> / <sub>4</sub>	8.30

## Replacement Heads

Catalog No.	Description	Weight	
		lb.	kg
18363	S14 Head Assembly	<sup>7</sup> / <sub>8</sub>	1.0
18368	S18 Head Assembly	1 <sup>1</sup> / <sub>4</sub>	1.5
18373	S24 Head Assembly	2 <sup>1</sup> / <sub>4</sub>	2.7
18378	S30 Head Assembly	8 <sup>7</sup> / <sub>8</sub>	4.0
18383	S36 Head Assembly	13 <sup>1</sup> / <sub>2</sub>	6.1
18388	S42 Head Assembly	18 <sup>1</sup> / <sub>4</sub>	8.3

# Cable Cutters



## No. 1380 Cable Cutter

- The Model 1380 Cable Cutter is designed to shear-cut insulated aluminum and copper cable through 1<sup>3</sup>/<sub>8</sub>" diameter and 750 MCM\*. Drop-forged, heat-treated, alloy steel jaws shear cable with minimum distortion of internal wires. Fitted with fiberglass-insulated handles and rubber grips.

\*Not intended for cutting steel or ACSR cable.

Catalog No.	Model No.	Description	Weight	
			lb.	kg
83350	1380	Aluminum and Copper Cable through 1 <sup>3</sup> / <sub>8</sub> Diameter and 750 MCM	4 <sup>1</sup> / <sub>2</sub>	2.0