CUTTING & DRILLING



Accessories

Catalog No.		Description
	76022	11/16" Ratchet Wrench
	76017	RT 3422 Tool Box

Pilots

Catalog No.	Description
76027	Coupon Retaining 1/4" Pilot
76032	Coupon Retaining 3/8" Pilot

Hole Saw Arbors

Catalog No.	Description	
76037	Small Arbor for 5/8" - 13/16" Hole Saws	
76042	Large Arbor for 15/16" - 13/4" Hole Saws	

Shaft Extensions

Catalog No. Description		Description
	76047	Small Shaft Extension for 5/8" - 13/16" Hole Saws
	76052	Large Shaft Extension for 1 5/16" - 13/4" Hole Saws

Valve Adapters

Catalog No. Description				
76057	CTS 3/4" Female			
76067	CTS 1" Female			
76072	CTS 11/4" Female			
76077	CTS 1 ¹ / ₂ " Female			
76082	CTS 2" Female			
76132	NPT 3/4" Male			
76137	NPT 1" Male			
76142	NPT 1 ¹ / ₄ " Male			
76147	NPT 1 ¹ / ₂ " Male			
76152	NPT 2" Male			
83997	³ / ₄ " Mueller 110			
84002	1" Mueller 110			
84007	1 ¹ / ₂ " Mueller 110			
84012	2" Mueller 110			

NPT Sets available only with steel, male valve adapters

RT3422 Tapping Tool

The Model RT3422 is designed for branching pressurized water, steam and natural gas mains. With up to 2" capacity, corrosion-proof design, ability to handle most types of material and lightweight, the Model RT3422 is the tool to meet your tapping needs.

- Easy to use. At only 21", this lightweight and compact tool is great for tight quarters and awkward locations.
- Heavy-Duty Design. Sturdy machined, corrosion-resistant materials for dependable lifelong benefits.
- Built-in bleed valve. Allows for easy purge of chips.
- Independent cutter feed gives the operator total independent control of the cutter feed rotation for optimal saw life.
- Taps a variety of materials. The RT3422 is capable of tapping into steel, cast iron, ductile iron and plastic pipe.
- Versatility. TheRT3422 is capable of tapping mains of water up to 500 psig and steam, air, and natural gas up to 150 psig.
- Coupon retaining bits. Exclusive pilot bits give you the confidence that the coupon will not be dropped in the pipe, preventing medium contamination or possible damage of downstream equipment.

Standard Equipment

The RT3422 sets include RT3422 tapping tool with bleed valve, shaft extensions, heavy-duty hole saw arbors, ¼" and ¾" coupon retaining pilot bits, ratchet wrench, (2) spud wrenches, and 5 valve adapters in a steel tool box. Cutters are available separately.

Specifications

- Tapping Capacity − 3/4 2".
- Mounting Saddle, Welded Nipple, Weld-o-let®, Thread-o-let®.
- Cutter Travel 14".
- Activation Hand Ratchet, Air Ratchet, Right Angle Drill.
- Cutter Feed Rotation of sleeve around an Acme threaded barrel.
- Pressure Water, 500 psig @ 100°F, Steam, Air and Natural Gas, 150 psig @ 370°F

Catalog	Model	Description	Weight	
No.	No.	Description	lb.	kg
75982	RT3422	Tapping Machine Only	16	7.30
75992	RT3422	³ / ₄ " - 2 NPT Set (Male)	53	2.90
91192	RT3422	³ / ₄ " - 2" CTS Set (Flared)	48	3.00

Cutters

Catalog	Model Diameter	Time				
No.	No.	in.	Туре			
52760	M16	5/8	Bi-Metal			
52780	M22	7/8	Bi-Metal			
52800	M29	11/8	Bi-Metal			
52820	M35	13/8	Bi-Metal			
52850	M44	13/4	Bi-Metal			
76267	-	5/8	Steel Shell			
76272	-	7/8	Steel Shell			
76292	-	5/8	CI/DI Bit			
76297	-	7/8	CI/DI Bit			
76317	-	5/8	Plastic Shell			
76322	-	⁷ /8	Plastic Shell			

Cutters

Catalog	Model	Diameter	Tuno
No.	No.	in.	Туре
76292	-	1 ¹ /8	Steel Shell
76297	-	1 ³ /8	Steel Shell
76302	M29	1 ¹ /8	CI/DI Shell
76307	M35	13/8	CI/DI Shell
76312	M44	13/4	CI/DI Shell
76317	-	5/8	Plastic Shell
76322	-	7/8	Plastic Shell
76327	-	1 ¹ /8	Plastic Shell
76332	-	1 ³ /8	Plastic Shell
76337	-	1 ³ / ₄	Plastic Shell

Note: Cutter diameter is 1/8 - 1/4" smaller than the diameter of the hole being cut.