

K-1500G Sectional Machine



For 2" (50 mm) to 10" (250 mm) Drain/Sewer Lines

A gasoline engine makes the powerful K-1500G well-suited for cleaning lines in remote locations where electrical power is unavailable. Cuts through roots fast.

- Unique, easy-to-use, instant-acting cable clutch maximizes operator control.
 - Pull down on the handle and the cable spins at 600 RPM.
 - Release handle, cable stops instantly.
- Comes equipped to use 1¼" (32 mm) cable to clean 3" (90 mm) to 10" (250 mm) lines through 300 feet (92 m).
- 6 HP gasoline engine drives cable via four-speed transmission. Allows the operator to vary the cable spinning speed to fit the application. Forward speeds of 333, 425 and 500 RPM, and a reverse speed of 250 RPM.
- Low-profile, four-wheel cart easily rolls to the job. Guards against machine upset and possible fuel spillage.
- Includes A-1 RIDGID® drain cleaning mitt and operator's manual.



Model K-1500G with C-14 shown above


Machine Options

Catalog No.	Model No.	Description	Weight	
			lb.	kg
44587	K-1500G	Machine Only with A-1 RIDGID Drain Cleaning Mitt, A-12 Coupling Pin Key and A-34-10 Rear Guide Hose, A-369-X 1¼" (32 mm) Jaw Set	190	86,4
48462	K-1500G w/C-14	Machine with Standard Equipment, includes: – Ten Sections Of C-14 Cable, Total 150 Feet (45,7 m) – Three A-8 Cable Carriers – A-1 Left-Hand RIDGID Drain Cleaning Mitt – A-12 Coupling Pin Key – A-34-12 Rear Guide Hose – A-2864 Hex Key – A-3516 Hex Key – A-3 Tool Box – T-2 Heavy-Duty Straight Auger – T-4 Heavy-Duty Funnel Auger – T-6 Retrieving Auger – T-8 Grease Cutter – T-13 Sawtooth Cutter – T-50 Sharktooth Cutter	350	159

For K-1500G Cables, Tools and Accessories, see Page 13.26-13.27.

Machine Dimensions:

Width (wheel to wheel): 26" (66 cm)
Length (incl. kickstand): 28" (71 cm)
Height (ground to top of handle): 38" (97 cm)
Back of handle to front: 49" (124 cm)
Height (ground to top of housing shell): 27" (69 cm)



A-17 Manhole Guide Pipe

Adjusts 7' (2,1 m) to 12' (3,7 m)
supports cables, locks into place quickly.

DRAIN CLEANING



K-1500SP & K-1500G Sectional Machines Cables, Tools and Accessories

Cables, Leaders and Cable Kits

		Catalog No.	Model No.	Description	Weight	
					lb.	kg
7/8" (22 mm)	 Sectional	62275	C-10	15' (4,6 m) All-Purpose Wind Requires A-368-X Jawset	9½	4,3
	 Sectional	25036	C-10 IC	15' (4,6 m) Inner Core Cable Requires A-368-X Jawset	10	4,5
1 1/4" (32 mm)	 Sectional	62280	C-11	15' (4,6 m) Standard All-Purpose Wind. 3/8" (10 mm) Pitch. Good for 4" (110 mm) Traps, 3" (75 mm) - 8" (200 mm) Lines	16	7,3
	 Sectional	24226	C-11IC	15' (4,6 m) Inner Core Cable		
	 Sectional	62285	C-12	15' (4,6 m) Extra-Heavy-Duty Wind. 3/8" (10 mm) Pitch. Recommended For 4" (110 mm) - 10" (250 mm) Long Runs, No 4" (110 mm) Traps	19	8,6
	 Sectional	62295	C-14	15' (4,6 m) Extra-Flexible Wind. 1/2" (13 mm) Pitch. Recommended For 3" (75 mm) - 10" (250 mm) Lines Through Cleanout, No 4" (110 mm) Traps	16	6,8
	 Sectional	62300	C-15	15' (4,6 m) Extra-Flexible Wind. 1/2" (13 mm) Pitch. Recommended For 3" (75 mm) - 6" (150 mm) Lines Good for Traps	12	5,5
	 Leader	63090	T-27	1 1/4" (32 mm) x 25" (63,5 cm) Leader	2¾	1,2

To adapt K-1500 to run 7/8" (22 mm) cable requires A-22A 7/8" (22 mm) Jawset (Cat. No. 59325) and 7/8" (22 mm) Cable Kit.

Accessories

	Catalog No.	Model No.	Description	Weight	
				lb.	kg
	59470	A-8	Cable Carrier 60-Foot (18 m) Capacity 1 1/4" (32 mm)	5½	2,5
	59475	A-9	Cable Carrier 150-Foot (45,7 m) Capacity 1 1/4" (32 mm)	14	6,4
	59415	A-34-10	10-Foot (3,1 m) Rear Guide Hose	13¾	6,2
	59395	A-34-12	12-Foot (3,7 m) Rear Guide Hose	20	9,1
	59400	A-34-16	16-Foot (4,9 m) Rear Guide Hose	26½	12,0
	59300	A-20	8-Foot (2,4 m) Front Guide Hose Assembly	25	11,4
	59205	A-1	Left-Hand RIDGID Drain Cleaning Mitt	1½	0,2
	59295	A-2	Right-Hand RIDGID Drain Cleaning Mitt	1½	0,2
	59360	A-3	Tool Box	5	2,3
	59225	A-12	Coupling Pin Key	1/8	0,1
	59440	A-4	Trap Spoon 30" (76 cm)	1¾	0,8
	59240	A-17	Manhole Guide Pipe	23	10,4
	59320	A-22	1 1/4" (32 mm) Replacement Jawset	¾	0,3

Tools – Fits 1¼" (32 mm) Sectional Cable (C-11, C-12, C-14 and C-15)

	Catalog No.	Model No.	Description	Replacement Blade(s)
	62840	T-1	Straight Auger	—
	61800	T-2	Heavy-Duty Straight Auger	—
	63105	T-3	Funnel Auger	—
	61790	T-4	Heavy-Duty Funnel Auger	—
	63190	T-5	Straight Retrieving Auger	—
	63195	T-6	Funnel Retrieving Auger Run Machine In Reverse	—
	63200	T-7	Hook Auger	—
	63205	T-8	Grease Cutter, 2½" (65 mm)	97920
	63210	T-9	Grease Cutter, 3½" (89 mm)	97925
	62845	T-10	Grease Cutter, 4½" (114 mm)	97865
	59480	T-11	"H" Cutter, 2½" (65 mm)	97800
	59485	T-12	"H" Cutter, 3½" (89 mm)	97945
	61970	T-13	Sawtooth Cutter, 2½" (65 mm)	98070
	61975	T-14	Sawtooth Cutter, 3½" (89 mm)	98075
	61770	T-15A	Expanding Cutter, 4" - 6" (110 - 150 mm)	62970
	61825	T-15B	Expanding Cutter, 6" - 8" (150 - 200 mm)	62980
	61960	T-16	Spiral Bar Cutter, 4" (110 mm)	97855
	61850	T-17	Spiral Bar Cutter, 6" (150 mm)	97955
	61855	T-18	Spiral Bar Cutter, 8" (200 mm)	97960
	59625	T-21	Spiral Sawtooth Cutter, 2½" (65 mm)	97965
	63075	T-23	Spiral Sawtooth Cutter, 3" (75 mm)	97970
	63085	T-23	Spiral Sawtooth Cutter, 4" (110 mm)	97850
	59765	T-24	4-Blade Cutter, 2½" (65 mm)	97940
	59770	T-25	4-Blade Cutter, 3½" (89 mm)	97975
	59775	T-26	4-Blade Cutter, 4½" (114 mm)	97805
	59780	T-26A	4-Blade Cutter, 5½" (140 mm)	97980
	63110	T-31	Chain Knocker, For 3" - 4" Pipe (75 - 110 mm)	97985
	63115	T-32	Chain Knocker, For 6" Pipe (150 mm)	97990
	63120	T-33	Chain Knocker, For 8" Pipe (200 mm)	97995
	63145	T-38	Flue Brush, 1½" (40 mm)	—
	63150	T-39	Flue Brush, 2" (50 mm)	—
	63155	T-40	Flue Brush, 2½" (65 mm)	—
	63160	T-41	Flue Brush, 3" (76 mm)	—
	63165	T-42	Flue Brush, 3½" (89 mm)	—
	63170	T-43	Flue Brush, 4" (110 mm)	—
	63175	T-44	Flue Brush, 4½" (114 mm)	—
	63240	T-45	Flue Brush, 5" (127 mm)	—
	63180	T-46	Flue Brush, 5½" (140 mm)	—
	63145	T-47	Flue Brush, 6" (150 mm)	—
	98030	T-50	Three Blade 3 - 4 - 5" (75 - 110 - 127 mm)	See Below
	98035	T-50-1	Sharktooth Cutter, 3" (75 mm)	98005
	98040	T-50-2	Sharktooth Cutter, 4" (110 mm)	98010
	98045	T-50-3	Sharktooth Cutter, 5" (127 mm)	98015