

### **CODE NUMBER**

70061001

### **DESCRIPTION**

SU-7006 Urinal and ROYAL 186 Flushometer.

### **COMPONENTS**

Flushometer: Code 3012636Urinal: Code 1107006

### **DETAILS**

• Flush Volume: 1.0 gpf (3.8 Lpf)

• Nominal Dimensions: 14  $^3$ /4"  $\times$  14 3/16"  $\times$  23  $^1$ /2" (375  $\times$  360  $\times$  597mm)

# **FLUSHOMETER FEATURES**

- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Sweat Solder Adapter with Cover Tube & Cast Wall Flange with Set Screw
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Diaphragm, Handle Packing and Vacuum Breaker to be molded from PERMEX® Rubber Compound for Chloramine Resistance
- ADA Compliant Metal Oscillating Non-Hold-Open Handle 3/4" I.P.S. Screwdriver Bak-Chek® Angle Stop w/ Free Spinning Vandal Resistant Stop Cap

# **FIXTURE FEATURES**

- White Vitreous China
- Washdown flushing action
- Integral flushing rim
- ¾" I.P.S. top spud inlet
- 2" NPT outlet flange
- Vandal resistant strainer assembly included
- All mounting hardware included
- 100% factory flush tested



## **COMPLIANCES & CERTIFICATIONS**













(ADA Compliant, BAA Compliant, cUPC Green Certified, EPD, HPD, WELL Building Standard)

### **DOWNLOADS**

- Small Spud Urinal Installation Instructions
- Royal Exposed Installation Instructions
- Sloan Diaphgram Chart (SP) Repair and Maintenance Guide
- SS/ST/SU/WETS/WEUS Fixtures Repair and Maintenance Guide
- Additional Downloads

# **NOTES**


All information contained within this document subject to change without notice.


# WARRANTY

View Warranty Information



# **ROUGH-IN**





Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com